GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS/ans/school hors/ MO2/2265

Dated: 3 1/12/15

FIRE SAFETY CERTIFICATE

Issued on....at New Delhi by

(Dr. G.C. Misra)

Chief Fire Officer

Ph -011- 23414333

07 · 884

To,

The H.M,

Ch. Braham Singh Memorial Public School, A-4, Ankur Enclave, Karawal Nagar, Delhi-94 Copy to:-.

The Director of Education,

East Delhi Municipal Corporation,

419, Udyog Sadan, Patparganj Industrial Area, Delhi-92

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: Ch. Braham Singh Memorial Public School, A-4, Ankur

Enclave, Karawal Nagar, Delhi-94

2. Building is comprised of

: G+1

3. Type of Occupancy

: Educational

4. Type of Case

: Renewal

5. Details of Previous NOC

: F.6/MS/DFS/06/2978 dated 06.10.2006

6. Fire Safety direction letter No

: Old requirements (Circular No. 262-362 dated 17.01.2005)

7. Date of Inspection

: 16.12.2015

8. Name of the Inspecting Officers: : Suresh Singh (ADO)

9. Name of the designation of Officer

from the building side

: H.M : 2000

10. Year of Construction 11. Applicant's letter No

: dated 26.11.2015

	Minimum Standards on fire safety	Old	Provided at Site	Remarks		
S.No	requirements as per circular no. 262-362	Requirement	Trovided de site	MR/NMF		
	dated 17.01.2005	Requirement		,		
1	Access to building					
1	Road width	6 m	6 m	MR		
	Gate width	N.A.	N.A.	N.A.		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement of	API 50.000 00				
	a. Number of Staircases					
	Upper Floor	1 no.	2 no.	MR		
	Basement	N.A	N.A.	N.A.		
	B. Width of Staircases		¥			
	Upper Floor	1.5 m	1.02 m, 0.80 m	MR		
	Basement	N.A	N.A.	N.A.		
	c. Protection of exits	N.A	N.A.	N.A.		
	Fire check door	N.A.	N.A.	N.A.		
	Pressurization	N.A.	N.A.	N.A.		
	e. No. of continuous staircases to terrace	1 no.	1 no.	MR		
	g. Width of Corridor	1.5 m	1.5 m	MR		
	h. Door Size	1 m	1 m	MR		
3	Compartmentation					
	Fire check door	N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	N.A.	N.A.	N.A.		
	Upper floor	N.A.	N.A.	N.A.		

5.	Fire Extinguisher							
	Total numbers	04 no.	06 no.	MR				
	types	CO ₂ & ABC	CO ₂ & ABC	MR				
	IS marking	ISI marked	ISI marked	MR				
6	First-aid-Hose Reels.							
	Total numbers of each floor	01 no.	01 no.	MR				
	Length of hose reel hose	30 m	30 m	MR				
	Nozzle diameter	5 mm	5 mm	MR				
7	Automatic fire detection and alarming system.							
	Type of detectors	N.A.	N.A.	N.A.				
	Location of main panel	N.A.	N.A.	N.A.				
	Location of repeater panel	N.A.	N.A.	N.A.				
	Alternate source of power	N.A.	N.A.	N.A.				
	Hooters's location	N.A.	N.A.	N.A.				
8	MOEFA	N.A.	NA	NA				
9	Public address System.	N.A.	NA	NA				
10	Automatic Sprinkler System.							
	basement	N.A.	N.A.	N.A.				
	upper floor	N.A.	N.A.	N.A.				
	sprinkler above false ceiling	N.A.	N.A.	N.A.				
11	Internal Hydrants							
	size of riser/down-comer	N.A.	N.A.	N.A.				
	Number of hydrants per floor	N.A.	N.A.	N.A.				
	Hose Box	N.A.	N.A.	N.A.				
12	Yard Hydrants.							
	Total number of hydrants	N.A.	N.A.	N.A.				
	Hose Box	N.A.	N.A.	N.A.				
13	Pumping Arrangements.							
	Ground Level	N.A.	N.A.	N.A.				
	Discharge of main Pump	N.A.	N.A.	N.A.				
	> Head of Main Pump	N.A.	N.A.	N.A.				
	Number of main pumps	N.A.	N.A.	N.A.				
	Jockey pump out put	N.A.	N.A.	N.A.				
	Jockey pump head	N.A.	N.A.	N.A.				
	Standby pump out put	N.A.	N.A.	N.A.				
	Standby pump Head	N.A.	N.A.	N.A.				
	Auto Starting /Manual stopping	N.A.	N.A.	N.A.				
	Pump House Access	N.A.	N.A.	N.A.				
	Terrace Level							
	Discharge of pump	220 LPM	220 LPM	MR				
	Head of the Pump	40 m	40 m	MR				
	> Power supply	Required	Provided	MR				
	Auto Starting of pump	Required	Provided	MR				

14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity	N.A.	N.A.	N.A.		
	Draw-off connection	N.A.	N.A.	N.A.		
	Fire service inlet	N.A.	N.A.	N.A.		
	Access to tank	N.A.	N.A.	N.A.		
	Overhead Tank capacity	2500 Liters	2500 Liters	MR		
15	Exit Signage.	N.A.	N.A.	N.A.		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car Firemen's grounding switch Lift Signage	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
17	Standby power supply	N.A.	N.A.	N.A.		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	N.A.	N.A.		
	Flow switch panel	N.A.	N.A.	N.A.		
	PA system panel Batter backup Building Floor Plans	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the NOC issued vide letter no. F.6/MS/DFS/06/2978 dated 06.10.2006 under the circular No. 262-362 dated 17.01.2005 it is recommended to grant Fire Safety Certificate.

Sengh 17.12.15

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

Dy CFO (RIDZ)

Dy CFO (RIDZ)

Dy CFO (RIDZ)