GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ MO2/2261

Dated :-- 31 / 12/4-1

FIRE SAFETY CERTIFICATE

Certified that the M/S K. C. Plaza located at 5588, Basant Road, Pahar Ganj, New Delhi comprised of Basement + Ground + 03 Upper floors, Basement (Storage), Ground floor (Reception + 10 guest rooms + 01 office + 01 dining room), 1st floor (12 guest rooms), 2nd floor (12 guest rooms) and 3rd floor (03 staff rooms), total 34 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/4197 dated 08/11/12. The premises was re-inspected by the officer concerned of this department on 22/12/15 in the presence of Sh. Vijay Bhatt (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 34 guest rooms only with effect from ----- 21/12/15 ----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 3.1-1-1---at New Delhi by.

(**Dr. G. C. Misra**) Chief Fire Officer Ph-011-23414333

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. letter No. 2495/Joint C.P./Lic.(H) dated 20/11/2015.
- Sh. Vijay Bhatt (Manager),
 M/S K. C. Plaza located at 5588, Basant Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building M/S K. C. Plaza located at 5588,

Basant Road, Pahar Ganj, New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

B + Gr. + 03 Upper floors (total 34 Guest rooms)

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2012/4197 dated

08/11/12.

5. Fire safety directives No.-

6. Date of inspection:-

N/A 22/12/15

7. Name of the inspecting officer:-

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

Sh. Vijay Bhatt (Manager)

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

No. 2495/Joint C.P./Lic.(H) dated 20/11/2015.

Old Case

				Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety	Requirement Existing	Provided at site PSS	Remarks MR/NMR	
	U/R 33				
1.	Access to Building		10	MD	
	1) Road width	N/A	12 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 Nos.	02 Nos.	MR	
	2. Basements	01 Nos.	01 Nos.	MR	
	B. Width of staircase) (D)	
	1. Upper floors	0.80 mtr.	1.45 to 1.50 Mtr. & 0.98 to 1.05 mtr.	MR	
	2. Basements	0.80 mtr.	0.98 Mtr.	MR	
	C. Protection of exits	27/1	21/4	NI/A	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace		27/4	NI/A	
	E. Width of corridor	N/A	N/A	N/A MR	
	F. Door size	1 mtr.	1 mtr.	IVIK	
3.	Compartmentation			21/4	
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	Exhaust fan	MR	
	2) Upper floors	12 a/c per hour	Natural	MR	
5.	Fire Extinguishers				

				1.00		
	1) Total numbers	14 Nos.	14 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6	First-Aid Hose Reel		0.1	1,6		
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & A			DI/A		
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor					
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
14	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping					
	2) Terrace level		al .	1		
		225 LPM	225 LPM	MR		
	a) Discharge of pump	223 LI IVI	And the second s			
		30 mtr.	30 mtr.	MR		
	b) Head of pump			MR MR		
	b) Head of pump c) Power supply	30 mtr.	30 mtr.			
14.	b) Head of pumpc) Power supplyd) Auto starting of pump	30 mtr. Required Required	30 mtr. Provided	MR		
14.	b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for F 1) Under ground tank	30 mtr. Required Required	30 mtr. Provided	MR		
14.	b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for F	30 mtr. Required Required Vire Fighting	30 mtr. Provided Provided	MR MR		

	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
e .	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
1	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Systeries Risk, if any:	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/GH/2015/2165 dated 26/10/15 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/4197 dated 08/11/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

