GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2016/ 52 37

Dated: 05/61/16

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Ambika Deluxe** located at 7A/68, WEA, Karol Bagh, New Delhi-110005 is comprised of Ground floor plus two upper floors, using ground floor as other property, first floor having reception & 06 guest rooms, second floor having 07 guest rooms (Total 13 guest rooms), a pantry for staff with staff room on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2012/3949 dated 23.10.2012 owned/ occupied by Mrs. Maninder Kaur (Owner). The guest house building was re- inspected by the officers concerned of this department on 23.12.2015 in the presence of Sh. Santosh Jha (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on. 6.5.1.9.1.16. at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- The Joint Commissioner of Police (Lic.)
 1st floor, P.S., Defence Colony, New Delhi.
 (Re. No.2710/Joint C.P./Lic.(H), Dated 16.12.2015)
- Mrs. Maninder Kaur (Owner) Hotel Ambika Deluxe, 7A/68 WEA, Karol Bagh, N.D-110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	INSPE	CTION REPORT			
	 Name & address of the building Type of Occupancy 	Hotel Andina	alterna Folian I	i Lima da la	
		Residential C	Collect Harry	VEA, Karol Bagh,	
	2. The or case	: New Case/Rene	wal	N.O-C	
	 Details of Previous NOC 	: Letter No. F.6//	SFS/MS/GH/2012/	20/ -Data 22 /- 2	
	5. Fire Safety directives letter No	:	- SINISIMIJADIAJ.	1949Date 23.10.10	
	Date of inspection	23.12.2015 D.O.S.K. Tomar & A.D.O. P.S. Dahiya			
	 Name of Inspecting Officer 				
	8. Name and designation of officer	S	na p 17.0.0	F.S. Dahiya	
	From the building side		ish The CMan		
	Year of Construction	: Before a	2001	ger	
	10. Applicant's letter No.	2710 Joint C	·P/LIC: CH) dat	led 16:12. 2015	
S.	Minimum Standards on fire	NBC/ BBL	Provided at	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1.	Access to building			TARRY TATALLY	
T T T T T T T T T T T T T T T T T T T	 Road width 	Accessible	09mtr	MR	
	 Gate width 	-	←	-	
	 Width of internal road 			1	
2.	Number, Width, Type & Arrangemen	t of Exits			
	a. Number of staircases				
	Upper Floors	One	Δ.		
	 Basements 	Une	One	MR	
	b. Width of staircases		Photosocial and the state of th	No Basement	
	 Upper Floor 		loocms to locms	Dag 44 / 6	
	 Basements 		Tocking to Hocking	MR, Old Case	
	c. Protection of exits			No Basement	
	 Fire check door 				
	pressurization	The second section of the second seco			
	d. No. of continuous staircases to		-		
1	terrace		<u> </u>	PRINT THE Second Page Continues on the Second Continues of the Second Continues on the Second Continue	
Account to the same	e. Width of Corridor		One		
	f. Door Size		114cms		
3.			87cms x 196cms	:	
3.	Compartmentation				
	 Fire check door 				
	 Sealing of electrical shafts 		0	Annual region of the second se	
	 Fire Rating of shaft door 		Sealed		
	 Water Curtain 				
	 Fire Dampers 		•		
4.	Smoke Management System			-	
	* Basements				
		30 a/c per	-	No Basement	
-	 Upper floors 	hour	Natural Ventilation	Makhadan aya dan aya dan aya dan aya da ay	
		The state of the s	Jara venpiape	n MR	

(III)

	M/24			
		12 a/c per hour		
5	Fire Extinguishers			
	 Total numbers 	Two ateach Floo	P 0	
	Types	Co2, W62	Provided	MR
-	 IS marking 	ISI marked	-do-	MR
6	First-Aid Hose Reels		151 Marked	MR
	 Total numbers on each floor 	One	Provided	A . C
	Length of hose reel hose	30 m	- do -	MR
	 Nozzle diameter 	5 mm	- do-	MR
7	Automatic fire detection and alarming	system	- 00	I. MR
	 Type of detectors 			
	 Location of Main Panel 	_		+
	 Location of Repeater Panel 			+
	 Alternate source of power 			
2 1.20 00000000	 Hooters' Location 			
8.	MOEFA	NIR	Pravillad	
9.	Public Address System	NIR	Psovided - do -	MR
10.	Automatic Sprinkler System		7 00 -	MR
	 Basement 		<u></u>	N/a Qa .
	 Upper Floor 			No Basement
	 Sprinkler above false ceiling 		1	
11.	Internal Hydrants			
	 Size of riser/down-comer 	S	The second secon	-
	 Number of hydrants per floor 		the state of the s	
	 Hose Box 			
		Construction of the second of		7
12.	Yard Hydrants	2		
12.	Yard Hydrants Total number of hydrants		J.	
	Yard Hydrants Total number of hydrants Hose Box		, , , , , , , , , , , , , , , , , , ,	
12.	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements		,	
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level		J.	
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual			
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put			

7A/68, WEA, Karol Bagh, New Delli - 110005.

	> Pump House Access		1	€ 1.		
	Terrace level	1 —		-		
	Discharge of pump					
	Head of the pump	N/R	450 LPM	MR		
	Power Supply	NIR	30 M Provided	MR		
		Reserve	Provided	MR		
* · · · · · · · · · · · · · · · · · · ·	Auto Starting of pump					
14.	Captive Water Storage for fire fighting					
	 Underground tank capacity 	-				
	Draw-off connection			-		
	Fire service inlet		-	-		
	Access to tank			-		
	 Overhead Tank capacity 	lac-r	6000 Ltr	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	 Pressurization of Lift Shaft 		•	Not in use		
	 Pressurization of Lift lobby 			- do -		
	 Communication In lift Car 					
	 Fireman's Grounding Switch 			-do -		
	Lift Signage			-do -		
			_	, -do -		
17.	Standby power supply	Required	D.G. Set of 18 KVA	MR		
18.	Define Ann		2			
IO.	Refuge Area. > Total Area	T				
	> Location		-	-		
	Location	_	2	•		
19.	Fire Control Room					
	Detector System Panel	_				
	Flow Switch Panel			i i		
	PA System Panel			• 1		
	Batter backup	Na	_			
	 Building Floor Plans 					
20.	Special Fire Protection System for		-			
	Protection of special Risks, if any:			-		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. FG/DFS/MS/GH/20/2/3949 dated 23.10.20/2 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S. K. Tomar

Designation Divisional Officer

Signature of Inspecting Office

Name P.S. Dahiya

Designation Appth. Divisional Officer

Cfo Couth Chi