GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ MD 2 / 104 Dated: 1-4/01/16.

Certified that the Raj Deluxe Guest House located at 8467, Arya Nagar, Pahar Ganj, New Delhi-110055.comprised of Ground + 5 Upper Floors (Ground floor – reception + office + 01 guest rooms, 1st floor to 4th floor 03 guest rooms at each floor - total 13 guest rooms) 5th floor staff room found sealed was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/4168 dated 07/11/2012. The premise was re-inspected by the officer concerned of this department on 06/01/16 in the presence of Mr. Sushil (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 13 guest rooms only as above with effect from 14/16/-------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, mentioned below.

Issued -14-01-16 New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service

Ph: - 011-23414333

Copy to:- (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) Raj Deluxe Guest House.

8467, Arya Nagar, Pahar Ganj, New Delhi-110055.

(3) The Commissioner, NDMC, Civic Centre, New Delhi – With the request to get the height measured and apprise this office.

Conditions:-

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1.Name & address of the building:-

Raj Deluxe Guest House,8467,Arya Nagar,

Pahar Ganj, New Delhi-110055. Residential Group A-1 Ground

2. Type of occupancy:-

+ 5 Upper Floors.(13 guest rooms) Renewal

3. Type of case:-

No. F6/MS/DFS/GH/2012/4168 dated

4. Details of previous FSC:-

07/11/2012.

5. Fire safety directives No.-

N/A

Date of inspection:-

06/01/16

7. Name of the inspecting officer:-

D.O. Gurmukh Singh

8. Name & designation of officer From the building side:-

Mr. Sushil (Manager)

9. Year of construction:-

2001

Nil. Dated 28/12/15

No.		Requirement (PSS Area)	Provi	ded at site	Rema MR/I			
	Access to Building			900	MR	-		
	1) Road width	N/A	4 m		N/A			
	2) Gate width	N/A	N/A		N/A			
	2)Width of internal road	N/A	N/A		IN/A			
2.	Number, Width Type & Arrangement of Exits							
2.	A. Number of staircases		- 1/2	1.	MR			
	1. Upper floors	01 No.	01 1		N/A			
	2. Basements	N/A	N/A		19(2)	_		
	B. Width of staircase		05	ems.	MR			
	1. Upper floors	80 cms.	N/A	71115.				
	2. Basements	N/A	18/7	1				
	C. Protection of exits	27/4	N/A	1	N/A	1		
	1. Fire check door	N/A	N/A		N/A			
	2. Pressurization	N/A	N/A		N/A			
	D. No. of continuous staircase to terrace	N/A		N/A		N/A		
	E. Width of corridor	N/A			MR			
	F. Door size	1 mtr.	1 mtr.		171)			
3.	Compartmentation		NIA		N/	Δ		
	1) Fire check door	N/A	-	N/A		N/A		
	2) Sealing of electrical shafts	N/A		N/A N/A		N/A		
	3) Fire rating of shaft door	N/A		/A	N/A			
	4) Water curtain	N/A		/A	N/A			
	5) Fire Dampers	N/A	14	//1				
4.	Smoke Management System	tem		N/A		N/A		
	1) Basements	30 ACPH		Natural		MR		
	2) Upper floors	IZ ACPH		1,000,00				
5.	Fire Extinguishers	10 Nos.		10 Nos.		MF		
	1) Total numbers	ABC & CO2		ABC &CO2		MF		
	2) Types	Abcacc	J. M.					

-N/20-

3) ISI marking	Rec	quired	Provided	M	R	
First-Aid Hose Reel					MR	
1)Total number at each	01	10.	01 no.	IV.	IK	
				MR		
	30	O III.			MR	
2) Mozzle diameter			5 mm.	IV	IK	
Automatic Fire Detection & A	157/6	IX	I/A			
1) Type of detectors	N/A				N/A N/A	
2) Location of main panel			The state of the s	N/A		
3) Location of repeater panel	The second secon			N/A N/A		
4) Alternate source of power	N/	A		-	N/A	
5) Hooter's Location	The second secon			N/A N/A		
					and the same of th	
	Re	equired	Provided	MR		
Automatic Sprinkler System					N/A	
1) Basement	N	/A				
	N	/A		-	N/A	
3) Sprinkler above false	N	/A	N/A		N/A	
Internal Hydrants					NT/A	
1) Size of riser/down-comer	N	I/A			N/A	
2) Number of hydrants per	N	/A	N/A		N/A	
1 2 2				-	27/4	
	N	N/A	N/A		N/A	
Vord Hydrants					2.71.6	
1) Total number of hydrants	1	V/A	N/A		N/A	
	1	N/A	N/A		N/A	
1) Ground level		N/A	N/A		N/A	
			N/A		N/A	
		(* W.S.E.			- 1	
bump 1) Head of main numn		N/A	N/A		N/A	
A CONTRACTOR OF THE PARTY OF TH	mn	and the same of th	N/A		N/A	
			N/A		N/A	
d) Jockey pump bood	41		N/A	93	N/A	
e) Jockey pump nead	out	A STATE OF THE PARTY OF THE PAR	N/A		N/A	
	d		N/A		N/A	
g) Stand by pump nea	u ual		N/A		N/A	
		1872				
stopping						
		425 I PM	425 LPM		MR	
					MR	
		The state of the s			MR	
c) Power supply		recourted			MR	
			11011000		I.	
. Captive Water Storage for	rFir	e rigning	N/A		N/A	
Under ground tank	<	N/A	TWEE			
	1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System/Intercom Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump c) Number of main pu d) Jockey pump out pu e) Jockey pump head f) Stand by pump out pu e) Jockey pump head f) Stand by pump head f) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pu Captive Water Storage for	First-Aid Hose Reel 1)Total number at each floor 2) Length of hose reel hose 30 3) Nozzle diameter 5 n Automatic Fire Detection & Alarm 1) Type of detectors N/ 2) Location of main panel N/ 3) Location of repeater panel N/ 4) Alternate source of power N/ 5) Hooter's Location N/ MOEFA Public Address System/Intercom Automatic Sprinkler System 1) Basement N/ 2) Upper floors N/ 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/ 2) Number of hydrants per floor 3) Hose box N/ Yard Hydrants 1) Total number of hydrants 2) Hose box N/ Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump head f) Stand by pump output e) Jockey pump head f) Stand by pump output g) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump c) Power supply	First-Aid Hose Reel 1)Total number at each floor 2) Length of hose reel hose 30 mtr. 3) Nozzle diameter 5 mm. Automatic Fire Detection & Alarming System 1) Type of detectors N/A 2) Location of main panel N/A 3) Location of repeater panel N/A 4) Alternate source of power N/A 5) Hooter's Location N/A Public Address Required System/Intercom Automatic Sprinkler System 1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A 2) Number of hydrants per floor 3) Hose box N/A Yard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level N/A a) Discharge of main pump N/A c) Number of main pump N/A d) Jockey pump out put N/A f) Stand by pump output N/A f) Stand by pump head N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump Aequired d) Auto starting of pump Required Captive Water Storage for Fire Fighting	First-Aid Hose Recl 1)Total number at each floor 2) Length of hose reel hose 30 mtr. 3) Nozzle diameter 5 mm. Automatic Fire Detection & Alarming System 1) Type of detectors N/A N/A 2) Location of main panel N/A N/A 3) Location of repeater panel N/A N/A 4) Alternate source of power N/A N/A 5) Hooter's Location N/A N/A Public Address Required Provided System/Intercom Automatic Sprinkler System 1) Basement N/A N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A N/A 3) Hose box N/A N/A Yard Hydrants 1) Total number of hydrants N/A N/A 2) Hose box N/A N/A Pubping Arrangement 1) Ground level N/A N/A 1) Stand by pump out put N/A N/A 1) Stand by pump head N/A N/A 1) Stand by pump head N/A N/A 1) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump Aequired Cantive Water Storage for Fire Fighting N/A N/A N/A N/A N/A N/A N/A N/A	3) ISI marking Required	

-N121-

	a) Draw-off connection	N/A	N/A	N/A
	 b) Fire service inlet 	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	 b) Pressurization of lift lobby 	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	 a) Detector system panel 	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	for Protection o	f special Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/MS/DFS/GH/2012/4168 dated 07/11/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

Dy CAO (NDZ)

