## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/NDZ/98
FIRE SAFETY CERTIFICATE

Dated :- 14/6//6

Certified that the Topaz Guest House located at 9140-41, Multani Dhanda, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (reception + 03 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor) and terrace floor (lift room + Mumti + 01 store), total 21 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/4164 dated 07/11/12. The premises was re-inspected by the officer concerned of this department on 23/12/15 in the presence of Sh. G.S. Panwar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service, Rules 2010, printed below

Issued - 17-10-1-16--at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333 Ofe

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. Sh. G.S. Panwar (Manager),

Topaz Guest House located at 9140-41, Multani Dhanda, Pahar Ganj, New Delhi. Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

## **INSPECTION REPORT**

1. Name & address of the building:-Topaz Guest House located at 9140-41,

Multani Dhanda, Pahar Ganj, New Delhi 2. Type of occupancy:-

Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 21 Guest rooms) 3. Type of case:-

Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2012/4164 dated

07/11/12. 5. Fire safety directives No.-N/A

6. Date of inspection:-23/12/15

7. Name of the inspecting officer:-Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:-Sh. G.S. Panwar (Manager) 9. Year of construction:-2009

10. Applicant's letter No:-No. Nil dated 14/12/2015.

	rippineant s letter 140	No. Mil date	1 14/12/2015.	014 0-	
S.No.	Minimum Standards on fire	Requirement	Provided at site	Old Case Remarks	
	Prevention and fire safety U/R 33	Existing	PSS PSS	MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr. approx	N/A	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases	8			
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase			14/11	
	1. Upper floors	0.80 mtr.	1.25 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits			11/21	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	01	01	MR	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation	The transfer of the transfer o			
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 a/c per	Natural	MR	
		hour			
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
	First-Aid Hose Reel				
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	

7.	Automatic Fire Detection & Alarming System			
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
0	MOEFA	N/A	N/A	N/A
8. 9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	Tiovided	17111
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
		IN/A	14/21	11771
11	ceiling			
11.	Internal Hydrants	N/A	N/A	N/A
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	IN/A	IN/A	14/71
	floor	NI/A	N/A	N/A
10	3) Hose box	N/A	11/71	INIA
12.	Yard Hydrants	NI/A	NI/A	N/A
	1) Total number of hydrants	N/A	N/A	N/A N/A
	2) Hose box	N/A	N/A	IN/A
13.	Pumping Arrangement		27/4	27/4
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			27/4
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level			
	a) Discharge of pump	225 LPM	225 LPM	MR
*	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for F	ire Fighting		
1	Under ground tank	N/A	N/A	N/A
	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	2500 ltr.	2500 ltr.	MR
	capacity			*
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		7	
10.		N/A	N/A	N/A
	a) Pressurization of lift	18/73	1 1/ / 1	1 11 1
	shaft	Dogwined	Provided	MR
	b) Pressurization of lift	Required	Flovided	IVIIX
A	lobby	Daguinal	Provided	MR
	c) Communication in	Required	Provided	IVIIX
	lift car			

N		0
	1	

	d) Fireman's switch	Required	Provided	110
	e) Lift signage	N/A	N/A	MR
17.	Stand by Power Supply	Required		N/A
18.	Refuge Area	-	Provided	MR
		N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A
			IN/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst	om Co. D		IN/A
	Special Fire Protection System for Protection of special Risk, if any:			NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/4164 dated 07/11/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

cod(NDZ) Oregon thours north flow.