GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ H02 /177

Dated: 27/1/16

FIRE SAFETY CERTIFICATE

Certified that the Galaxy International Guest House located at 8487, Arakashan Road, Pahar Ganj, New Delhi. comprised of Ground + 3 Upper Floors (ground floor – reception + 02 guest rooms, 1st floor & 2nd floor 03 guest rooms at each floor & 3rd floor 02 guest rooms total 10 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/3802 dated 17/10/2012. The premise was re-inspected by the officer concerned of this department on 19/01/16 in the presence of Mr. Sonu Pathak (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 10 guest rooms only as above with effect from —27/1-1/16----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, mentioned below.

Issued - 27/1/16 ---- at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to:- (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,Galaxy International Guest House,8487, Arakashan Road, Pahar Ganj, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1.Name & address of the building:-

Galaxy International Guest House,8487 ,Arakashan Road ,Pahar Ganj,New Delhi.

2. Type of occupancy:-

Residential Group A-1 Ground + 3 Upper Floors.(10 guest rooms)

3. Type of case:-

Renewal

4. Details of previous FSC:-

No. F6/DFS/MS/2012/GH/3802 dated 17/10/2012.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

19/01/16

7. Name of the inspecting officer:-

A.D.O. Manoj Kumar Sharma.

8. Name & designation of officer From the building side:-

Mr. Sonu Pathak (Manager)

9. Year of construction:-

2001

10. Applicant's letter No:-

106/Joint C.P./Lic. (H) dated 13/01/16

O1d	Case
Olu	Casc

					Old	Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement (PSS Area)	Provid PSS	led at site		narks /NMR	
1.	Access to Building						
	1) Road width	N/A	06 m	tr.	MR		
	2) Gate width	N/A	N/A		N/A	253	
	3) Width of internal road	N/A	N/A		N/A	A	
2.	Number, Width Type & Arrang	gement of Exits					
2.	A. Number of staircases						
	1. Upper floors	01 Nos.	01 No	S.	MR		
	2. Basements	N/A	N/A	N/A		4	
	B. Width of staircase						
	1. Upper floors	80 cms.		25 cms.		2	
	2. Basements	N/A	N/A	N/A		A	
	C. Protection of exits						
	1. Fire check door	N/A	N/A			N/A	
	2. Pressurization	N/A	N/A		N/A		
	D. No. of continuous	N/A	N/A		N/	A	
	staircase to terrace		3.714		NT/	A	
	E. Width of corridor	N/A	N/A		N/		
	F. Door size	1 mtr.	1 mtr.		M	K	
3.	Compartmentation	77					
	1) Fire check door	N/A	N/A		N/	2000	
	2) Sealing of electrical shafts	N/A	N/A		N/A N/A		
	3) Fire rating of shaft door	N/A	N/A			/A	
	4) Water curtain	N/A	N/A			/A /A	
	5) Fire Dampers	N/A	N/A		IN.	A	
4.	Smoke Management System	an CDIT	N.T	1 / A		N/A	
	1) Basements	30 ACPH	N/A Natural			MR	
	2) Upper floors	12 ACPH	IN IN	atural		IVIIC	
5.	Fire Extinguishers	00 M	0	9 Nos.		MR	
	1) Total numbers	09 Nos.		BC &CO2)	MR	
	2) Types	ABC & CO2	L = I	IDC &CO2		14117	

	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			2
	1)Total number at each floor	01 no.	01 no.	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	5 mm.	5 mm.	MR
7.	Automatic Fire Detection & A			a
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling		A CONTRACTOR OF THE CONTRACTOR	
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	A	77 217 1119 - 25	
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
12.	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
13.	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	11/12		and estimated the state
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outpu		N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual		N/A	N/A
	stopping	17/21	1.77.2	A SERVE
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 Mtr.	30 Mtr.	MR
	c) Power supply	Required	Provided	MR
			Provided	MR
1.4	d) Auto starting of pum Captive Water Storage for F	ire Fighting	TTOVIGO	11111
14.		N/A	N/A	N/A
	1) Under ground tank capacity	11/17	14/17	1.77.1
		N/A	N/A	N/A
	a) Draw-off connection	1N/F1	1 4/ 2 %	11/11

	b) Fire service inlet	N/A	N/A	N/A	
		N/A	N/A	N/A	
	c) Access to tank d) Over head tank	2,500 ltrs.	2,500 ltrs.	MR	
	capacity	Required	Provided	MR	
5.	Exit Signage.	Required			
6.	Provision of Lifts.		N/A	N/A	
	a) Pressurization of lift shaft	N/A			
	b) Pressurization of lift	N/A	N/A	N/A	
	lobby	4. 40.00		N/A	
	c) Communication in	N/A	N/A	N/A	
	lift car	NT/A	N/A	N/A	
	d) Fireman's switch	N/A N/A	N/A	N/A	
	e) Lift signage	Required	Provided	MR	
17.	Stand by Power Supply		N/A	N/A	
18.	Refuge Area	N/A		N/A	
	Total area location	N/A	N/A	14/11	
19.	Fire Control Room			N/A	
17.	a) Detector system	N/A	N/A	N/A	
	panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A N/A	N/A	N/A	
	d) Battery backup	11/11		10	
	Duilding floor plan	N/A	N/A	N/A	
	e) Building floor plan		on of special Risk. if	N/A	
20.	Special Fire Protection System for Protection of special Risk, if N/A				
	any:			and found	

The fire protection system provided in the guest house were tested, checked at random and found

functional at the time of inspection. In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/2012/GF/3802 dated 17/10/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

> Manoj Kumar Sharma Assistant Divisional Officer