GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ MD2 / 185

Dated : 29 / 0/ /6-

FIRE SAFETY CERTIFICATE

Certified that Hotel Shivish International located at 7875, Arakashan Road, (Opp. Ajanta Hotel), Pahar Ganj, New Delhi-110055.comprises of Basement, Ground + 04 Upper floor – basement – storage, Ground floor - reception + 01 guest room, 1st floor to 4th floor 02 guest rooms at each floor total 09 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1246 dated 14/07/2015. The premises was re-inspected by the officer concerned of this department on 21/01/2016 in the presence of Mr Devender Uppal and found that the said guest house building have added 03 more rooms at 1st floor to 3rd floor 01 guest room at each floor. Now the floor wise occupancy at basement – storage, Ground floor - reception, 1st floor to 4th floor 03 guest rooms at each floor- total 12 guest rooms and have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 12 guest rooms only with effect from

28-1-04-1-----2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on ... 12. f.o.f. ... at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Le

MI

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. Hotel Shivish International, 7875, Arakashan Road, (Opp. Ajanta Hotel), Pahar Ganj, New Delhi-110055.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

			INSPECTION R	EPC	PAT
T	0 11	 23			

1. Name & address of the building

Hotel Shivish International,7875,Arakashan
Road,(Opp. Ajanta Hotel),Pahar Ganj,New

Delhi-110055.

2. Type of occupancy:
Residential, Sub Division-A-1 (Basement, Ground + 04 Upper floor – 12 guest rooms)

3. Type of case:-4. Details of previous FSC:-No. F6/D

No. F6/DFS/MS/GH/2015/NDZ/1246 dated

5. Fire safety directives No.- N/A
6. Date of inspection:- 21/01/16

21/01/16

7. Name of the inspecting officer:8. Name & designation of officer

D.O. Gurmukh Singh Chauhan.

8. Name & designation of officer From the building side:-

Mr. Devender Uppal.

9. Year of construction:-10. Applicant's letter No:-

Nil. Dated 13/01/16.

S.No.	Minimum Ct. 1 1 C			Old Case		
	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site PSS	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	5 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrar					
	A. Number of staircases					
	1. Upper floors	01 No.	01 No.	MR		
	2. Basements	01 No.	01 No.	MR		
	B. Width of staircase					
	1. Upper floors	80 cms.	1.15 mtr. to 1.20 mtr.	MR		
	2. Basements	80 cms.	1 mtr.	MR		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
9	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	N/A	N/A	N/A		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
5.	Fire Extinguishers	The state of the s				

	1) Total numbers	10 Nos.	10 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR a			
ŧ	3) ISI marking	Required	Provided	MR			
5.	First-Aid Hose Reel	:					
	1) Total number of eachfloor	N/A	N/A	N/A			
	2) Length of hose reel hose	N/A	N/A	N/A			
	3) Nozzle diameter	N/A	N/A	N/A			
<i>'</i> .	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
	MOEFA	N/A	N/A	N/A			
).	Public Address System	N/A	N/A	N/A			
0.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling	200 000 000	STATE OF STATES				
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor	1 1/1 1	1771	, ,			
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
3.	Pumping Arrangement	14/21	14/21	14/11			
<i>J</i> ,	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
		IN/A	IN/A	IN/A			
	pump h) Head of main nump	N/A	N/A	N/A			
	b) Head of main pump		N/A	N/A			
	c) Number of main pump	N/A	N/A	N/A			
	d) Jockey pump out put		N/A N/A	N/A			
	e) Jockey pump head	N/A					
	f) Stand by pump output		N/A	N/A N/A			
	g) Stand by pump head	N/A	N/A				
	h) Auto starting/Manual	N/A	N/A	N/A			
	stopping						
	2) Terrace level	77/4	27/4	DT/A			
	a) Discharge of pump	N/A	N/A	N/A			
	b) Head of pump	N/A	N/A	N/A			
	c) Power supply	N/A	N/A	N/A			
	d) Auto starting of pump		N/A	N/A			
14.	Captive Water Storage for Fire Fighting						
	1) Under ground tank	N/A	N/A	N/A			
	capacity	1					

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	N/A	N/A	N/A
R	capacity			
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	 a) Pressurization of lift shaft 	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			NA

The licensee has stated that earlier adjoining property was used for his residence & now used for guest house by adding 01 guest room at 1^{st} floor to 4^{th} floor each.

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2015/NDZ/1246 dated 14/07/2015, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Chauhan
Divisional Officer

State 27 1 Diary No. 6

Dycho (NDZ)

May we will be a second of the second of the