## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2016/ 52 152

Dated: 21/1/16

## **FIRE SAFETY CERTIFICATE**

Certified that the Guest House **Delhi Heights** located at 4/39, WEA, Krishna Market, Karol Bagh, New Delhi-110005 is comprised of Basement, Ground floor plus six upper floors, using basement as storage, ground floor as reception, lobby, office & 02 guest rooms, first, second & third & floor each having 09 guest rooms respectively (Total 29 guest rooms), fourth, fifth & sixth floor sealed by the owner was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/135 dated 13.01.2010 for 38 guest rooms owned/ occupied by Sh. Jatender Pal Singh. The guest house building was re- inspected by the officers concerned of this department on 12.01.2016 in the presence of Sh. J.P. Singh (Managing Director) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph;-011-23414333

Copy to:-

- 1. Sh. Jatinder Pal Singh (Owner) Guest House Delhi Heights, 4/39, WEA, Krishna Mkt., Karol Bagh, N.D-110005.
- 2. The Joint Commissioner of Police (Lic.)

  1<sup>st</sup> floor, P.S., Defence Colony, New Delhi.

  (Re. No.1754/Joint C.P./Lic.(H), Dated 17.09.2015)

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

## Basement, Ground Floor blus six upper Floors.

Note: - Fourth to sixth floor have been sealed.

	The second secon	eurea.					
	INSPEC	TION REPORT					
	<ol> <li>Name &amp; address of the building :</li> </ol>	Delhi Heights, 4/39, WEA, Krishna MKt., Karol					
		: Residential (Guest House) N.DO.					
	3. Type of Case	New Case/Renewal  Letter No. F.6/Dfs/ms/GH/10/135 Date 13.01.20					
	4. Details of Previous NOC						
	1 - 000., 63 16 [[6] 140 .						
	6. Date of inspection	12.01.2016 D.O.S.K. Tomar & A.D.O. P.S. Dahiya					
	7. Name of Inspecting Officer						
	0 - 1.01.01.01.01.001.0						
	From the building side :	: Sh. J. P. Singh					
	9. Year of Construction :	: Sh. J. P. Singh : 1995-96 : NiL dated 10:12.2015					
	10. Applicant's letter No.						
	Minimum Standards on fire	NBC/BBL	Provided at	Remarks			
۱o.	prevention and fire safety U/R 33	Requirement		MR/NMR			
	Access to building		1	J WHY HAVE			
	<ul> <li>Road width</li> </ul>	Accessible	07mtr	MR			
	<ul> <li>Gate width</li> </ul>		295 cms	MR			
	• Width of internal road	*	0.13				
	Number, Width, Type & Arrangement	of Evite					
*	a. Number of staircases	U LAIG	T				
	• Upper Floors	Δ.					
	• Basements	One	One	MR, Old Cas			
	b. Width of staircases	-do-	-do-	-do -			
	• Upper Floor			B)			
	Basements		125cms	MR, Old Case			
	c. Protection of exits	-	115 cms	-do-			
	• Fire check door		1	ı			
				250			
	• pressurization			- Proposition in commence of the commence of t			
	d. No. of continuous staircases to			* ,			
	terrace	-	One	:			
	e. Width of Corridor		135cm6, 300cms				
	f. Door Size			Amount of the second se			
			89 cms x 205 cms	-			
	Compartmentation	The second secon					
	Fire check door			0.1			
	<ul> <li>Sealing of electrical shafts</li> </ul>		0	The state of the s			
	<ul> <li>Fire Rating of shaft door</li> </ul>		Sealed				
	Water Curtain						
	• Fire Dampers		•	i <del>-</del>			
4.	Smoke Management System						
	<ul> <li>Basements</li> </ul>	30 a/c per	Exhaust Fons on				
	<ul> <li>Upper floors</li> </ul>	hour	Provided	MR			
	L		Natural Ventilation	MR			

	M114.		<i>3</i> 7	13*		
		12 a/c per hour		_		
5.	Fire Extinguishers					
	<ul> <li>Total numbers</li> </ul>	Two at each Floor	Provided	MR		
	<ul><li>Types</li></ul>	Co, WG, ABC	- do:-	MR		
	<ul><li>IS marking</li></ul>	ISI marked	151 Marked	MR		
6.	First-Aid Hose Reels					
	<ul> <li>Total numbers on each floor</li> </ul>	One	Provided	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	- do-	MR		
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	-do-	MR		
7.	Automatic fire detection and alarming	g system	The second is the second			
	<ul> <li>Type of detectors</li> </ul>	-		+		
3	<ul> <li>Location of Main Panel</li> </ul>	-				
	<ul> <li>Location of Repeater Panel</li> </ul>					
	<ul> <li>Alternate source of power</li> </ul>		-	<u>.</u>		
	<ul> <li>Hooters' Location</li> </ul>	-	_	+		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	- do -	-do-	MIR		
10.	Automätic Sprinkler System					
	<ul> <li>Basement</li> </ul>	Required	Provided	MR		
	<ul> <li>Upper Floor</li> </ul>	V -				
	<ul> <li>Sprinkler above false ceiling</li> </ul>	_				
11.	Internal Hydrants					
	<ul> <li>Size of riser/down-comer</li> </ul>		Promo.			
	<ul> <li>Number of hydrants per floor</li> </ul>	-				
	<ul> <li>Hose Box</li> </ul>		<u> </u>	1		
12.	Yard Hydrants		1.	i		
n E	<ul> <li>Total number of hydrants</li> </ul>					
L	<ul> <li>Hose Box</li> </ul>	_		<u> </u>		
13.	Pumping Arrangements					
	<ul> <li>Ground Level</li> </ul>			A STATE OF THE STA		
	Discharge of main Pump		rane.	_		
	Head of Main pump		•			
	Number of main pumps	(	1.			
	> Jockey Pump out put		•	-		
	> Jockey pump head					
	> Standby Pump out put			-		
	> Standby Pump Head		ke i			
	Auto Starting/Manual			_		
	stopping					

N/15 4/39, WEA, Krishna Market, Karol Beigh, New Delhi-110005.

	Pump House Access	<b>19</b> -		<b></b>
	<ul> <li>Terrace level</li> </ul>			0 10
	Discharge of pump	-	534 LPM	MR Old Ca
	Head of the pump	-	38 M	-do-
	Power Supply	Required	Provided	MR
	Auto Starting of pump	-		<u> </u>
4.	Captive Water Storage for fire fighting			1
	<ul> <li>Underground tank capacity</li> </ul>	-		-
	Draw-off connection		-	-
	Fire service inlet	-	Provided	-
	Access to tank	_	_	-
	<ul> <li>Overhead Tank capacity</li> </ul>		6000 Ltr	MR, Old Cas
15.	Exit Signage.	Required	Provided	MR
13.	Exit Signage.		% 20	2
16.	Provision of Lifts.			
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	•	-	-
	<ul> <li>Pressurization of Lift lobby</li> </ul>	-		
	Communication In lift Car	-	Provided	MR
	<ul> <li>* Fireman's Grounding Switch</li> </ul>	0	- do -	MR
	Lift Signage	Required - do -	-do-	MR
				MR
17.	Standby power supply	Required	D.G Set of 82.5 kv	!
27.				
18.	Refuge Area.			
	Total Area	F		
	> Location		-	-
	1			
19.	Fire Control Room			
	Detector System Panel  Standard Banel  The Societate Banel  The Soc			- 1
	Flow Switch Panel			
	PA System Panel     Pather healting			
	Batter backup  Building Floor Plans			
	Building Floor Plans			-
20.	Special Fire Protection System for Protection of special Risks, if any:	*	-	_

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS MS 6H 2010 135 dated 13.01.2010 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

By CFOCCED 18 116

Signature of Inspecting Officer

Name P. S. Dahiya

Designation ABBH. Divisional Officer