GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/MS/DFS/SZ/GH/2016/ 57/ 194

Dated: 02/02/16

FIRE SAFETY CERTIFICATE

Certified that the Hotel Conclave Comfort located at D-150, East of Kailash New Delhi -110048 comprised of basement, ground & 03 upper floors (24 guest room) owned/occupied by Unit of Libra Hotels (P) Ltd. was granted FSC by this department vide letter No. F6/DFS/MS/ GH/2012/3465 dated 21/09/2012. The premises was re-inspected by the officer concerned of this department on 23/01/2016 in the presence of Mr. Parveen Jha and observed that the said premises have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Group-A**, **Residential (Lodging or Rooming House)** with effect from... 22/22/16... for a period of **three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued -02/02/16---at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Tel: 011-23414333

Te Hyman (Ber)

Copy to:-

- (1) The Joint Commissioner Of Police, 1st Floor, Police Station Defence Colony, New Delhi
- (2) Hotel Conclave Comfort, D-150,East Of Kailash, New Delhi-110048.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- Hotel Conclave Comfort (Unit of Libra Hotels(P) Ltd.), D-150, East Of Kailash, New Delhi-110048
- 2. Type of occupancy:- Residential, Group-A, Rooming or Lodging Houses (Guest House)
- 3. Type of case: Renewal
- 4. Details of previous NOC: F6/DFS/MS/GH/2012/3465 dated :- 21/09/2012
- 5. Fire safety directives No.- Nil
- 6. Date of inspection: 23/01/2016
- 7. Name of the inspecting officer:- D.B.Mukherjee, A.D.O.(BCP)
- 8. Name & designation of officer From the building side: Mr. Parveen Jha
- 9. Year of construction: 2006
- 10.Applicant's letter No:- No.2604/Joint C.P./Lic.(H) dated New Delhi the 03/12/2015 applicant letter no Nil, dated 17/12/2015
- 11. Composition of building; Basement, Ground + 03 Upper Floors. (24 guest room)

| l. [0 | Minimum Standards on fire Prevention and fire safety U/R 33 | BBL/NBC Requirement | Provided at site | Remarks MR/NMR | | |
|----------|--|------------------------|-------------------|-------------------|--|--|
| | Access to Building | | D :dod | MR | | |
| • | 1) Road width | 12mtr | Provided | N/A | | |
| | 2) Gate width | N/A | N/A | | | |
| | 3)Width of internal road | N/A | N/A | N/A | | |
| | Number, Width Type & Arrangement of | Exits | | | | |
| 2. | A. Number of staircases | | 100 | MD | | |
| | 1. Upper floors | lnos. | Provided 02 nos. | MR | | |
| | | 2nos. | Provided 02 nos. | MR | | |
| | 2. Basements | | | | | |
| | | 1.25m | 1.25mtr &0.83mtr | MR | | |
| | 1. Upper floors | 1.25m | 1.25mtr & 0.83mtr | MR | | |
| | 2. Basements C. Protection of exits | | | 31/4 | | |
| | | N/A | N/A | N/A | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization D. No. of continuous staircase to terrace | 01nos | 01 nos. | MR | | |
| | | N/A | N/A | N/A | | |
| | E. Width of corridor | 1m | Provided | MR | | |
| | F. Door size | 1111 | | | | |
| 3. | Compartmentation | NI/A | N/A | N/A | | |
| - | 1) Fire check door | N/A | N/A | N/A | | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | | |
| | 4) Water curtain | N/A | N/A | N/A | | |
| | 5) Fire Dampers | N/A | | | | |
| 4. | Smoke Management System | 120 / 120 | Exhaust Fan | MR | | |
| | 1) Basements | 30 a/c per hour | N/A | N/A | | |
| | 2) Upper floors | 12 a/c per hour | 14/11 | | | |
| 5. | | | | | | |
| | 1) Total numbers | 101.14 | ABC, Co2 | MR | | |
| | 2) Types | ISI Marked | ADC, C02 | | | |
| 6. | First-Aid Hose Reel | | | | | |
| 0. | 1) Total number of each floor | 01 no. | Provided | MR MR | | |
| | 2) Length of hose reel hose | 30 m | Provided | MR | | |
| | 3) Nozzle diameter | 5 mm | Provided | 1,111 | | |

| 7. | Automatic Fire Detection & Alarming | System | | |
|------|--|------------|------------------|------------|
| | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | Required | Provided | MR |
| 10. | Automatic Sprinkler System | | | |
| | 1) Basement | Required | Provided | MR |
| | 2) Upper floors | NR | N/A | N/A |
| | 3) Sprinkler above false ceiling | N/A | N/A | N/A |
| 11. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per floor | N/A | N/A | N/A |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | Yard Hydrants | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | N/A |
| 13. | Pumping Arrangement | 1 | | |
| 10. | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main pump | N/A | N/A | N/A |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A |
| | 2)Terrace level | IN/A | IVA | 14/21 |
| | a) Discharge of pump | 450Lpm | Provided 450 lpm | MR |
| ĺ | b) Head of pump | 35mtr | Provided 35 mtr | MR |
| | c) Power supply | Required | Provided D G set | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 14 (| Captive Water Storage for Fire Fighting | Required | Tiovided | IVIIC |
| 14.0 | 1) Under ground tank capacity | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | a) Draw-off connectionb) Fire service inlet | Required | Provided | MR |
| | | N/A | N/A | N/A |
| | c) Access to tank d) Over head tank capacity | 10,000ltr | 10,000 Ltrs. | MR |
| 15 | | Required | Provided | MR |
| 15. | Exit Signage. Provision of Lifts. | Required | Trovided | 1411 |
| 16. | | N/A | N/A | N/A |
| | | N/A N/A | N/A N/A | N/A |
| | b) Pressurization of lift lobby c) Communication in lift car | N/A N/A | N/A N/A | N/A |
| | | N/A N/A | N/A N/A | N/A |
| | d) Fireman's switch | N/A N/A | N/A N/A | N/A N/A |
| 1= | e) Lift signage | | | MR |
| 17. | Stand by Power Supply | Required | Provided DG Set | IVIK |
| 18. | Refuge Area | | | |
| | Total area | N/A | N/A | N/A |
| | Location | N/A | N/A | N/A |

to

| 19. | Fire Control Room | N/A | N/A | N/A |
|-----|--|-----|-----|-----|
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Pro | N/A | | |

The shortcomings issued vide letter no.F.6/DFS/MS/GH/2015/2427 dated :-20/11/15 have been rectified. Keeping in view of the compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, renewal of the FSC issued vide letter No. F6/DFS/MS/GH/2012/3465 dated 21/09/2012, under rules 35 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly DFA is put up for perusal and signature pl.

Signature of the inspecting officer

Name: - D.B.Mukherjee.

Designation:- Assistant Divisional Officer (BCP)

Do (South)

29/1/16