## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS/ONS/ EH/2016/NDZ/189

Dated: 29/01/16

## FIRE SAFETY CERTIFICATE

Certified that the QD'S Restaurant (Eating House) running at ground floor level of a building comprised of basement, ground plus three upper floors at A-47,Guru Nanak Pura,Laxmi Nagar,Delhi -92, owned/occupied by M/s QD'S Restaurant Pvt. Ltd. have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on dated 05.01.16 & 15.01.16 in the presence of Sh.Sarjit Gupta (Director) and found that the ground floor of building is fit for occupancy class D-Assembly (Restaurant/Eating House) with effect from 12.9 1.6.. for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, subject to conditions printed overlean

Issued on 29/01/16 at New Delhi by

(Dr.G.C.Misra) Chief Fire Officer Ph.011-23414333

To,

The Dy. Health Officer,
East Delhi Municipal Corporation ,Health Department,
Shahdara (South) Zone, Karkardooma, Shahdara, Delhi
Copy to-

Shri Sarjit Gupta M/s QD'S Restaurant Pvt. Ltd A-47,Guru Nanak Pura,Laxmi Nagar,Delhi -92

## CONDITIONS:

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc may be got verified from the authorities concerned.
- 5. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate,six months prior to its expiry"
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

: QD'S Restaurant , Ground floor, A-47, 1. Name & address of the building

Guru Nanak Pura, Laxmi Nagar, Vikas Marg, Delhi.

2. Building is comprised of

: Basement, ground + three upper floors

3. Type of Occupancy

: Restaurant(Assembly)

4. Type of Case

: New Case

: Nil

5. Details of Previous FSC 6. Fire Safety direction letter No

: NBC Part IV

7. Date of Inspection

: 05.01.16 & 15.01.16

:ADO R.K.Yadav

8. Name of the Inspecting Officers: 9. Name of the designation of Officer

from the building side

: Sh. Sarjit Gupta (Director)

10. Year of Construction

: 1981 & 1991

: DHO/SHD/S-2015/1864 dated 08.12.15

1. Ap	plicalle s lecter	HD/S-2015/1864 dat	Provided at	Remarks	
.No	Minimum Standards on fire	Requirement/NBC	Site	MR/NMR	
	prevention and fire safety U/R33	Requirement, Noc	Site		
1	Access to building	C 122	15 m	MR	
	Road width	6 m N.A.	N.A.	N.A.	
	Gate width		N.A.	N.A.	
	Width of internal road	N.A.	14.74		
2	Number, Width, Type and Arrangement of Exits				
	a. Number of Staircases		02 no.	MR	
	Upper Floor	2 no.	N.A.	N.A.	
	Basement	N.A.	IV.A.	147	
	b. Width of Staircases		1.5 m each	MR	
	Upper Floor	1.5 m		N.A.	
	Basement	N.A.	N.A.	11.7.	
	c. Protection of exits		D 'ded	MR	
	Fire check door	Required	Provided	N.A.	
	Pressurization	N.A.	N.A.	MR	
	e. No. of continuous staircases to	01 no.	2 nos.		
	terrace	N.A.	N.A.	N.A.	
	g. Width of Corridor	2 m	2 m & 1.30	MR	
	h. Door Size				
3	Compartmentation.	Required	Provided	MR	
	Fire check door		N.A.	N.A.	
	Sealing of electrical shafts	N.A.	N.A.	N.A.	
	Fire rating of shaft door	N.A.		N.A.	
	Water curtain	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.	
4	Smoke Management System.				
	❖ Basement	N/A	N.A.	N.A.	
	Upper floor	Required	Naturally Ventilated	M/R	

IV	
-	

5.	Fire Extinguisher	03 nos.	04 nos.	MR
	Total numbers	CO <sub>2</sub> & ABC	CO <sub>2</sub> & ABC	MR
	types IS marking	ISI marked	ISI marked	MR
	First-aid-Hose Reels.			
5	Total numbers of each floor	01 No.	01 No.	MR
	Length of hose reel hose	30 m	30 m	MR
	Nozzle diameter	5 mm	5 mm	MR
	Automatic fire detection and alarming systems	em.		
7		Smoke& heat	Provided	MR
	Type of detectors Location of main panel	Reception	Provided	MR
	Location of repeater panel	At ground floor	Provided	MR
	Alternate source of power	Required	Provided	MR
	Hooters's location	Near staircase	Provided	MR
		Required	Provided	MR
8	MOEFA	N.A.	N.A.	N.A.
9	Public address System.	IV.A.		
10	Automatic Sprinkler System.	N.A.	N.A.	N.A.
	* Basement	N.A.	N.A.	N.A.
	upper floor	N.A.	N.A.	N.A.
	sprinkler above false ceiling	N.A.	14.7 0	
11	Internal Hydrants	01 No	01 No.	MR
	size of riser/down-comer	01 No.	01 no.	MR
	Number of hydrants of each floor	1 no.	01 no.	MR
	Hose Box	01 no.	01110.	
12	Yard Hydrants.	1 21 2	N.A.	N.A.
	otal number of hydrants	N.A.	N.A.	N.A.
	tose Box	N.A.	IV.A.	14.74
13	Pumping Arrangements.		NI A	N.A.
	Ground Level	N.A.	N.A.	N.A.
1	> Discharge of main Pump	N.A.	N.A.	N.A.
1	Head of Main Pump	N.A.	N.A.	N.A.
	Number of main pumps	N.A.		N.A.
	Jockey pump out put	N.A.	N.A.	N.A.
	Jockey pump head	N.A.	N.A.	N.A.
	> Standby pump out put	N.A.	N.A.	N.A.
1967	> Standby pump Head	N.A.	N.A.	N.A.
	> Auto Starting /Manual stopping	N.A.	N.A.	N.A.
	> ump House Access	N.A.	N.A.	IV.A.
	• 'errace Level		4501084	NAD
* 1	► Cischarge of pump	450 LPM	450 LPM	MR
	➤ Head of the Pump	40 m	40 m	MR
	> Power supply	Required	Provided	MR
	Auto Starting of pump	Required	Auto	MR

it: Basement is lying vacant and sealed.

- 4	V	

.4	Captive Water Storage for Fire Fighting.	N.A.	N.A.	N.A.
A B	Underground tank capacity	N.A.	N.A.	N.A.
	Draw-off connection	N.A.	N.A.	N.A.
	Fire service inlet		N.A.	N.A.
	Access to tank	N.A.	10,000 Liters	MR
	Overhead Tank capacity	10,000 Liters	Provided	MR
15	Exit Signage.	Required	Provided	IVIN
16	Provision of Lifts.			
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.
	Pressurization of Lift lobby	N.A.	N.A.	N.A.
	Communication in lift car	N.A.	N.A.	N.A.
	Firemen's grounding switch	N.A.	N.A.	N.A.
	Lift Signage	N.A.	N.A.	N.A.
17	Standby power supply	Required	Provided	MR
17	Standby power suppry			
18	Refuge Area.  Total area	N.A.	N.A.	N.A.
		N.A.	N.A.	N.A.
	Location	14.7%		
19	Fire Control Room	N.A.	N.A.	N.A.
	Detector system panel	N.A.	N.A.	N.A.
	Flow switch panel			N.A.
	PA system panel	N.A.	N.A.	N.A.
	Battery backup	N.A.	N.A.	A DESCRIPTION OF STREET SECTION OF
	Building Floor Plans	N.A.	N.A.	N.A.
20	Special Fire Protection systems for	N.A	N.A	N.A
20	protection of special Risks, if any:			1

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

This department had issued FSC for banquet at ground floor & first floor | vel vide letterno.F.6/DFS/MS/GH/2014/NDZ/1286 dated 17/10/2014 & vide letterno.F.6/DFS/MS/GH/2015/NDZ/284 dated 27/02/15 for guest house at second floor of the said building .Now the ground floor banquet is converted into QD'S restaurant (Eating house) no other change is there.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name: R.K.Yada Designation: AD/ (LN)

DO(ED)

Submitted for apportual please