GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/2016/ NO.Z/ 254

Dated:----12/02/16

FIRE SAFETY CERTIFICATE

Issued $\frac{12}{2}$ at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Ph-011-23414333

O/L

Copy to:-

Sh. Ashutosh Kumar,
 Videsh Sanchar Bhawan,
 Bangla Sahib Road, New Delhi.
 Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building: Videsh Sanchar Bhawan, Bangla Sahib Road, New Delhi.

2. Type of occupancy

: Business Building

(B + Gr. + 07 Upper floors)

3. Type of case:-

: Renewal

4. Details of previous FSC

: F.6/DFS/MS/2012/2087 dated 07/06/2012

5. Fire safety directives No.

: NA

6. Date of inspection:-

06/02/16

7. Name of the inspecting officer

: Sh. Gurmukh Singh DO/CD, Sh. M.K. Sharma ADO/CC

8. Name & designation of officer From the building side

: Sh. Sanjay Sharma (Astt. Manager) &

Sh. Ashutosh Kumar

9. Year of construction

: 1976

10. Applicant's letter No

: Nil Dated 25/01/2016

| | | Old Case | | | | |
|-------|---|-------------------------|--------------------------------------|-------------------|--|--|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement Existing | Provided at site | Remarks MR/NMR | | |
| 1. | Access to Building | | | | | |
| | 1) Road width | 06 mtr. | 06 mtr. | MR | | |
| | 2) Gate width | 05 mtr. | 05 mtr. (TwoNos.) | MR | | |
| | 3) Width of internal road | 06 mtr. | 06 mtr. | MR | | |
| 2. | Number, Width Type & Arrangement of Exits | | | | | |
| | A. Number of staircases | | | ** | | |
| | 1. Upper floors | 02 No. | 02 No. | MR | | |
| | 2. Basements | 02 No | 02 No.& 01 Ramp | MR | | |
| | B. Width of staircase | | | | | |
| | 1. Upper floors | 1.25 & 0.80 mtr. | 1.35 & 1.15 mtr. | MR | | |
| | 2. Basements | 1.25 mtr. | 1.35 & 1.15 mtr. 01 ramp 3.5 mtr. | MR | | |
| | C. Protection of exits | | | | | |
| | 1. Fire check door | Required | Provided | MR | | |
| | 2. Pressurization | N/A | N/A | N/A | | |
| | D. No. of continuous staircase to terrace | 01 No | 01 No | MR | | |
| | E. Width of corridor | N/A | N/A | N/A | | |
| | F. Door size | 1 Mtr. | 1 Mtr. | MR | | |
| 3. | Compartmentation | | | | | |
| | 1) Fire check door | Required | Provided | MR | | |
| | 2) Sealing of electrical shafts | Required | Provided | MR | | |
| | 3) Fire rating of shaft door | Required | Provided | MR | | |
| | 4) Water curtain | N/A | N/A | N/A | | |
| | 5) Fire Dampers | Required | Provided | MR | | |
| 4. | Smoke Management System | | | | | |
| | 1) Basements | 30 ACPH | Provided | MR | | |
| | 2) Upper floors | 12 ACPH | Provided | MR | | |

h -

mest.

| 5. | E: E (: 1 | | | | | |
|-----|--|-----------|--|-------|--|--|
| 3. | Fire Extinguishers | | | | | |
| | 1) Total numbers | 215 Nos. | 219 Nos. | MR | | |
| | 2) Types | ABC & CO2 | ABC, CO2 & W.CO2 | MR | | |
| | 3) ISI marking | Required | Provided | MR | | |
| 6. | First-Aid Hose Reel | | | | | |
| | 1)Total number of each floor | 01 No. | 01 No. | MR | | |
| | 2) Length of hose reel hose | 30 m | 30 m | MR | | |
| | 3) Nozzle diameter | 5 mm | 5 mm | MR | | |
| 7. | Automatic Fire Detection & Alarming System | | | | | |
| | 1) Type of detectors | Required | Provided | MR | | |
| | 2) Location of main panel | Gr. Floor | Provided | MR | | |
| | 3) Location of repeater panel | Required | Provided 4 th floor | MR | | |
| | 4) Alternate source of power | Required | Provided | MR | | |
| | 5) Hooter's Location | Required | Provided Every floor Near S/case | MR | | |
| 8. | MOEFA | Required | Provided | MR | | |
| 9. | Public Address System | Required | Provided | MR | | |
| 10. | Automatic Sprinkler System | | | | | |
| | 1) Basement | Required | Provided | MR | | |
| | 2) Upper floors | Required | Provided | MR | | |
| | 3) Sprinkler above false ceiling | NA | NA | NA | | |
| 11. | Internal Hydrants | L | | | | |
| | 1) Size of riser/down-comer | 150 MM | 150 MM | MR | | |
| | 2) Number of hydrants per floor | 01 | 01 | MR | | |
| | 3) Hose box each floor | 01 | 01 | MR | | |
| 12. | Yard Hydrants | | O I | IVIIC | | |
| | 1) Total number of hydrants | 04 | 04 | MR | | |
| | 2) Hose box | 04 | | MR | | |
| 13. | Pumping Arrangement | | | IVIIC | | |
| | 1) Ground level | | | | | |
| , | a) Discharge of main pump | 2850 LPM | 2850 LPM | MR | | |
| | b) Head of main pump | 80 mtr. | 80 mtr. | MR | | |
| | c) Number of main pump | 01 | | MR | | |
| | d) Jockey pump out put (2 Nos.) | 220 LPM | 04 04 2850 LPM 80 mtr. 01 220 LPM | MR | | |
| | e) Jockey pump head | 80 mtr. | 80 mtr. | MR | | |
| | f) Stand by pump output | 2800 LPM | 2800 LPM | MR | | |
| | g) Stand by pump head | 80 mtr. | 80 mtr. | MR | | |
| | h) Auto starting/Manual stopping | Required | Provided | MR | | |
| | 2) Terrace level | | | | | |
| | a) Discharge of pump | N/A | N/A | NI/A | | |
| | b) Head of pump | N/A | N/A N/A | N/A | | |
| | | 11/71 | IN/A | N/A | | |





| | c) Power supply | N/A | N/A | N/A | | |
|-----|--|---------------|---------------|-----|--|--|
| | d) Auto starting of pum | ip N/A | N/A | N/A | | |
| 14. | Captive Water Storage for Fire Fighting | | | | | |
| | 1) Under ground tank capacity | 1,00,000 ltr. | 1,00,000 ltr. | MR | | |
| | a) Draw-off connection | Required | Provided | MR | | |
| | b) Fire service inlet | Required | Provided | MR | | |
| | c) Access to tank | Required | Provided | MR | | |
| | d) Over head tank capacity | 20,000 Ltrs. | 20,000 Ltr. | MR | | |
| 15. | Exit Signage. | Required | Provided | MR | | |
| 16. | Provision of Lifts. | | | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A | | |
| | b) Pressurization of lift lobby | N/A | N/A | N/A | | |
| | c) Communication in lift car | Required | Provided | MR | | |
| | d) Fireman's switch | Required | Provided | MR | | |
| | e) Lift signage | Required | Provided | MR | | |
| 17. | Stand by Power Supply | Required | Provided | MR | | |
| 8. | Refuge Area | N/A | N/A | N/A | | |
| | Total area location | N/A | N/A | N/A | | |
| 19. | Fire Control Room | Required | Provided | MR | | |
| | a) Detector system panel | Required | Provided | MR | | |
| | b) Flow switch panel | Required | Provided | MR | | |
| | c) PA system panel | Required | Provided | MR | | |
| | d) Battery backup | Required | Provided | MR | | |
| | e) Building floor plan | NA | NA | NA | | |
| 20. | . Special Fire Protection System for Protection of special Risk, if any: | | | | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/2015/1466 & 2662 dated 06/07/2015 & 22/12/015 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no.F.6/DFS/MS/2012/2087 dated 07/06/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspetting Officer

Name :- G.S Chauhan

Designation :- DO (CD)

Signature of the Inspecting Officer

Name:- M.K. Sharma Designation:- ADO (CC)

Dy CRO (NDZ)

Lapp

RESERVE SAFER SERVE SAFER SAFE