## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ HD2/273

Dated: 19/02/16

## FIRE SAFETY CERTIFICATE

Certified that Grand Shanti Palace Guest House located at 18/1, Krishna Market, Main Bazar, Pahar Ganj, New Delhi comprises of Ground + 03 Upper floor – Ground floor – reception + shops, 1<sup>st</sup> floor – 07 guest rooms & 2<sup>nd</sup> & 3<sup>rd</sup> floor owner's residence total 07 guest rooms was granted NOC by this department vide letter No.F6/DFS/MS/GH/2010/1174 dated 21/04/2010. The premises was re-inspected by the officer concerned of this department on 09/02/2016 in the presence of Mr Hari Singh Rathore and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 07 guest rooms only with effect from – 2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. The Licensee,

Grand Shanti Palace Guest House,

18/1, Krishna Market, Main Bazar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to it expiry.

-N/8-

INSPECTION REI	PORT
----------------	------

1. Name & address of the building:- Grand Shanti Palace Guest House, 18/1,

Krishna Market, Main Bazar, Pahar Ganj,

New Delhi.

2. Type of occupancy:- Residential Group A-1 Ground

+ 3 Upper Floors.(07 guest rooms at 1<sup>st</sup> floor)

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2010/1174 dated

21/04/2010.

5. Fire safety directives No.-

6. Date of inspection: 09/02/16

7. Name of the inspecting officer:- D.O. Gurmukh Singh

8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Hari Singh Rathore.

2009.

N/A

Nil- Dated 03/02/16

10.	Applicant's letter No	NII- Dated (	J3/U2/10	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement (PSS Area)	Provided at site PSS	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 Mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	80 cm.	82 cms. to 90 cms.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	

	2) Upper floors		- 2		
5.	Fire Extinguishers	12 ACPH	Natural	MR	
_	1) Total numbers				
	2) Types	02 Nos.	04 Nos.	MR	
	3) ISI marking	ABC & CO2	ABC &CC	)2 MR	
6.	First-Aid Hose Reel	Required	Provided	MR	
0.	1) Total purel			IVIIC	
	1)Total number at each floor	01 no. (1 <sup>st</sup>	Provided	MR	
		floor)		IVIIC	
	2) Length of hose reel hose	30 mtr.	Provided	MR	
7.	3) Nozzle diameter	5 mm.	~	MR	
/.	Automatic Fire Detection &	Alarming System	n	IVIK	
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
0	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	N/A	N/A N/A	N/A	
9.	Public Address	N/A		N/A	
	System/Intercom	14/21	N/A	N/A	
10.	Automatic Sprinkler System				
	1) Basement	N/A			
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	The second secon	N/A	N/A	
	ceiling	N/A	N/A	N/A	
11.	Internal Hydrants				
3	1) Size of riser/down-comer	27/4	3.		
	2) Number of hydrants per	N/A	N/A	N/A	
	floor	N/A	N/A	N/A	
	3) Hose box	4	- Control of the Cont		
2.		N/A	N/A	N/A	
2.	1 and Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
3.	2) Hose box	N/A	N/A	N/A	
).	Pumping Arrangement			IN/A	
	1) Ground level	N/A	N/A	27/4	
	a) Discharge of main	N/A	N/A	N/A	
7.	pump		IV/A	N/A	
	b) Head of main pump	N/A	NI/A		
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
/	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	The state of the s	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping	N/A	N/A	N/A	
	2) Terrace level		Negoting.		
-	, , , , , , , , ,		- Longe		
-	- January Starting	180 LPM	180 LPM	MR	
	b) Head of pump	30 Mtr.			

-N/10-

	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
×	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.	1		1111		
.1	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
5	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
X	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System any:	for Protection	of special Risk, if	N/A		

Shortcomings issued vide our letter dated 19/01/16 have been rectified

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2010/1174 dated 21/04/2010, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

19.2-16

Dycho(NDZ)