GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ 33.5

Dated: 82/03/20/6

FIRE SAFETY CERTIFICATE

Issued 62/03/2016 at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi
- 2. The Manager,
 Pash Dx Guest House located at 2958, Gali No. 2, Bhagat Singh Street, Chuna Mandi,
 Pahar Ganj, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building Pash Dx Guest House located at 2958, Gali No. 2, Bhagat Singh Street, Chuna Mandi,

Pahar Ganj, New Delhi

2. Type of occupancy:-Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 08 Guest rooms) 3. Type of case:-

Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2013/688 dated 18/02/13.

5. Fire safety directives No.-N/A 6. Date of inspection:-

18/02/16 7. Name of the inspecting officer:-Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Sh. Vinod (Partner)

1991

Nil dated 03/02/16.

- 1			1411 dated	03/02/10.				
C	.No.	M G			Old Case			
3.	.INO.	Minimum Standards on fire	Requirement	Provided at site	Remarks			
and the same		Prevention and fire safety	Existing	PSS	MR/NMR			
1		U/R 33						
1.		Access to Building						
ŀ	,	1) Road width	Spl. area	06 mtr.	MR			
		2) Gate width	N/A	Directly accessible	MR			
		2)Width - C: - 1	1220	from the road	1,11			
2.		3) Width of internal road	N/A	N/A	N/A			
4.	Number, Width Type & Arrangement of Exits							
-		A. Number of staircases						
		1. Upper floors	01 Nos.	01 Nos.	MR			
		2. Basements	N/A	N/A	N/A			
l		B. Width of staircase			1011			
l		1. Upper floors	0.80 mtr.	1.12 to 1.27 Mtr.	MR			
			ti .		TVIIC			
		2. Basements	N/A	N/A	N/A			
044000000000000000000000000000000000000		C. Protection of exits			1 1111			
COMMUNICATION		1. Fire check door	N/A	N/A	N/A			
Married		2. Pressurization	N/A	N/A	N/A			
		D. No. of continuous	01	01	MR			
l		staircase to terrace			IVIK			
Colombia		E. Width of corridor	N/A	N/A	N/A			
		F. Door size	N/A	N/A	N/A			
Consumer of the last		Compartmentation	1471	IV/A	IN/A			
		1) Fire check door	N/A	N/A	27/4			
Designation of the last		2) Sealing of electrical shafts	N/A	N/A N/A	N/A			
		3) Fire rating of shaft door	N/A		N/A			
-		4) Water curtain	N/A	N/A	N/A			
TOTAL PARTY OF THE		5) Fire Dampers	N/A	N/A	N/A			
H			N/A	N/A	N/A			
-	_	Smoke Management System 1) Basements	20 4 0577					
To the last of the	_		30 ACPH	N/A	N/A			
The second second		2) Upper floors	12 a/c per	Natural	MR			
			hour					

5.	Fire Extinguishers			05.3	T	M	D	
	1) Total numbers	07 N		07 N		M		
	2) Types		& CO2		C & CO2	M		
	3) ISI marking		ired	Prov	vided	IVI	N	
5.	First-Aid Hose Reel			01		M	D	
	1) Total number of eachfloor		01		4	MR		
	2) Length of hose reel hose		tr.	30 mtr.		MR		
	3) Nozzle diameter		05 mm		05 mm		MR	
7.	Automatic Fire Detection & A	Alarm	ning Syste	em		N	/ /	
	1) Type of detectors		N/A		N/A		N/A N/A	
	2) Location of main panel		N/A		N/A		N/A	
	3) Location of repeater panel		N/A		N/A		N/A	
	4) Alternate source of power		N/A		N/A		N/A N/A	
	5) Hooter's Location		N/A		N/A		I/A	
8.	MOEFA Public Address System		N/A N/A		N/A N/A			
9.					P	N/A		
10.	Automatic Sprinkler System				A	N	Ι/Λ	
	1) Basement	N/A	112		N/A		N/A N/A	
	2) Upper floors	N/A			N/A N/A		N/A N/A	
	3) Sprinkler above false		N/A		A	T	V/ /\tag{1}	
	ceiling							
11.	Internal Hydrants		37/4		N/A		N/A	
	1) Size of riser/down-comer		N/A		N/A N/A		N/A	
	2) Number of hydrants per		N/A		IN/A		14/11	
	floor		N/A		N/A		N/A	
	3) Hose box							
12.	Yard Hydrants		DT/A		N/A		N/A	
	1) Total number of hydrants		N/A N/A		N/A		N/A	
	2) Hose box		1	11/	A			
13.	Pumping Arrangement		DT/A		N/A	-	N/A	
	1) Ground level		N/A		N/A		N/A	
	a) Discharge of main		N/A	10	11/17		1 1/11	
	pump		N/A		N/A		N/A	
	b) Head of main pum		N/A N/A		N/A		N/A	
	c) Number of main p		N/A		N/A		N/A	
\$1j	d) Jockey pump out p		N/A		N/A		N/A	
	e) Jockey pump head		N/A		N/A		N/A	
	f) Stand by pump ou		N/A		N/A		N/A	
	g) Stand by pump he		N/A N/A		N/A		N/A	
	h) Auto starting/Man		IN/A		11/21			
	stopping							
	2) Terrace level		225 LP	M	Provided		MR	
	a) Discharge of pum		30 mtr.		Provided		MR	
	b) Head of pump		Required		Provided		MR	
1	c) Power supply		Require		Provided		MR	
	d) Auto starting of p		INCHAIL	u	110,100	1		
14.	Captive Water Storage	for F		inσ				

new

capacity
a) Draw-off connection N/A N/A N/A
b) Fire service inlet N/A N/A N/A

	capacity		T	0.00
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A N/A
	c) Access to tank	N/A	N/A	
Mary!	d) Over head tank capacity	2500 ltr.	2500 ltr.	N/A MR
15.	Exit Signage.	Required	Provided	MD
16.	Provision of Lifts.		Tiovided	MR
A SIVI	a) Pressurization of lift shaft	N/A	N/A	N/A
IPE	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
17.	e) Lift signage	N/A	N/A	N/A
	Stand by Power Supply	Required	15 KVA Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any: One Co ₂ type fire ext	n for Protection	on of special	MR

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/688 dated 18/02/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

26 76

Dosep) (15/1/16