GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/GH/2016/ MOZ/362

Dated :- 4 1 3 / 1 6

FIRE SAFETY CERTIFICATE

Certified that Shanti Niwas Guest House, 159, Kucha Ghasi Ram ,Fatehpuri Delhi comprises of Ground + 03 Upper floor – Ground floor - reception + 08 guest room, 1st floor & 2nd floor residence total 08 guest rooms was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/1671 dated 09/05/2012. The premises was re-inspected by the officer concerned of this department on 18/02/2016 in the presence of Sh. Parmod Soni and found that the said guest house building have added 19 guest rooms at 1st, 2nd & 3rd floors. Now the floor wise occupancy at Ground floor - reception + 07 guest rooms & store, 1st floor 08 guest rooms + store, 2nd floor & 3rd floor 06 guest rooms & 02 stores at each floor total 27 guest rooms and have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 27guest rooms only with effect from ------2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on ...4.1.3. 1.6...... at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. Shanti Niwas Guest House, 159, Kucha Ghasi Ram Fatehpuri Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to it expiry.

INSPECTION REPORT

1.Name & address of the building:-Shanti Niwas Guest House 159, Kucha Ghasi

Ram Fateh Puri Delhi. 2. Type of occupancy:-

Residential Group A-1, Ground + 3 Upper

Floors.(27 guest rooms) 3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/MS/DFS/GH/2012/1671 dated

5. Fire safety directives No.-09/05/2012.

6. Date of inspection:-N/A 18/02/16

7. Name of the inspecting officer:-D.O. Gurmukh Singh

8. Name & designation of officer From the building side:-

Mr. Parmod 9. Year of construction:-2002.

10. Applicant's letter No:-Nil- dated 11/02/16

	Nil- dated 11/02/16					
S.No.	Minimum Standards on fir Prevention and fire safety U/R 33 Access to Building			Old Case e Remarks MR/NMI		
	1) Road width					
	2) Gate width	N/A	N/A	77//		
		N/A	N/A	N/A		
2.	3) Width of internal road	N/A		N/A		
2.	Number, Width Type & Arr	rangement of Fyit	IN/A	N/A		
-		DAIL	.5			
-	1. Upper floors	01 No.	01 No.			
+	2. Basements	N/A	N/A	MR		
-	B. Width of staircase		IN/A	N/A		
-	1. Upper floors	80 cms.	0.7			
	2. Basements	N/A	97 cms.	MR		
<u> </u>	C. Protection of exits	1071	N/A	N/A		
	1. Fire check door	N/A	27/			
4	2. Pressurization	N/A	N/A	N/A		
I	O. No. of continuous	N/A	N/A	N/A		
	staircase to terrace	IV/A	N/A	N/A		
E	E. Width of corridor	N/A				
F	. Door size	1 mtr.	N/A	N/A		
C	Compartmentation	1 IIItr.	1 mtr.	MR		
1) Fire check door	NT/A				
2)	Sealing of electrical shafts	N/A	N/A	N/A		
3)	Fire rating of shaft door	N/A	N/A	N/A		
4)	Water curtain	N/A	NT/A	N/A		
5)	Fire Dampers	N/A	NT/A	N/A		
Sn	moke Management System	N/A	NT/A	N/A		
1)	1) Resements					
	Upper floors	30 ACPH	N/A	NI/A		
Fi	re Extinguishers	12 ACPH	Natural	N/A		
1)	Total numbers		- maidi	MR		
2)	Types	08Nos.	10 Nos	MD		
(2)	Types	ABC & CO2	ABC &CO2	MR		
			TADE &CO2	MR		

	3) ISI marking	(0		
6.	First-Aid Hose Reel	Required	Provided	1
	1)Total number at each		210 / 1400	
	floor	01 no.	01 no.	MR
	2) Length of hose reel hose	e 30 mtr.	20	
7.	3) NOZZIE diameter	~	30 mtr.	MR
7.	Automatic Fire Detection a	& Alarming Sys	5 mm.	MR
		N/A		
	2) Location of main panel	NT/A	N/A	N/A
	3) Location of repeater pan	01 11/4	N/A	N/A
	4) Alternate source of now	er N/A	N/A	N/A
8.	3) Hooter's Location	N/A	N/A	N/A
9.	MOEFA	N/A	N/A	N/A
10.	Public Address System	NI/A	N/A	N/A
10.	Automatic Sprinkler System	1	N/A	N/A
	1) Basement	N/A	NT/A	
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
11.	ceiling		N/A	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	
	2) Number of hydrants per	N/A	N/A N/A	N/A
	floor		IN/A	N/A
12.	3) Hose box	N/A	N/A	
12.	Yard Hydrants		IVA	N/A
	1) Total number of hydrants	N/A	N/A	1271
3.	2) Hose box	N/A	N/A	N/A
J.	Pumping Arrangement		IVA	N/A
	1) Ground level	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A
	pump		IN/A	N/A
	b) Head of main pump	N/A	N/A	271
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping		11/11	N/A
-	2) Terrace level			
	a) Discharge of pumpb) Head of pump	450 LPM	450 LPM	MD
	of partip	30 Mtr.	30 Mtr.	MR
	c) Power supply	Required	Provided	MR
-	d) Auto starting of pump	Dagg: 1	Provided	MR
	Captive Water Storage for Fire	Fighting	1 TO VIGOU	MR
	1) Under ground tank	N/A	N/A	NT/A
	capacity		11/11	N/A
	a) Draw-off connection 1	V/A	N/A	77/4
			11/11	N/A

19-19

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
2	d) Over head tank capacity	5,000 ltrs.	5,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		IVIIC
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			

Shortcomings issued vide letter dated 27.11.15 found rectified & owner of guest house informed that 3rd floor of the premises used as residential purpose since 2002.

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/MS/DFS/GH/2012/1671 dated 09/05/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

Dycho (HDZ)

Date 1-3-16
Mary MR 493 *

Cro sky Min 18/2