GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2016/ \$ 2 / 373

Dated: 09/03/16

FIRE SAFETY CERTIFICATE

Certified that the Anila Hotels (a unit of Le-passage to India Tours & Travels Pvt. Ltd.) located at A-15, Naraina Vihar, New Delhi-110028 is comprised of Basement, stilt floor, ground floor plus three upper floors, using basement as hall/storage, stilt floor as a parking, ground floor having 09 guest rooms, office and reception, first, second and third floor each having 09 guest rooms and one store respectively (Total 36 guest rooms), a pantry for staff in a tin shed on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2013/566 dated 12.02.2013 owned/occupied by Sh. Manish Goel. The guest house building was re inspected by the officers concerned of this department on 24.02.2016 in the presence of Sh. Sripal Rawat and found that the management have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

1. Sh. Manish Goel (Owner) Anila Hotels (a unit of Le-passage to India Tours & Travels Pvt. Ltd.), A-15, Naraina Vihar, New Delhi-110028.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	1. Name & address of the	INSPEC	TION REPORT (A	unit of Le-basse ravels Put (1d)	ege to India	tou
	 Name & address of the Type of Occupancy 	. Bandung:	mile Moccis,	A-15, Narain	a Vibar, N	,0-
	3. Type of Case	:	A Polarental (GUEST HOUSE)		
	4. Details of Previous NO		New Case/Rene	wai		
	5. Fire Safety directives le		Letter 140. F.6/1	DES/MS/GH/2013/	566Date_12.0	2.20
	6. Date of inspection		91.	A 9 0 - 10		****
	7. Name of Inspecting Of	ficer	N.O. C. L. T.	02.2016	0 0 1	
	8. Name and designation	of officers	D.O 2.V. 10	mar & A.D.O	P.S. Dahir	ja_
ý	From the building side		Sh. Shripal	Rount		/
	9. Year of Construction	:	Before 2010)	The second secon	
	10. Applicant's letter No.		Mil dated			
5.	Minimum Standards on fire		NBC/BBL	Provided at	Remarks	
Vo.	prevention and fire safety (J/R 33	Requirement	site	MR/NMR	
l.	Access to building					
	 Road width 	Wilderson or the second	Accessible	18 mtr	MR	
	Gate width			370 cms	MR	7
	Width of internal roa					į
?	Number, Width, Type & Arr	angement	of Exits		Antonia ada da conducercania a cadare del R. Districtor conservação de la final de conservação de conserv	<u>-</u> -
	a. Number of staircases				The state of the s	
	• Upper Floors		One	One	Na O	
	Basements		Two	Two	MR	
	b. Width of staircases		100	100	MR	
	 Upper Floor 			132 cms	Na0 011	0-
	• Basements		phone and the same		MR, Old	Casi
	c. Protection of exits	1		150 cms, 115cms	- do -	
	 Fire check door 				and the second s	***********
	 pressurization 				The state of the second	
	d. No. of continuous stairce	ses to				
	terrace		Son.	One		1.
	e. Width of Corridor f. Door Size				The control of the advantage of the state of the control of the co	en y a resser regular and an order of
	f. Door Size			147cms, 180cms	property and an appropriate or married a laster reservoir a factor	
	Compartmentation			88 cms x 220 cm		
	The same of the sa				,	
	 Fire check door Sealing of electrical s 		_	•		
		hafts		Sealed	and the second section of the sect	
	 Fire Rating of shaft d 	bor		Searen		
	Water Curtain		•		office where it is a finishes the state of t	
	• Fire Dampers				did manage of the population of the control of the	
١.	Smoke Management Syster	n			Manager of the first of the second se	
-	* Basements	P.	30 a/c per	Exhaust Fans	A section with the section of the se	
	 Upper floors 		hour	are Provided	mR	
			(Natural Ventilatio	h MR	k-,

		H/10		, ————————————————————————————————————
		12 a/c per		
		hour		!
5.	Fire Extinguishers			2
	The state of the s			,
	Total numbersTypes	20 Nos	Psevided	MR
	TypesIS marking	ABC, WCo2, Co2	-do-	MR
6.	First-Aid Hose Reels	ISI marked	IsI Marked	MR
	Local Lighting 2 Oil 69CH 1100L	One	Provided	MR
	Length of hose reel hoseNozzle diameter	30 m	-do-	MR
7.	A rest facilities of the property of the second sec	5 mm	- do:-	MR.
	Automatic fire detection and alarmin	ng system		
	Type of detectors		Smoke	MR
	cocation of Main Panel	-	C-	
	 Location of Repeater Panel 	-	, man	
	 Alternate source of power 	_		
0	* Hooters' Location			
8.	MOEFA	Required	Provided	MR
9,	Public Address System	-do-	- do -	MR
10.	Automätic Sprinkler System	/		
	• Basement	Required	Provided	MR
	 Upper Floor 	V		
1.5	 Sprinkler above false ceiling 			
11.	Internal Hydrants			
	 Size of riser/down-comer 	-	100 m.m	MR
	 Number of hydrants per floor 		One	MR
	 Hose Box 		-do-	MR
12.	Yard Hydrants		J.	17/
	 Total number of hydrants 		One	MiR
4.0	* Hose Box		- do-	MR
13.	Pumping Arrangements			
	 Ground Level 			
	Discharge of main Pump			Annual State of the State of th
	Head of Main pump	-		:
	Number of main pumps			the second secon
	> Jockey Pump out put			
	Jockey pump headStandby Pump out put	-		
	Standby Pump Out putStandby Pump Head			
	> Auto Starting/Manual			
	stopping			

N/11 A-15, Naraina Vihar, New Delhi-110028.

 Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet 	450 LPM Each 30 M Each Required	450 LPM Each 30 M Each Provided Both	MR (O2 Pum)			
 Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet 	30 M Each Required	30 M Each Provided	MR			
 Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet 	30 M Each Required	30 M Each Provided	MR			
 Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet 	Required	Provided				
• Underground tank capacity > Draw-off connection > Fire service inlet		Both	1			
 Underground tank capacity Draw-off connection Fire service inlet 		_	1			
 Underground tank capacity Draw-off connection Fire service inlet 	-		The state of the s			
Draw-off connectionFire service inlet	****	1				
		Agreem.	_			
N. A		Provided	MR			
Access to tank		130170				
 Overhead Tank capacity 	15000 ltr	15000 (1x	MR			
Exit Signage	Required	Provided	MR			
	4					
		_				
 Communication In lift Car 		Parilal	MR			
 Fireman's Grounding Switch 	0					
	Regleired		MR			
	-do-	- do -	, MR			
Standby power supply	Required	D.G.Set of 140 KV	A MR			
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			± = = = = = = = = = = = = = = = = = = =			
Refuge Area.						
> Total Area		_				
> Location						
,		*****				
Fire Control Room	i	s	-			
 Detector System Panel 	-					
 Flow Switch Panel 		-	-			
 PA System Panel 						
Batter backupBuilding Floor Plans	-	Provided	MR			
		7 - 00/14 Ed.	1			
Special Fire Protection System for Protection of special Risks, if any:						
	 Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection System for 	• Overhead Tank capacity IScool Ur Required	• Overhead Tank capacity ISO00 Itr ISO00 Itr Required Required Psovided Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car • Fireman's Grounding Switch • Lift Signage Required Psovided Required Area Standby power supply Refuge Area. > Total Area > Location • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup • Building Floor Plans Special Fire Protection System for			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2013/566 dated 12.02.2013 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation AssH. Divisional Officer