GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ ND 2/374

Dated: 03/03/16

FIRE SAFETY CERTIFICATE

Certified that M/s Hotel Saka 782, Motor Market, Jama masjid, Delhi comprises of Ground + 04 Upper floor, Ground floor (commercial use), first floor (reception + 04 guest rooms), second floor (04 guest rooms + 01 staff room) and third floor (04 guest rooms), total 12 guest rooms was granted NOC by this department vide letter No.F6/DFS/MS/GH/2012/2351 dated 03/07/2012. The premises was re-inspected by the officer concerned of this department on 19/02/2016 in the presence of Mohd. Akbar and found that the said guest house building have added 09 rooms at 1st floor,03 more room at 2nd floor,03 more rooms at 3rd floor. Now the floor wise occupancy at Ground floor (commercial use), first floor (reception + 07 guest rooms), second floor (07 guest rooms) and third floor (07 guest rooms) & 4th floor (04 rooms private use- total 21 guest rooms and have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 21 guest rooms only with effect from

-0.7-1.2.3-1----2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service

Ph: - 011-23414333

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. The Owner, M/s Hotel Saka 782, Motor Market, Jama masjid, Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-N-16

INSPECTION REPORT

1. Name & address of the building Hotel Saka 782, Motor Market, Jama

masjid, Delhi

2. Type of occupancy:-Residential, Sub Division-A-1 (Ground +

04 Upper floor)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2012/2351 dated

03/07/12.

5. Fire safety directives No.-N/A

6. Date of inspection:-19/02/16 7. Name of the inspecting officer:-D.O Gurmukh Singh

8. Name & designation of officer

From the building side:-9. Year of construction:-

Mohd. Naseem (manager)

1967

10. Applicant's letter No:-1325-26/Joint C.P./Lic.(H) dated

21/08/2015.

Old Case S.No. Minimum Standards on fire Requirement Provided at site Remarks Prevention and fire safety Existing PSS MR/NMR U/R 33 1. Access to Building 1) Road width N/A 24 mtr. N/A 2) Gate width N/A N/A N/A 3) Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 01 Nos. 01 Nos. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 0.80 mtr. 01 mtr. MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous N/A N/A N/A staircase to terrace E. Width of corridor N/A N/A N/A F. Door size 1 mtr. 1 mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements N/A N/A N/A

	2) Unnon floors	NT/A	NT/A	DI/A		
5.	2) Upper floors	N/A	N/A	N/A		
٥.	Fire Extinguishers 1) Total numbers	12 Na.	12 N	MD		
6		12 Nos.	12 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
7.	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & A			27/4		
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	8				
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor					
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump		ž.			
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping			1,111		
	2) Terrace level					
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire	1	TTOVICCE	IVIIX		
		2 I IZHUHY				

	1) Under ground tank capacity	N/A	N/A	N/A
4	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1	Trovided	IVIIX
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
1-	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	of special Risk, if	NA	

The Licensee has informed that renovation work done and big rooms converted in small rooms and no new construction made

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/ GH/ 2012 /2351 dated 03/07/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Dy CRO (NDZ) GF+04.

Gurmukh Singh
Divisional Officer