FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2016/w2/393

Dated: 11/3/16

FIRE SAFETY CERTIFICATE

Certified that the Holy Child Senior Secondary School located at Tagore Garden, New Delhi – 110027 comprised of Ground + 02 Upper Floors only was issued FSC vide Letter No. F6/DFS/MS/2011/1557 Dated 12-07-2011. The premises was re inspected by the officer concerned of this department on 08-02-2016 in the presence of Sh. Chako V.J. (Accountant) and observed that a new block comprising basement and ground floor is added in the premise. All the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance DOE Circular 262 – 362 Dated 17-01-2005 and that the premises is fit for occupancy class "Educational" Group B with effect from 1/2//6 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 4.1.7.116 at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer, Ph: 011 – 23414333.

0/2 By

Copy to:

The Principal, Holy Child Senior Secondary School Tagore Garden, New Delhi – 110027.

Following fire safety directives must be adhered to:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used strictly as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Holy Child Senior Secondary School, Tagore Garden, New Delhi – 110027.

2. Type of Occupancy : Educational (1 Block = Ground + 02 Upper Floors & 1 Block = Basement + Ground Floor only)

3. Type of Case : Renewal / Addition + Alteration.

4. Details of previous NOC : Letter No. F6/DFS/MS/2011/1557 Dated 12-07-2011.

5. Fire Safety directives Letter No.: DOE 262-362 dated 17-01-2005

6. Date of inspection : 08-02-2016

7. Name of the Inspecting Officer: Mukesh Verma, ADO (MN)

8. Name and designation of Officer

from the building side :

: Sh. Chako V.J. (Accountant)

9. Year of Construction : 1967

10. Applicant's letter No. : Letter no. Nil dated 22-01-2016

S	Minimum standards on fire	DOE 262-362	Provided at	Remarks	
No	prevention and fire safety U/R 33	dated 17-01-05	site	MR/NMR	
1.	Access of building				
	 Road width 	Accessible	Provided	MR	
	 Gate width 	Accessible	Provided	MR	
	 Width of internal road 	NA	NA	NA	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases				
	 Upper floors 	2	5 Provided	MR	
	 Basements 	1	2 Provided	MR	
	b. Width of staircases		\		
	• Upper floors	Block 1=2X1.5m,	137 cm, 138 cm, 139 cm, 122 cm, 124	MR	
	• Basements	Block	108 cm, 130	MR	
	Description of the	2=1X1.5m	cm		
	c. Protection of exits				
	• Fire check door	NA	NA	NA	
	• Pressurization	NA	NA	NA	
	d. No of continuous staircase to terrace	Required	Provided	MR	
	e. Width Of Corridor	1.5 m	230 cm	MR	
	f. Door Size	1 m	Provided	MR	
	Compartmentation				
	Fire check door	NA	NA	NA	

I)	10
N	19
, -	

		,,,		
	 Sealing of electrical shafts 	NA	NA	NA
	 Fire Rating of shaft door 	NA	NA	NA
	Water Curtain	NA	NA	NA
	• Fire Dampers	NA	NA	NA
4.	Smoke managements System			
1.	Basements	Required	Provided	MR
	Upper floors	NA	NA	NA
5.	Fire Extinguishers	1111	7	
٥.	Total numbers	12 nos.	27 Provided	MR
K		ABC, CO ₂	Provided	MR
	• Types	ISI marked	Provided	MR
_	IS marking First Add Hear Peals	151 marked	Tiovided	17110
6.	First – Aid Hose Reels	Block 1= 2 on	Provided	MR
	• Total numbers on each	each floor,	Trovided	IVIIC
	floor	Block 2=1 on		
		each floor		
	I 41 61 1 hogg	30m	Provided	MR
	• Length of hose reel hose	5mm	Provided	MR
7	Nozzle diameter Automic fine detection and alar	The state of the s	TTOVIGEG	IVIIC
7.	Automatic fire detection and alar	NA	NA	NA
	• Type of detectors	NA NA	NA NA	NA
	• Location of Main Panel	NA NA	NA NA	NA NA
	• Location of Repeater	INA	IVA	INA
	Panel	NA	NA	NA
	Alternate source of	INA	INA	IVA
	power • Hooters' Location	NA	NA	NA
8.	MOEFA	NA	NA	NA
9.	Public Address System	NA	NA	NA
10.	Automatic Sprinkler System			
	Basements	Required	Provided	MR
	Upper Floor	NA	NA	NA
	Sprinkler above false	NA	NA	NA
	ceiling	<u></u>		
11.	Internal Hydrants:			
	Size of riser/down-	100 mm	Provided	MR
	comer			2
	 Number of hydrants per 	Block 1= 2 on	Provided	MR
	floor	each floor,		
		Block 2=1 on		
	W 1 - 12 - 12 - 12 - 12 - 12 - 12 - 12 -	each floor		
		Required	Provided	MR
	 Hose Box 	-		
12.	Hose Box Yard Hydrants			
12.		NA	NA	NA
12.	Yard Hydrants • Total number of		NA	NA
12.	Yard Hydrants • Total number of hydrants		NA NA	NA NA
	Yard Hydrants Total number of hydrants Hose Box	NA		
12.	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements:	NA		
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements: Ground Level	NA NA	NA	
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements: Ground Level Discharge of main pump	NA NA	NA NA	NA NA
	Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements: Ground Level	NA NA	NA	NA

		N/10 -				
	Jockey pump out put	NA	NA	NA		
	Jockey pump head	NA	NA	NA		
	Standby Pump out put	NA	NA	NA		
7	Standby Pump Head	NA	NA	NA		
	Auto Staring/Manual	NA	NA	NA		
	stopping			1000 3000 300		
	Pump House Access	NA	NA	NA		
	Terrace level					
	Discharge of pump	450 lpm & 180	Provided	MR		
	11 - 1 - C - 1	lpm				
	Head of the pump	40 m	Provided	MR		
	Power supply	Required	Provided	MR		
	Auto starting of pump	Required	Provided	MR		
14. Captive water Storage for fire fighting:						
	 Under ground tank 	NA	25,000 litres	NA		
	capacity		provided			
	Draw off connection	NA	NA	NA		
	Fire service inlet	NA	NA	NA		
	Access to tank	NA	NA	NA		
	 Overhead Tank capacity 	5,000 Litres	10,000 litres	MR		
			Provided			
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	Pressurization of Lift	NA	NA	NA		
	Shaft					
	Pressurization of lift	NA	NA	NA		
	lobby					
	Communication in lift	NA	NA	NA		
	Car					
	Fireman's Grounding Switch	NA	NA	NA		
	➤ Lift Signage	3.1				
	Lift Signage	NA	NA	NA		
17.	Standby power supply	NA	NA	NA		
18.	Refuge Area			11/1		
	> Total area	NA	NA	NA		
	Location	NA	NA	NA		
19.	Fire control room	1	2.12.2	1111		
	Detector system panel	NA	NA	NA		
	> Flow Switch Panel	NA	NA	NA		
	PA System Panel	NA	NA	NA		
	Battery backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20.	Special Fire Protection Systems	NA	NA	NA		
	for Protection of special Risks,		- 14 4	1121		
	if any:			*		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide Letter No. F6/DFS/MS/2011/1557 Dated 12-07-2011 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Impacting Officer

Signature of the Inspecting Officer

Nami 12