GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/GH/2016/M02/384

Dated: 10/2/16

FIRE SAFETY CERTIFICATE

Certified that the Hotel Ashoka International located at 3382, Christian Colony, D.B.G Road, Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor, Mezzanine floor + Four Upper floors, using basement as hall, ground floor as reception and three guest rooms, mezzanine floor as office (between staircase area), first, second & third floor each having six guest rooms respectively, fourth floor having one guest room, one hall, one store with pantry (Total 22 guest rooms) was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2013/542 dated 10-07-2013. The premises was re- inspected by the officer concerned of this department on 05-03-2016 in the presence of Sh. Vinay Sheel Gautam (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 22 guest rooms with effect from Lo. Lo. 2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on 10/9/2016 at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Ph. 011-23414333

Copy to:-

1. Mr. Ashok Shukla (Owner), Hotel Ashoka International, 3382, Christian Colony, D.B.G. Road, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	. Name	CONTRACTOR OF THE PROPERTY OF	CCTION REPORT Hotel Ashoka Interna	ational, 3382, Chris	tian Colony, D.B.G Ro		
			Karol Bagh, New Del				
2	2. Type	of Occupancy	: Residential (G.H.) B		est rooms-22		
3		of Case	: Renewal				
4	. Detai	ls of Previous NOC	: F.6/DFS/MS/GH/20	13/542 dated 10/0	7/2013		
5	5. Fire S	afety directives letter No	: N/A				
6	. Date	of inspection	: 05/03/2016				
7		e of Inspecting Officer	: Dy. C.F.O Rajesh Par				
8		e and designation of officers		v			
		the building side	: Sh. Vinay Sheel Gau	ıtam (Manager)			
		of Construction :	: Before 2005	_			
	10. Applicant's letter No.		Nil dated 24.02.2016				
S. No.	1	<mark>num Standards on fire preventi re safety U/R 33</mark>	on NBC/BBL Requirement	Provided at site	Remarks MR/NMR		
1.		s to building	2				
	•	Road width	Accessible	18 mtr	MR		
	•	Gate width	NA	NA	NA		
	•	Width of internal road	NA	NA	NA		
2.	Numb	er, Width, Type & Arrangemen	nt of Exits				
		nber of staircases					
	•	Upper Floors	One	One	MR		
	•	Basements	One	One	MR, Old Case		
	b. Wid	dth of staircases					
			125 cms	118 to 120 cms	MR, Old Case		
	•	Upper Floor	125 cms	177 cms	MR, Old Case		
	•	Basements	123 01118	177 01115	Titt, Old Case		
	c Dro	tection of exits	NT 4	D.T.A.	NT A		
	C. PIO	Fire check door	NA	NA	NA		
		Pressurization	NA	NA	NA		
	d No	o. of continuous staircases to					
		race	One	One	MR		
		idth of Corridor	1.0 Mtr	1.50 Mtr	MR		
	f. Do	oor Size	1.0 Mtr.	78cm X 202 cm	MR, Old Case		
3.	Comm	partmentation					
J.	Comp		NA	NA	NA		
	•	Fire check door					
	•	Sealing of electrical shafts	NA	Sealed	MR		
	•	Fire Rating of shaft door	NA	NA	NA		
	•	Water Curtain	NA	NA	NA		
	•	Fire Dampers	NA	NA	NA		
4.	Smok	e Management System					
		Basements	30 ACPH	Exhaust fans are	MR		
		<u>Jasements</u>		provided			
		Upper floors	12 ACPH	Natural	MR		
				Ventilation			
5.	Fire F	Extinguishers		J			
		Total numbers	02 at each floor	Provided	MR		
		Types	ABC, Co2, WCO2	Provided	MR		
		IS marking	ICI marks d	ISI marked	MR		
6	Eine4	Aid Hose Reels	ISI marked	151 marked	1,111		
6.		Total numbers on each floor	One	Provided	MR		
	•		30 m	Provided	MR		
	•	Length of hose reel hose Nozzle diameter	5 mm	Provided	MR		

	Automatic fire detection and alarming sys	NA	NA	NA
	Type of detectors	NA -	NA	NA
	Location of Main Panel	NA -		NA
	Location of Repeater Panel	2	NA NA	MR
	Alternate source of power	NA NA	NA NA	NA
	Hooters' Location MOEFA	Required	Provided	MR
•	Public Address System	Required	Provided	MR
0.	Automatic Sprinkler System	-		
	Basement	Required	Provided	MR
	Bussinsin	NA	NA	NA
	Ground Floor	NA	NA	. NA
	 Sprinkler above false ceiling 			
1.	Internal Hydrants		D.T.A.	NA
	Size of riser/down-comer	NA	NA	NA NA
	 Number of hydrants per floor 	NA	NA	NA
	Hose Box	NA	NA	TALX
2.	Yard Hydrants		D.T.A.	NA
	Total number of hydrants	NA	NA	NA NA
	Hose Box	NA	NA	INA
13.	Pumping Arrangements			
	Ground Level		NT A	NA
	Discharge of main Pump	NA	NA	NA NA
	➤ Head of Main pump	NA	NA	
	Number of main pumps	NA	NA	NA
	> Jockey Pump out put	NA	NA	NA
	Jockey pump headStandby Pump out put	NA	NA	NA
	> Standby Pump Head	NA	NA	NA
	> Auto Starting/Manual	NA	NA	NA
	Stopping	NA	NA	NA
	> Pump House Access	IVA	1111	
	Terrace level	450 I DM	450 LPM	MR, Old Case
	Discharge of pump	450 LPM		MR, Old Case
	Head of the pump	30 M	24 M	
	Power Supply	Required	Provided	MR
	Auto Starting of pump	NA	NA	NA
14.	 Captive Water Storage for fire fighting Underground tank capacity 	NA	NA	NA
	● Underground tank capacity > Draw-off connection	NA	NA	NA
	> Fire service inlet	NA	Provided	MR
	> Access to tank	NA	NA	NA
	Overhead Tank capacity	5000 Ltr	5000 Ltr	MR, Old Case
		Required	Provided	MR
15.	Exit Signage.			
16.	Provision of Lifts.	371	NA	NA
	 Pressurization of Lift Shaft 	NA		NA
	 Pressurization of Lift lobby 	NA	NA D idad	MR
	 Communication In lift Car 	Required	Provided	
	 Fireman's Grounding Switch 	Required	Provided	MR
	Lift Signage	Required	Provided	MR

17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.			
	> Total Area	NA	NA	NA
	> Location	NA	NA	NA
19.	Fire Control Room			
	Detector System Panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
	PA System Panel	NA	NA	NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
20.	Special Fire Protection System for Protection of special Risks, if any:	NA	NA	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2013/542 dated 10.07.2013 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting Officer

Name:- Rajesh Panwar

Designation:- Dy. C.F.O (NDZ)

Signature of Inspecting Officer

Name

Designation