GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/GH/2016/MO2) 186

Dated: 10/7/16

FIRE SAFETY CERTIFICATE

Certified that the Guest House Inn Tawang located at 8A/32, WEA, Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor + Three Upper floors, using basement as storage, Ground floor as reception, office, pantry and one guest room, first, second & third floor each having six guest rooms respectively (Total 19 guest rooms), a staff room in temporary shed on terrace was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2013/159 dated 09-04-2013. The premises was re- inspected by the officer concerned of this department on 29-02-2016 in the presence of Mr. Rajeev Sharma (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 19 guest rooms with effect from -15-1-2016 for a period of three years in accordance with rule 19 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on 10/2/2016 at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Ph. 011-23414333

TU.

1. Mr. Dorjee Wangdi Dewatshang (Owner), Guest House Inn Tawang, 8A/32, WEA, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

INSPECTION REPORT

Name & address of the building
 Type of Occupancy
 G.H Inn Tawang, 8A/32, WEA, Karol Bagh, N.D-05.
 Residential (G.H.) B+G+3 Floor total guest rooms-19

3. Type of Case : Renewa

4. Details of Previous NOC : F.6/DFS/MS/GH/2013/159 dated 09/04/2013

5. Fire Safety directives letter No : N/A

6. Date of inspection : 29/02/2016

7. Name of Inspecting Officer : Dy. C.F.O Rajesh Panwar

8. Name and designation of officers

From the building side : Sh. Rajeev Sharma (Manager)

9. Year of Construction : 2010-11

S. No.	Minimum Standards on fire preven and fire safety U/R 33	tion NBC/BBL Requirement	Provided at site	Remarks MR/NMR				
l.	Access to building	`		1.00				
	 Road width 	Accessible	18 mtr	MR				
	Gate width	NA	NA	NA				
	 Width of internal road 	NA	NA	NA				
2.	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases							
	 Upper Floors 	One	One	MR, Old Case				
	 Basements 	Two	Two	MR				
	b. Width of staircases							
		125 cms	125 cms	MR, Old Case				
	Upper Floor	125 cms	125, 72 cms	MR, Old Case				
	• Basements							
	c. Protection of exits	NA	NA	NA				
	Fire check door	NA	NA NA	NA				
	Pressurization	NA	INA	INA				
	d. No. of continuous staircases to			1.00				
	terrace	One	One	MR				
	e. Width of Corridor	1.0 Mtr	1.35, 2.30 Mtr	MR				
	f. Door Size	1.0 Mtr.	90cm X 202 cm	MR, Old Case				
3.	Compartmentation							
	Fire check door	NA	NA	NA				
	 Sealing of electrical shafts 	NA	Sealed	MR				
	 Fire Rating of shaft door 	NA	NA	NA				
	Water Curtain	NA	NA	NA				
	Fire Dampers	NA	NA	NA				
4.	Smoke Management System	IVA	1471	1111				
4.		20 A CDI I	Exhaust fans are	MR				
	Basements	30 ACPH	provided	IVIIX				
		12 ACPH	Natural	MR				
	• Upper floors	12 ACI II	Ventilation					
5.	Fire Extinguishers							
J.	Total numbers	02 at each floor	Provided	MR				
	• Types	ABC, Co2, WCO2	Provided	MR				
	IS marking	ISI marked	ISI marked	MR				
6.	First-Aid Hose Reels	101 marked	and the second					
0.	Total numbers on each floor	One	Provided	MR				
	Length of hose reel hose	30 m	Provided	MR				
	LCHELI OI HOSC ICCI HOSC							

7.	Automatic fire detection and alarming sys	tem					
	Type of detectors	NA	NA	NA			
	 Location of Main Panel 	NA	NA	NA			
	 Location of Repeater Panel 	NA	NA NA	NA MR			
	 Alternate source of power 						
	· · · · · · · · · · · · · · · · · · ·	NA NA	NA	NA			
8.	Hooters' Location MOEFA	Required	Provided	MR			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System	required	Tiorided	17111			
	Basement	NA	NA	Area less than 200 sq.m			
	Ground Floor	NA	NA	NA			
	Sprinkler above false ceiling	NA	NA	NA			
11.	Internal Hydrants						
	Size of riser/down-comer	NA	NA	NA			
	Number of hydrants per floor	NA	NA	NA			
	Hose Box	NA	NA	NA			
12.	Yard Hydrants						
	 Total number of hydrants 	NA	NA	NA			
12	Hose Box	NA	NA	NA			
13.	Pumping Arrangements						
	Ground Level	27.1					
	Discharge of main Pump	NA	NA	NA			
	Head of Main pumpNumber of main pumps	NA	NA	NA			
	> Jockey Pump out put	NA	NA	. NA			
	> Jockey Pump bad	NA	NA	NA			
	Standby Pump out putStandby Pump Head	NA	NA	NA			
		NA	NA	NA			
	Auto Starting/Manual	NA	NA	NA			
	Stopping	NA	NA	NA			
	Pump House Access	100 page 1850					
	Terrace level	450 LPM	450 LPM	MR			
	Discharge of pump	30 M	38 M	MR			
	Head of the pumpPower Supply		Provided				
	Power SupplyAuto Starting of pump	Required		MR			
	Auto starting or pump	NA	NA	NA			
14.	Captive Water Storage for fire fighting	:					
17.	Underground tank capacity	NA	NA	NA			
	> Draw-off connection	NA	NA	NA			
	➤ Fire service inlet	NA	NA	NA NA			
	> Access to tank	NA NA	NA	NA			
	Overhead Tank capacity			MR			
		5000 Ltr Required	5000 Ltr Provided	MR			
15.	Exit Signage.	Required	Tiovided	1411			
16.	Provision of Lifts.						
	Pressurization of Lift Shaft	NA	NA	. NA			
	Pressurization of Lift lobby	NA	NA	NA			
	Communication In lift Car	Required	Provided	MR			
	 Fireman's Grounding Switch 	Required	Provided	MR			

17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.	-		
	Total Area	NA	NA	NA
	> Location	NA	NA	NA
19.	Fire Control Room	NA NA	NA NA	NA NA
	PA System Panel	NA	NA	NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
1	Special Fire Protection System for	NA	NA	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2013/159 dated 09.04.2013 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting Office

Name: - Rajesh Panwar

Designation: - Dy. C.F.O (NDZ)

Signature of Inspecting Officer

Name

Designation