GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/GH/2016/ MD2 / 570

Dated: 12/04/16

FIRE SAFETY CERTIFICATE

Certified that New Hindustan International Dx. Guest House, 2503, Nalwa Street, Chuna Mandi, Pahar Ganj, New Delhi comprises of Ground + 03 Upper floor – Ground floor – 04 guest rooms, reception & office, 1st floor to 3rd floor - 08 guest rooms at each floor total 28 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/08 dated 05/03/2013. The premises was re-inspected by the officer concerned of this department on 05/04/2016 in the presence of Mr Mohit and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 28 guest rooms only with effect from

12-4-9-4-----2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on 12./. 5.4. /.(...... at New Delhi by.

(Dr. G.C.Misra) Director Delhi Fire Service Ph: - 011-23414333

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. The Licensee,

New Hindustan International Dx. Guest House,

2503, Nalwa Street, Chuna Mandi, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to it expiry.

| 2 | INSF | PECTION REPO | RT | | | |
|--------|--|-----------------|---|----------|--|--|
| 1.1 | Name & address of the building:- New Hindustan International Dx. Guest | | | | | |
| | House, 2503, Nalwa Street, Chuna Mandi, | | | | | |
| | Pahar Ganj, New Delhi. | | | | | |
| 2. | Type of occupancy:- | | Group A-1 Ground | | | |
| | | | + 3 Upper Floors.(28 guest rooms) | | | |
| 3. | 2 1 | Renewal | | , | | |
| 4. | Details of previous FSC:- | No. F6/DFS | No. F6/DFS/MS/GH/2013/08 dated | | | |
| | | 05/03/2013. | | | | |
| | Fire safety directives No | N/A | | | | |
| | Date of inspection:- | 05/04/16 | • | | | |
| | Name of the inspecting officer | | | | | |
| 8. | Name & designation of officer | | | | | |
| 0 | From the building side:- | Mr. Mohit. | | | | |
| | Year of construction:- | 2007. | D / 1 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 | | | |
| 10. | Applicant's letter No:- | 811/Joint.C. | P. /Lic. (H) Dated | | | |
| S.No. | Minimum Standards on fire | D | D 111 : 1 | Old Case | | |
| S.1NO. | | Requirement | Provided at site | Remarks | | |
| | Prevention and fire safety U/R 33 | (PSS Area) | PSS | MR/NMR | | |
| 1. | Access to Building | | | | | |
| | 1) Road width | N/A | 06 Mtr. | N/A | | |
| | 2) Gate width | N/A | N/A | N/A | | |
| | 3)Width of internal road | N/A | N/A | N/A | | |
| 2. | Number, Width Type & Arran | gement of Exits | | | | |
| | A. Number of staircases | | | | | |
| | 1. Upper floors | 01 No. | 01 No. | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | B. Width of staircase | | | | | |
| | 1. Upper floors | 80 cm. | 122 cms. to 125 | MR | | |
| | | | cms. | | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | C. Protection of exits | | | | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization | N/A | N/A | N/A | | |
| | D. No. of continuous | N/A | N/A | N/A | | |
| | staircase to terrace | | | | | |
| | | 000 Vac 157 / | 1 DA 1 DES 10 | | | |

N/A

N/A

N/A

N/A

N/A

N/A

30 ACPH

1 mtr.

N/A

N/A

N/A

N/A

N/A

N/A

N/A

1 mtr.

N/A

MR

N/A

N/A

N/A

N/A

N/A

N/A

E. Width of corridor

Compartmentation

1) Fire check door

4) Water curtain

5) Fire Dampers

1) Basements

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

F. Door size

3.

4.

M-12

| | 2) Upper floors | 12 A CDIV | | - |
|-----|--------------------------------------|-----------------|------------|------|
| 5. | Fire Extinguishers | 12 ACPH | Natural | MR |
| | 1) Total numbers | 1037 | | |
| | 2) Types | 10 Nos. | 10 Nos. | MR |
| | 3) ISI marking | ABC & CO | 2 ABC &CO2 | MR |
| 6. | First-Aid Hose Reel | Required | Provided | MR |
| | 1)Total number at each | 0.1 | | |
| | floor | 01 no. | Provided | MR |
| 2 | 2) Length of hose reel hose | 30 mtr. | Provided | MD |
| 7. | 3) Nozzle diameter | 5 mm. | | MR |
| 1. | Automatic Fire Detection & | Alarming System | m | MR |
| | 1) Type of detectors | N/A | N/A | 27/1 |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of nower | N/A | N/A | N/A |
| 0 | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | Required | | N/A |
| 9. | Public Address | | Provided | MR |
| | System/Intercom | Required | Provided | MR |
| 10. | Automatic Sprinkler System | | | 183 |
| | 1) Basement | N/A | 27/4 | |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A |
| | ceiling | IN/A | N/A | N/A |
| 1. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | NT/A | | |
| | 2) Number of hydrants per | N/A | N/A | N/A |
| | floor | N/A | N/A | N/A |
| | 3) Hose box | 27/4 | | |
| 2. | Yard Hydrants | N/A | N/A | N/A |
| | 1) Total number of hydrants | 2.21 | | |
| | 2) Hose box | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | Pumping Arrangement 1) Ground level | | | |
| |) o third level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| - | pump | | | IN/A |
| - | b) Head of main pump | N/A | N/A | N/A |
| - | c) Number of main pump | N/A | N/A | N/A |
| - | d) Jockey pump out put | N/A | N/A | |
| - | e) Jockey pump head | N/A | N/A | N/A |
| - | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| 5 | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | | IN/A | N/A |
| | 2) Terrace level | | | |
| | a) D' 1 | 225 LPM | 225 I D. 6 | |
| | h) Hood of | 0.0 - | 225 LPM | MR |
| | 1 P | JU IVILI. | 30 Mtr. | MR |

| | | -19-1) | | 8 | | |
|-----|---|-------------------|------------------|--------------|--|--|
| | c) Power supply | | | | | |
| | d) Auto starting of pur | Required | Provided | MR | | |
| 14. | Captive Water Storage for | mp Required | Provided | MR | | |
| | Captive Water Storage for Fire Fighting 1) Under ground tank N/A N/A | | | | | |
| | capacity | N/A | N/A | N/A | | |
| | a) Draw-off connection | n N/A | N 7 1 | | | |
| | b) Fire service inlet | N/A | N/A | N/A | | |
| | c) Access to tank | N/A | N/A | N/A | | |
| | d) Over head tank | 5,000 ltrs. | N/A | N/A | | |
| 1.7 | capacity | 3,000 Itrs. | 5,000 ltrs. | MR | | |
| 15. | Exit Signage. | Required | | | | |
| 16. | Provision of Lifts. | required | Provided | MR | | |
| | a) Pressurization of lift | | | | | |
| | shaft | N/A | N/A | N/A | | |
| | b) Pressurization of lift | | | IVA | | |
| | lobby | N/A | N/A | N/A | | |
| | c) Communication in | | | IVA | | |
| | lift car | N/A | N/A | N/A | | |
| | d) Fireman's switch | | C Company | IV/A | | |
| | e) Lift signage | N/A | N/A | N/A | | |
| 7. | Stand by Power Supply | N/A | N/A | N/A N/A | | |
| 8. | Pofess A | Required | Provided | | | |
| 0. | Refuge Area | N/A | N/A | MR | | |
| | Total area location | N/A | | N/A | | |
| | | IN/A | N/A | N/A | | |
| 9. | Fire Control Room | NI/A | | S 1967-7-198 | | |
| | | N/A | N/A | N/A | | |
| | a) Detector system panel | N/A | N/A | N/A | | |
| | | | 5 | IV/A | | |
| | , switch paller | N/A | N/A | N/A | | |
| | | N/A | N/A | | | |
| | d) Battery backup | N/A | N/A | N/A | | |
| | a) D- '11' | | - 1/2 | N/A | | |
| | e) Building floor plan | N/A | N/A | 77/4 | | |
| | Special Fire Protection System any: | for Protecti | 2.1/11 | N/A | | |
| | any: | ioi Protection of | special Risk, if | N/A | | |

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2013/08 dated 05/03/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Divisional Officer