GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ ND2/ 6/9

Dated: 21/09/16

FIRE SAFETY CERTIFICATE

Issued 21/04/16 at New Delhi by.

(Rajesh Panwar)
Dy. Chief Fire Officer
Delhi Fire Service
Ph-011-23412025

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 805/Joint C.P./Lic. (H) New Delhi dated 17/03/16.
- 2. The Manager, Suvidha Dx. Guest House at 3335, Hari Mandir, Paharganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT Suvidha Dx. Guest House located at 3335, 1. Name & address of the building Hari Mandir, Paharganj, New Delhi Residential, Sub Division-A-1 2. Type of occupancy:-Gr. + 04 Upper floors (total 2 Guest rooms) Renewal 3. Type of case:-No. F6/DFS/MS/GH/2012/34 dated 4. Details of previous FSC:-03/01/13. N/A 5. Fire safety directives No.-02/04/16 6. Date of inspection:-Sh. Manoj Kumar Sharma (ADO/CC) 7. Name of the inspecting officer:-8. Name & designation of officer Sh. Abdul (Manager) From the building side:-1990 9. Year of construction:-No. 805/Joint C.P./Lic. (H) dated 17/03/2016. 10. Applicant's letter No:-Old Case Remarks Provided at site Requirement Minimum Standards on fire S.No. MR/NMR PSS Existing Prevention and fire safety U/R 33 Access to Building 1. N/A 15 feet approx. N/A 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3) Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 01 Nos. 01 Nos. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase MR 1.01 Mtr. 0.80 mtr. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization MR 01 01 D. No. of continuous staircase to terrace N/A N/A N/A E. Width of corridor N/A N/A N/A F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. N/A N/A 30 ACPH 1) Basements MR Natural 12 a/c per 2) Upper floors hour Fire Extinguishers 5. MR 12 Nos. 12 Nos.

MAI

1) Total numbers

	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	N/A	Provided	N/A		
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants	*				
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor					
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual stopping	N/A	N/A	N/A		
	2) Terrace level					
	a) Discharge of pump	220 LPM	220 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire Fighting					
	Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		

-	Special Fire Protection System for Protection of special Risk, if any:			NA
0.	e) Building floor plan	N/A	N/A	N/A
			N/A	N/A
	d) Battery backup	N/A		N/A
	c) PA system panel	N/A	N/A N/A	N/A
	panel b) Flow switch panel	N/A	N/A	
	a) Detector system	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
18.	Refuge Area	N/A	N/A	N/A
	Stand by Power Supply	Required	Provided	MR
17.	e) Lift signage	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	lift car	N/A	N/A	N/A
	lobby c) Communication in		N/A	N/A
	shaft b) Pressurization of lift	N/A		
	a) Pressurization of lift	N/A	N/A	N/A
16.	Provision of Lifts.	1	Trovided	IVIK
15.	capacity Exit Signage.	Required	Provided	MR
	d) Over head tank	2500 ltr.	2500 ltr.	MR
	c) Access to tank	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/34 dated 03/01/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DO(CB)

lushing 5/10)16