## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6 D65 [ MS 2 16 3 9

Dated: 26/04/16

## FIRE SAFETY CERTIFICATE

(Dr.G.C.Misra)

Director,

Delhi Fire Service

Tel:-011-23414000

Copy to:

Ole

1. Shalimar Place, Plot no − 1, District Centre Shalimar Bagh.

Following fire safety directives must be adhere to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The basement shall be used strictly as per building bye laws.
- 7. The owner / occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

## INSPECTION REPORT

2. Name & address of the building: Shalimar Place located at Plot No - 1,

: (Mercantile) (Basement + Ground + 2 U Fs) District Canter Shalimar Bagh. : Renewal

Type of Occupancy

: F6/DFS/MS/DC/2013/119 Dated 26-03-2013. Type of Case

6. Fire Safety directives Letter No.: F6/DFS/MS/BP/2007/1288 dated 08-05-2007 5. Details of previous NOC

: 07-04-2016 7. Date of inspection

8. Name of the Inspecting Officer: Do West & ADO (WP)

9. Name and designation of Officer

: Mr. Gagan set from the building side

: 2007-2008 10. Year of Construction

: Nil dated - Nil 11. Applicant's letter No.

S Minimum standards on fire Provide S No prevention and fire safety U/R Requirement S site	d at Remarks MR/NMR
<ul> <li>Road width <ul> <li>Gate width</li> <li>Width of internal road</li> </ul> </li> <li>Number, width, Type &amp; Arrangements of exits</li> <li>Number of staircases <ul> <li>Upper floors</li> <li>Basements</li> <li>Width of staircases</li> <li>Upper floors</li> <li>Basements</li> <li>Providence</li> </ul> </li> <li>12 mtrs <ul> <li>4.5mtr</li> <li>Providence</li> </ul> </li> <li>15 mtr each</li> <li>5x1</li> <li>1.5 mtr each</li> <li>5x2</li> <li>1.5 mtr each</li> <li>1.5 mtr e</li></ul>	ided MR

14/11

		-		1
(	Compartmentation  Fire about door	Required	Provided	MR
Fire check door  Casling of electrical		Required	Provided	MR
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	11011404	
	<ul><li>Fire Rating of shaft door</li></ul>	Required	Provided	MR
	<ul><li>Water Curtain</li></ul>	Required	Provided	MR
		Required	Provided	MR
	• Fire Dampers	Required	1101144	
	Smoke managements System	Required	Provided	MR
	<ul> <li>Basements</li> </ul>	Required	Provided	MR
	• Upper floors	Required	TTOTTAGG	
	Fire Extinguishers	10 23	Provided	MR
	<ul> <li>Total numbers</li> </ul>	40 nos.	Provided	MR
	<ul> <li>Types</li> </ul>	ABC & CO <sub>2</sub> ISI marked	Provided	MR
	<ul> <li>IS marking</li> </ul>	1SI markeu	Tiovided	17111
	First – Aid Hose Reels			
	*		05 Provided	MR
	<ul> <li>Total numbers on each</li> </ul>	3	US FIOVICEU	IVIIC
	floor	2.0	Provided	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30m	Provided	MR
	<ul> <li>Nozzle diameter</li> </ul>	5mm	Provided	IVIIX
	Automatic fire detection and ala	rming system	D '1 1	MR
	<ul> <li>Type of detectors</li> </ul>	Required	Provided	
	<ul> <li>Location of Main Panel</li> </ul>	Required	Provided	MR
	<ul> <li>Location of Repeater</li> </ul>	each floor	Provided	MR
	Panel	Required	Provided	MR
	<ul> <li>Alternate source of</li> </ul>	Required	110,100	
	power	Required	Provided	MR
1.27	<ul> <li>Hooters' Location</li> </ul>		Provided	MR ·
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Flovided	TVIIC
10.	Automatic Sprinkler System			
		Required	Provided	MR
	<ul> <li>Basements</li> </ul>		Provided	MR
	<ul> <li>Upper Floor</li> </ul>	Required	Provided	MR
	<ul> <li>Sprinkler above false</li> </ul>	Required	Tiovided	1,222
	ceiling			
11.				
11.	Internal Hydrants:	150	Provided	MR
11.		150 mm	Provided	MR
11.	Internal Hydrants:  • Size of riser/down-comer			
11.	<ul> <li>Internal Hydrants:</li> <li>Size of riser/down-comer</li> <li>Number of hydrants pe</li> </ul>		Provided  05 provided	MR MR
11.	<ul> <li>Internal Hydrants:</li> <li>Size of riser/down-comer</li> <li>Number of hydrants perfloor</li> </ul>	r 3	05 provided	MR
11.	<ul> <li>Internal Hydrants:</li> <li>Size of riser/down-comer</li> <li>Number of hydrants pe</li> </ul>			
11.	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants perfloor</li> <li>Hose Box</li> </ul>	r 3	05 provided	MR
	Internal Hydrants:  Size of riser/down-comer  Number of hydrants perfloor Hose Box Yard Hydrants	3 3	05 provided	MR
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants perfloor</li> <li>Hose Box</li> </ul>	r 3	05 provided 05 Provided	MR MR

1	3.	Pumping Arrangements:			
-		Ground Level			
		<ul> <li>Discharge of main</li> </ul>	NIA		
		pump	NA	NA	NA
		Head of main pump	NA	NIA	
		Number of main pumps	NA	NA	NA
		> Jockey pump out put	NA	NA NA	NA
		Jockey pump head	NA	NA NA	NA
		Standby Pump out put	NA	NA NA	NA NA
		Standby Pump Head	NA	NA	NA NA
		Auto Staring/Manual	NA	NA	NA
		stopping		1121	INA
		Pump House Access	NA	NA	NA
		<ul> <li>Terrace level</li> <li>Discharge of nump</li> </ul>			1111
		Discharge of pump	900 lpm &180	Provided	MR
		Head of the pump	lpm		15-00-00-00-00-00-00-00-00-00-00-00-00-00
		Power supply	40 mtrs	Provided	MR
		Auto starting of pump	Required	Provided	MR
14	. (	Captive water Storage for fire fig	Required	Provided	MR
		Under ground tank		77.	
		capacity	NA	NA	NA
		> Draw off connection	NA	DT A	
		Fire service inlet	NA	NA	NA
		Access to tank	NA	NA NA	NA
		Overhead Tank	25,000 litres	Provided	NA
		capacity	20,000 11103	Trovided	MR
15	E	xit Signage	Required	Provided	MR
16.	P	rovision of Lifts	•		TVIIC
		Pressurization of Lift	Required	Provided	MR
		Shaft  Pressurization of lift			
		Pressurization of lift lobby	Required	Provided	MR
			D		
		Car	Required	Provided	MR
		) F:	D · 1		
		Switch	Required	Provided	MR
		➤ Lift Signage	Required	D 1 1	100
17	Q.		required	Provided	MR
17. 18.	D	andby power supply	Required	Provided	MR
10,	K	efuge Area			
	a constitu	_ T	NA	NA	NA
19.	Fi	re control room	NA	NA	NA
17.	1 11	N D	0 - 1		
			Required	Provided	MR
	Contraction of the Contraction o	DAC DA	Required	Provided	MR
		Dottom 1 1	Required	Provided	MR
	Washington,	Divilding Di	Required Required	Provided	MR
			cequired	Provided	MR

		~	13	17	
20.	Special Fire Protection	Co2 flooding	Provided	MR	
20.	Systems for Protection of			1 1	1 and
	The fire protection system	ms provided in	n the building	were test checke	a and
	found functional at the time of in In view of the deemed co	ompliance of r	ninimum stan	dards on fire prevenience of the dards on fire prevenience of the dards of the dard	ention er no.
	E6/DES/MS//DC/2013/119 Date	3d 20-03-2013	renewal und	er rule 35 of the	Delhi
	Fire Service Rules 2010 is recom	nmended.			
	So Ith			Mary V	1
	Signature of the Inspecting Office			e Inspecting Office	2
			1 S	m) Shoud	nary
	Name War Vir 800		Designation	Dole	
	Designation Apply	2	Designation		