GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

E-mail: gargatul@hotmail.com, Tel:- 011-26189168

No. F6/DFS/MS/School/2016/ 52/658

Dated: 28/09/16

FIRE SAFETY CERTIFICATE

Certified that S.D.M.C Primary School located at Hari Nagar, Ashram, New Delhi- 110014 comprised of ground and one upper floor was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2012/3746 dated 10/10/2012. The school building was re-inspected by the officer concerned of this department on 21/04/2016 in presence of Ms. Sushila Monika, Principal of the school and found that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with the Directorate of Education circular No. F.6/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 and that the school building is fit for occupancy class "Educational" with effect from the date of issue of this certificate for a period of three years, subject to compliance of the under mentioned conditions.

Issued on -28-1-5-4+6- at New Delhi by.

(ATUL GARG) Dy. CHIEF FIRE OFFICER

Copy to: -

- The Principal, S.D.M.C Primary School, Hari Nagar, Ashram, New Dellii 2914116 110014.
 The Commissioner SDMC Comm
- 2. The Commissioner, SDMC, Civic Centre, Minto road, NewDelhi-110002.

Conditions for the Validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : S.D.M.C Primary School, Hari Nagar, Ashram, New Delhi-

110014

1. Type of Occupancy : Educational

2. Type of Case : Renewal

3. Details of previous NOC : F6/DFS/MS/School/2012/3746 dated 10/10/2012

4. Fire Safety directives letter No : Directorate of Education circular No. F.16/Estate/CC/Fire

Safety/2011/3298 to 3398 dated 01-03-2011.

5. Date of inspection : 21.04.2016

6. Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M.Rd)

7. Name and designation of officers

from the building side : Ms. Sushila Monika, Principal

9. Year of Construction : 2011

10. Applicant's letter No. : Nil dated 22.03.2016.

S.D.M.C Primary School is comprised of ground and one upper floor.

| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | Directorate of Education circular | Provided at site | Remarks MR/NMR | |
|-----------|---|---|----------------------|-------------------|--|
| 1 | Access to building | | | | |
| | Road widthGate width | 06 mts 4.5 mts | Provided Provided | MR MR | |
| | Width of internal road | N/A | N/A | N/A | |
| 2 | Number, Width, Type & Arrangement of Exits | | | | |
| | a. Number of staircases | | | | |
| | • Upper Floors | 02 Nos. | Provided | MR | |
| | Basements | N/A | N/A | N/A | |
| | b. Width of staircases | | | | |
| | Upper Floors | 1.5 mts or less & 0.75 mt | 1.70 mts each | MR | |
| | • Basements | N/A | N/A | N/A | |
| | c. Protection of exits | | | | |
| | Fire check door | N/A | N/A | N/A | |
| | Pressurization | N/A | N/A | N/A | |
| | e. No. of continuous staircases to terrace | 01 | Provided (02) | MR | |
| | g. Width of Corridor | N/A | N/A | N/A | |
| | h. Door Size | 1.0 mts | Provided (1.0 mt) | MR | |
| | Compartmentation. | | | × | |
| | Fire check door | N/A | N/A | N/A | |
| | Sealing of electrical shafts | N/A | N/A | N/A | |
| | Fire Rating of shaft door | N/A | N/A | N/A | |
| | Water Curtain | N/A | N/A | N/A | |
| | Fire Dampers | N/A | N/A | N/A | |

| | Basements | 30 a/c per hour | N/A | N/A | | | | |
|----|--|-----------------|------------|------|--|--|--|--|
| | Upper floors | 12 a/c per hour | N/A | N/A | | | | |
| 5 | | | | | | | | |
| 3 | Total numbers | 08 nos. | Provided | MR | | | | |
| | Types | ABC type | Provided | MR | | | | |
| | IS marking | ISI marked | Provided | MR | | | | |
| 6 | First-Aid Hose Reels. | | | | | | | |
| | Total numbers on each floor | | N/A | N/A | | | | |
| | Length of hose reel hose | 30 m | N/A | N/A | | | | |
| | Nozzle diameter | 5 mm | N/A | N/A | | | | |
| 7 | Automatic fire detection and alarming | system No | t required | | | | | |
| / | Type of detectors | N/A | N/A | N/A | | | | |
| | Location of Main Panel | N/A | N/A | N/A | | | | |
| | Location of Repeater Panel | N/A | N/A | N/A | | | | |
| | Alternate source of power | N/A | N/A | N/A | | | | |
| | Hooters' Location | N/A | N/A | N/A | | | | |
| 8 | MOEFA | N/A | N/A | N/A | | | | |
| 9 | Public Address System. | N/A | N/A | N/A | | | | |
| 10 | Automatic Sprinkler System | | | 27/1 | | | | |
| | Basement | N/A | N/A | N/A | | | | |
| | Upper Floor | N/A | N/A | N/A | | | | |
| | Sprinkler above false ceiling | N/A | N/A | N/A | | | | |
| 11 | Internal Hydrants | | | | | | | |
| | Size of riser/down-comer | N/A | N/A | N/A | | | | |
| | Number of hydrants per floor | N/A | N/A | N/A | | | | |
| | Hose Box | N/A | N/A | N/A | | | | |
| 12 | Yard Hydrants. | | | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | | | |
| | Hose Box | N/A | N/A | N/A | | | | |
| 13 | Pumping Arrangements | | | | | | | |
| | Ground Level | | | | | | | |
| | Discharge of main Pump | N/A | N/A | N/A | | | | |
| | ➤ Head of Main pump | N/A | N/A | N/A | | | | |
| | > Number of main pumps | N/A | N/A | N/A | | | | |
| | Jockey Pump out put | N/A | N/A | N/A | | | | |
| | Jockey pump head | N/A | N/A | N/A | | | | |

| 4 | Standby Pump Head | 14/11 | 14/11 | 14/21 | | |
|-----|--|-----------------|--|-------------------|--|--|
| | > Auto Starting/ Manual | N/A | N/A | N/A | | |
| | stopping | N/A | N/A | N/A | | |
| | > Pump House Access | | | | | |
| | Terrace level | N/A | N/A | N/A | | |
| | Discharge of pump | N/A | N/A | N/A | | |
| | Head of the pump | N/A | N/A | N/A | | |
| | Power Supply | N/A | N/A | N/A | | |
| 1.4 | Auto Starting of pump Continue Water Starting for five Sighting | | | | | |
| 14 | Captive Water Storage for fire fighting | 1 | DT/A | DI/A | | |
| | Underground tank capacity | N/A | N/A | N/A | | |
| | Draw-off connection | N/A | N/A | N/A | | |
| | Fire service inlet | N/A | N/A | N/A | | |
| | Access to tank | N/A | N/A | N/A | | |
| | Overhead Tank capacity | N/A | N/A | N/A | | |
| 15 | Exit Signage. | Required | Provided | MR | | |
| 16 | 6 Provision of Lifts. Not Applicable | | | | | |
| | Pressurization of Lift Shaft | N/A | N/A | N/A | | |
| | Pressurization of Lift lobby | N/A | N/A | N/A | | |
| | Communication In lift Car | N/A | N/A | N/A | | |
| | Fireman's Grounding Switch | N/A | N/A | N/A | | |
| | • Lift Signage | N/A | N/A | N/A | | |
| 17 | Standby power supply | N/A | N/A | N/A | | |
| 18 | | | | | | |
| | Total Area | N/A | N/A | N/A | | |
| | ➤ Location | N/A | N/A | N/A | | |
| 19 | Fire Control Room | | | | | |
| | Detector System Panel | N/A | N/A | N/A | | |
| | Flow Switch Panel | N/A | N/A | N/A | | |
| | PA System Panel | N/A | N/A | N/A | | |
| | Batter backup | N/A | N/A | N/A | | |
| | Building Floor Plans | N/A | N/A | N/A | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | Required | 01 ABC type fire extinguisher is provided near elect. Panel. | MR | | |
| Т | The fire protection systems provided in the | e building were | test checked and found | functional at the | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/School/2012/3746 dated 10/10/2012, renewal under the Directorate of Education circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 is recommended.

DFA is put up for approval & signature please

00(8Z) / 25/4/L

DCFO(SZ)

DIRECTORIORS

Signature of the Inspecting Officer Name (M.K. CHATTOPADHYAY)

Assistant Divisional Officer (MRD)