GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F6/OFS/ans/ Bengut/2016/402/687 Dated: 29/04/16

FIRE SAFETY CERTIFICATE

Certified that the J.R.P. Vatika Banquet Hall running at First & Second floor of building at C-25, Acharya Niketan, Opp. Mayur Vihar-1, Delhi -92, owned /occupied by J.R.P. Vatika Banquet Hall, comprised of ground, mezzanine plus two upper floors was granted fire safety certificate vide letter no. F6/DFS/MS/Banquet/2013/294 dated 14.05.2013. The building was inspected by the officer concerned of this department on 21.04.2016 in the presence of Sh. Surinder Singh Gulati and found that the building have deemed complied with the fire prevention and fire safety requirements in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 and that the first & second floor of building is fit for occupancy Group "Assembly Building/Banquet" with effect from ... 29/10/4/6... for a period of three years, subject to conditions printed overleaf.

Issued on ... 28. J. o. 14.6. at New Delhi by

(Rajesh Panwar) Dy.Chief Fire Officer Ph. 011-23412025

To,

J.R.P.Vatika Banquet Hall C-25,Acharya Niketan,Opp.Mayur Vihar-1, Delhi -92

Copy to:-

The Dy. Health Officer, East Delhi Municipal Corporation ,Health Department, Shahdara (South) Zone, Karkardooma, Shahdara, Delhi

CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management

shall be responsible.

4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.

5. This Fire Safety certificate can not be treated in any case for regularizations of

unauthorized if any.

6. "The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate, six

months prior to its expiry"

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building : J.R.P. Vatika Banquet Hall at fisrt & Second floor

at C-25, Acharya Niketan, Opp. Mayur Vihar-1, Delhi -92.

2. Type of Occupancy :Assembly3. Type of Case : Renewal

4. Details of Previous FSC : F.6/DFS/MS/Banquet/ 2013/294 dated 14.05.13

5. Fire Safety directives No : F.6/DFS/MS/BP/2013/39 dated 31.01.13

6. Date of Inspection : 21.04.167. Name of the Inspecting Officer : ADO R.K.Yadav

8. Name of the designation of Officer

From the building side : Mr.Surender Singh Gulati (Owner)

From the building side : Mr.Surer

9. Year of Construction : 1999

10.Applicant's letter No :13.04.16

10.App	olicant's letter No :13.04.16	v				
S.NO.	Minimum Standards on fire	NBC	Provided at	Remarks		
	prevention and fire safety U/R33	Requirement	Site	MR/NMR		
1	Access to building					
	 Road width 	12 Mtrs	13.5 Mtrs.	MR		
	 Gate width 	N/A	N/A	N/A		
	 Width of internal road 	N/A	N/A	N/A		
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases					
	Upper Floor	02 Nos	02 Nos.	MR		
	Basement	N/A	N/A	N/A		
	B. Width of Staircases					
	Upper Floor	1.5 M	1.5 & 1.4 M	MR		
	Basement	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	Required	Provided	MR		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to	2 No.	2 No.	MR		
	terrace	N/A	N/A	N/A		
	g. Width of Corridor	2.0 Mtr.	2 no. of 2 M	MR		
	h. Door Size	2.0	<u> </u>			
3	Compartmentation.					
	 Fire check door 	Required	Provided	MR		
	 Sealing of electrical shafts 	Required	Sealed	MR		
	 Fire rating of shaft door 	N/A	N/A	N/A		
	 Water curtain 	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	 Basement 	N/A	N/A	N/A		
	Upper floor	Required	Provided	MR		
5.	Fire Extinguisher					
	Total numbers	04 no.	14 No.	MR		
	• types	ABC & Co2	ABC & Co2	MR		
	 IS marking 	ISI marked	ISI marked	MR		
6	First-aid-Hose Reels.					
	 Total numbers of each floor 	1 no.	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	 Nozzle diameter 	5 mm	Provided	MR		

7	Automatic fire detection and alarming syste	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A	N/A		
	 Location of main panel 	N/A	N/A	N/A		
	Location of repeater panel	N/A	N/A	N/A		
	Alternate source of power	Required	Provided	MR		
	Hooters's location	Different	Different	MR		
	1 Hooters s location	Location	Location			
8	MOEFA	Required	Provided	MR		
9	Public address System.	N/A	N/A	N/A		
10	Automatic Sprinkler System.			1		
	basement	N/A	N/A	N/A		
*	upper floor	N/A	N/A	N/A		
	sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants	IN/A	11/7	14/7		
T T		100 mm	100 mm	MR		
	size of riser/down-comer	01 no.	01 no.	MR		
	Number of hydrants per floor					
	Hose Box	01 no.	01 no.	MR		
L2	Yard Hydrants.	NI/A	NI/A	N1/A		
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
L3	Pumping Arrangements.	1	21/2	1		
	Ground Level	N/A	N/A	N/A		
	Discharge of main Pump	N/A	N/A	N/A		
	Head of Main Pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A		
0	Jockey pump head	N/A	N/A	N/A		
	Standby pump out put	N/A	N/A	N/A		
	Standby pump Head	N/A	N/A	N/A		
	Auto Starting / Manual stopping	N/A	N/A	N/A		
	Pump House Access	N/A	N/A	N/A		
	Terrace Level	Required	Provided	MR		
	Discharge of pump	450 LPM	450 LPM	MR		
	Head of the Pump	40 M	40 M	MR		
	Power supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for Fire Fighting.					
	 Underground tank capacity 	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	Required	Provided	MR		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	15000 Ltrs.	15000 Ltrs.	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication in lift car	Required	Provided	MR		
	8	·		0.40		
	Firemen's grounding switch	Required	Provided	MR		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
	• Location	N/A	N/A	N/A		

19	Fire Control Room			
	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	N/A	N/A
	PA system panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The fire safety certificate issued vide letter no. :F.6/DF\$/MS/Banquet/2013/294 Dated 14.05.13 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer 25 4 246

Name:-R.K.Yadav Designation:-ADO(L.N)

Submitted for approval please.

Dy CPO(NDX)

Su, FT helter as put up for ngrapus pl.