## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ NO2/667

Dated: 28/04/16

## **FIRE SAFETY CERTIFICATE**

Certified that the Shyam Palace Guest House located at 8228 & 8230, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Reception + 01 guest room), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (04 guest rooms at each floor), and terrace floor (02 guest rooms), total 15 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/3999 dated 25/10/12. The premises was re-inspected by the officer concerned of this department on 09/04/16 in the presence of Sh. Virender (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 15 guest rooms only with effect from - 28/64-/--- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 28/04/16--at New Delhi by.

(Rajesh Panwar) Dy. Chief Fire Officer Delhi Fire Service

Ph-011-23412025

Copy to:-

Olem 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. no. 853/Joint C.P./Lic. (H) dated 22/03/16.

2. The Manager, Shyam Palace Guest House at 8228 & 8230, Arakashan Road, Pahar Ganj, New Delhi

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPECTION REPORT					
1.	Name & address of the building Shyam Palace Guest House located at 82					
			rakashan Road, Pa	har Ganj,		
_		New Delh				
2.	Type of occupancy:- Residential, Sub Division-A-1					
3	Gr. + 03 Upper floors (total 15 Guest rooms) Renewal A. Details of previous FSC:-  No. F6/DFS/MS/GH/2012/3999 dated 25/10/12.					
т.						
5.	Fire safety directives No	N/A				
	Date of inspection:-	09/04/16				
	Name of the inspecting officer					
	Name & designation of officer	J.	(	- 0, 00)		
	he building side:-		der (Manager)			
9.	Year of construction:-	1990				
10.	Applicant's letter No:-	853/Joint C	.P./Lic. (H) dated 2	2/03/2016.		
-	T			Old Case		
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks		
	Prevention and fire safety	Existing	PSS	MR/NMR		
1	U/R 33			- 2		
1.	Access to Building					
	1) Road width	N/A	09 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	80 cms	1.30 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits	27/4	27/4	27/4		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization D. No. of continuous	N/A 01	N/A	N/A		
	staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	01 mtr.	01 mtr.	MR		
3.	Compartmentation	or mu.	Of filt.	IVIIX		
J.	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A N/A	N/A N/A	N/A N/A		
	3) Fire rating of shaft door	N/A N/A	N/A N/A	N/A N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
т.	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 a/c per	Natural	MR		
	2) Opper Hoors	hour	1 tataiai	1111		
			ia .			

				110
5.	Fire Extinguishers			
	1) Total numbers	08 Nos.	08 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	<b>Automatic Fire Detection &amp;</b>			
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			1,111
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	1 1/2 1	14/11	IVA
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	11//1	IVA	IN/A
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	IN/A		
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	IVA	IN/A	IN/A
13.	1) Ground level	N/A	NI/A	DT/A
	a) Discharge of main	N/A	N/A N/A	N/A
	pump	N/A	IN/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum	o N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level			
	a) Discharge of pump	225 LPM	225 LPM	MR
	b) Head of pump	25 mtr.	25 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump		Provided	MR
14.	Captive Water Storage for I		11011000	IVIIC
	1) Under ground tank	N/A	N/A	N/A
	-) Should tulk	14/11	11/11	IVIA

ten

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
		N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
5.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
10.	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
5	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/3999 dated 25/10/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dolest John 18

Dycro(HDZ)