FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2016/ W 2 742

Dated: 10/05/16

FIRE SAFETY CERTIFICATE

Certified that the Aggarwal Corporate Height, located at A-7, Netaji Subhash Place, Wazir Pur District Centre, Delhi - 110034 comprised of Basement + Ground + 15 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2013/169 dated 10-04-2013. The premises was re inspected by the officers concerned of this department on 28-04-2016 in the presence of Mr. Sunil Jain (Vice President) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Mercantile & Business Building" Group F & Group E with effect from ________ for a period of three years in accordince with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Delhi Fire Service.

Copy to:

- 1. Sh. Sunil Jain (Vice President), A-7, Netaji Subhash Place, Wazir Pur District Centre Delhi - 110034Following fire safety directives must be adhered to:-
- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Aggarwal C0rporate Height, A-7, Netaji Subhash Place, Wazir Pur District Centre, Delhi – 110034.

2. Type of Occupancy

: Mercantile + Business (Mixed), (Basement +

Ground + 15 Upper Floors)

3. Type of Case

: Renewal

4. Details of previous NOC: Letter No. F6/DFS/MS/2013/169 dated 10-04-2013

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/2007/663 dated 06-03-07

6. Date of inspection

: 28-04-2016

7. Name of the Inspecting Officer: DO (West) & ADO (WP)

8. Name and designation of Officer

from the building side

: Sh. Sunil Jain (Vice President)

9. Year of Construction

: 2008-09

10. Applicant's letter No.

: Form J dated 15-04-2016

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR
1.	Road width Gate width Width of internal road	09 m 5 m NA	Provided On open Road NA	MR MR NA
2.	 Number, width, Type & Arrange a. Number of staircases Upper floors Basements 	2 2	Provided Provided	MR MR
	b. Width of staircasesUpper floors	2x125cm	1x140cm &1x150cm	MR
9	Basements	2x125cm	1x129cm &135cm	MR
	 c. Protection of exits Fire check door Pressurization d. No of continuous 	Required Required	Provided Provided Provided	MR MR MR
	staircase to terrace e. Width Of Corridor f. Door Size	150cm 1m	Provided Provided	MR MR

C	Compartmentation	D : 1	Provided	MR		
	Fire check door	Required	Provided	MR		
	 Sealing of electrical 	Required	Provided	TVIIC		
	shafts	D !d	Provided	MR		
1	 Fire Rating of shaft door 	Required	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	1471			
5	Smoke managements System					
		20 ala non hour	Exhaust Fans	MR		
	 Basements 	30 a/c per hour	Provided			
		NA	NA	NA(Build. Not		
	 Upper floors 	INA		centralized AC)		
	E' E dia avishara					
	Fire Extinguishers					
_	Total numbers	37 nos.	Provided	MR		
		CO ₂ & ABC	Provided	MR		
	• Types	ISI marked	Provided	MR		
_	IS marking Aid Hose Reels					
	First – Aid Hose Reels • Total numbers on each	1	Provided	MR		
	floor					
	 Length of hose reel hose 	30 m	Provided	MR		
	Length of hose reer hose Naggle diameter	5 mm	Provided	MR		
	Nozzle diameter					
	Type of detectors	Smoke & Heat	Provided	MR		
	 Type of detectors Location of Main Panel 	Required	Provided	MR		
	Location of Repeater	Required	Provided	MR		
	Panel) (D		
	Alternate source of	Required	Provided	MR		
	power			MD		
	 Hooters' Location 	Required	Provided	MR		
)	MOEFA	Required	Provided	MR		
8.	Public Address System	Required	Provided	MR		
9.	Automatic Sprinkler System	*				
10.	Automatic Sprinkler System					
	Basements	Required	Provided	MR		
	• Upper Floor	Required	Provided	MR		
	• Sprinkler above false	Required	Provided	MR		
	ceiling					
11.						
11.	internal 11 district		2 11 1	MD		
	Size of riser/down-	150 mm	Provided	MR		
	comer		D 11 1	MR		
	Number of hydrants pe	r 1	Provided	IVIIV		
	floor		D :1-1	MR		
	Hose Box	Required	Provided	IVIIX		
12			- 11	NIA		
12	• Total number of	NA	Provided	NA NA		
	hydrants	NA	Provided	NA		
	Hose Box					

	P	umping Arrangements			
		Ground Level		A CONTRACTOR OF THE CONTRACTOR	
		Ground LevelDischarge of main pump	2850 lpm	Provided	MR
		Discharge of man pass-p	80 m	Provided	MR
			2	Provided	MR
			2x180 lpm	Provided	MR
		1 1	80 m	Provided	MR
			2850 lpm	Provided	MR
		- 11 D II J	80m	Provided	MR
		Auto Staring/Manual	Required	Provided	MR
3		stopping > Pump House Access	Required	Provided	MR
		-	Required	110	
		• Terrace level	NA	NA	NA
		Discharge of pumpHead of the pump	NA	NA	NA
The second second				NA	NA
		Power supplyAuto starting of pump	NA	NA	NA
-			NA 1 times	11/11	
1	4.	Captive water Storage for fire fig	nung		
-			2,00,000 litres	Provided	MR
-	0	 Under ground tank 	2,00,000 111168	110 1100	
THE RESIDENCE OF		capacity	Dogwinad	Provided	MR
		> Draw of connection	Required	Provided	MR
		> Fire service inlet	Required	Provided	MR
Name and Address of the Owner, where the Owner, which is the Owner, where the Owner, which is the Own		> Access to tank	Required	Provided	MR
		 Overhead Tank capacity 	20, 000 litres	Provided	MR
1	5	Exit Signage	Required [Fig. 15th Fg]	Tiovided	
1	6.	Provision of Lifts (Lift Run from	1 GF to 13 FS)	Provided	MR
		Pressurization of Lift Shaft	Required		
		Pressurization of lift lobby	Required	Provided	MR
		Communication in lift	Required	Provided	MR
		Car > Fireman's Grounding	Required	Provided	MR
		Switch > Lift Signage	Required	Provided	MR
-	17.	Standby power supply	Required	Provided	MR
-	18.	Refuge Area			1.00
-	10.	> Total area	Required	Provided	MR
		> Location	5 th , 7 th , 10 th	Provided	MR
	A CONTRACTOR OF THE PERSON OF	Location	Floor		
-	10	Fire control room			
	19.	THE Control room	p		3.00
-		> Detector system panel	Required	Provided	MR
		Flow Switch Panel	Required	Provided	MR
		D - 1	Required	Provided	MR
	Domonto Paris		Required	Provided	MR
		Battery backupBuilding Floor Plans	Required	Provided	MR

	Costoms	Manual CO2	Provided	MR
.0.	Special Fire Protection Systems for Protection of special Risks,			
	if any;			1.12

The fire protection systems provided in the building were test checked and found

functional at the time of inspection. In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide Letter No. F6/DFS/MS/2013/169 dated 10-04-2013 renewal under rule 35 of the Pelhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Udas Viv big 2

Signature of the Inspecting Officer

Name Somil chordhany

Designation

Designation 50/w