FOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI JEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

76.018/MS/GH/2016/ ND2/739

Dated:

10/05/16

FIRE SAFETY CERTIFICATE

Certified that the Benz International Guest House located at 10175/1, Naiwalan, WEA, Bagh, New Delhi-110005 comprises of Basement, Ground floor + Three Upper floors, using as storage, Ground floor as reception, office and four guest house, first & second floor each men guest rooms respectively, third floor having three guest rooms and store al guest rooms) was granted NOC by this department and S/MS/GH/2013/NDZ/1054 dated 09-10-2013. The premises was re-inspected by the officer of this department on 04-05-2016 in the presence of Sh. Shokat Ali Khan and found that the guest house building have deemed complied with the fire prevention and fire safety requirements to ad unce with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for me co class Residential, Sub-Division A-1 Guest House for 21 guest rooms with effect from 16/05/ 2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or concelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Somire Rules, 2010.

(Rajesh Panway Dy. Chief Fire Officer Ph. 011-23412025

Prayeen Manchanda (Owner), Benz International Guest House, 10175/1, Naiwalan, WEA, Bagh, New Delhi-110005.

litten for the validity of fire safety certificate

- the fire safety arrangements provided therein shall be maintained in good working reaction at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on arraw.dfs.delhigovt.nic.in.
- As y loss of life or property due to non-functional fire safety measures shall be at the coronsibility of the management.
- The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its

1						
	INSPECT	ON REPORT				
1.	AND THE PARTY OF THE CONTROL OF THE PARTY OF					
2.		Residential (G.H.) B+G+3 Floor total guest rooms-21				
3.	,	enewal				
4.		.6/DFS/MS/GH/20	013/NDZ/1054 date	ed 09/10/2013		
5.	Fire Safety directives letter No : N	I/A				
6.		4/05/2016				
7.	Name of Inspecting Officer : D	y. C.F.O Rajesh Pa	anwar	- ×		
8.	8. Name and designation of officers					
	From the building side : S	Sh. Shokat Ali Khar	n			
9.		2009				
		Nil dated 19.04.20				
S. No.	Minimum Standards on fire prevention	NBC/BBL	Provided at site	Remarks		
	and fire safety U/R 33	Requirement		MR/NMR		
1.	Access to building	Accessible	04 mtr approx	MR, Old Case		
	Road width	NA	NA NA	NA		
	• Gate width	NA	NA	NA		
2	Width of internal road New York Wilds True & Assumption of					
2.	Number, Width, Type & Arrangement of a. Number of staircases	EXITS				
	Upper Floors	One	One	MR		
	Basements			One, MR Old Case		
	b. Width of staircases	One	One	One, IVIK Old Case		
	b. Width of stancases			100 0110		
	Upper Floor	80 cms	120cm to 135cm			
	Basements	100 cms	110cm to 125cm	MR, Old Case		
~						
	c. Protection of exits	NA	NA	NA		
	Fire check door	NA	NA	NA		
	 Pressurization 					
22	d. No. of continuous staircases to	One	One	MR		
	terrace e. Width of Corridor	NA	NA	NA		
	e. Width of Corridor					
	f. Door Size		82 cm X 206 cm	NA NA		
			02 cm 7 200 cm	1 1121		
3.	Compartmentation	NIA	NA	NA		
	Fire check door	NA		3		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain Time Daymana	NA	NA	NA		
	Fire Dampers	NA	NA	NA		
4.	Smoke Management System					
	 Basements 	30 ACPH	Exhaust fans are	MR		
		10 1 CDV	provided Natural	MR		
	 Upper floors 	12 ACPH	Ventilation	IVIIC		
_	T' F ' L					
5.	Fire Extinguishers	10 Nos	Provided	MR		
	• Total numbers	ABC, WCO2	Provided	MR		
	• Types		The Harden of Children and Child	MR		
	IS marking	ISI marked	ISI marked	IVIK		
6.	First-Aid Hose Reels	0	Provided	MR		
	Total numbers on each floor	One 30 m	Provided	MR		
	• Length of hose reel hose	5 mm		MR		
	Nozzle diameter	J IIIII	Provided	IVIK		

7.	Automatic fire detection and alarming sy			
	 Type of detectors 	NA	NA	NA
	 Location of Main Panel 	NA	NA	NA
	 Location of Repeater Panel 	NA	NA	NA
	 Alternate source of power 	NA	NA	MR
	I I I I I I I I I I I I I I I I I I I	NA NA	NA	NA
3.	Hooters' Location MOEFA	Required	Provided	MR
).	Public Address System	Required	Provided	MR
0.	Automatic Sprinkler System	Required	Tiovided	IVIIC
.0.	Basement	NA	NA	Area less than 200
		4		sq.m
	Ground Floor	NA	NA	NA
	 Sprinkler above false ceiling 	NA	NA	NA
1.	Internal Hydrants			
	Size of riser/down-comer	NA	NA	NA
	 Number of hydrants per floor 	NA	NA	NA
	Hose Box	NA	NA	NA
12.	Yard Hydrants			
	 Total number of hydrants 	NA	NA	NA
	Hose Box	NA	NA	NA
3.	Pumping Arrangements			9
	Ground Level			
	Discharge of main Pump	NA	NA	NA
	Head of Main pump	NA	NA	NA
	> Number of main pumps	NA	NA	NA
	> Jockey Pump out put	NA	NA	NA
	Jockey pump headStandby Pump out put	NA	NA	NA
	> Standby Pump Head	NA	NA	NA
	> Auto Starting/Manual			
	Stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
	Terrace level			
	Discharge of pump	450 LPM	450 LPM	MR
	Head of the pump	35 M	35 M	MR
	Power Supply	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
			9	
4.	Captive Water Storage for fire fighting	NIA	NIA	NIA
	 Underground tank capacity Draw-off connection 	NA	NA	NA
	> Draw-off connection . > Fire service inlet	NA	NA	NA
	Access to tank	NA	NA	NA
	Overhead Tank capacity	NA	NA	NA
	a tallicad rails capacity	5000 Ltr	5000 Ltr	MR
15.	Evit Signago	Required	Provided	MR
13.	Exit Signage.			
16.	Provision of Lifts.Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of Lift Shart Pressurization of Lift lobby			
	Communication In lift Car	NA Paguirad	NA Provided	NA MR
	Fireman's Grounding Switch	Required		
	Lift Signage	Required	Provided	MR
	Littoigliage	Required	Provided	MR

17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.			
10.	> Total Area	NA	NA	NA
	> Location	NA	NA	NA
19.	Fire Control Room			
17.	Detector System Panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
	PA System Panel	NA	NA	NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
20.	Special Fire Protection System for Protection of special Risks, if any:	NA	01 Co ₂ & 01 ABC fire extinguisher provided near electric panel	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2013/NDZ/1054 dated 09.10.2013 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting Off

Name: - Rajesh Panwar

Designation: - Dy. C.F.O (NDZ)

Signature of Inspecting Officer

Name

Designation