GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/GH/2016/ ND2 / 752

Dated: 11/05/16

FIRE SAFETY CERTIFICATE

(Rajesh Panwar) Dy. Chief Fire Officer Ph:-011-23412025

one

Copy to:-

- 1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 972/Joint C.P./Lic.(H) dated New Delhi 28-04-2016
- 2. Sh. Sukhpal Singh (Owner), Guest House Rama Deluxe, 2278-79, Chowk Gurudwara Road, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

| <u> </u> | The state of the s | | | | | |
|----------|--|--|--------------------------|-------------------|--|--|
| 3 | | ION REPORT | | | | |
| | 1. Name & address of the building : G.H Rama Deluxe, 2278-79, Chowk Gurudwara F | | | | | |
| | | Karol Bagh, New Delhi-110005. | | | | |
| · 2 | | Residential (G.H.) G+Mezz+3 Floor total guest rooms-25 | | | | |
| | | Renewal F.6/DFS/MS/GH/2013/204 dated 25/04/2013 | | | | |
| | | | | | | |
| | Fire Safety directives letter No : N/A | | | | | |
| | · | 06/05/2016 Dy. C.F.O Rajesh Pa | | | | |
| | * | | | | | |
| , | 8. Name and designation of officers From the building side : | | | | | |
| | | | | | | |
| | | Before 1990 | Lic.(H) dated 28.04.2016 | | | |
| C N | | | | | | |
| S. No. | Minimum Standards on fire prevention | NBC/BBL | Provided at site | Remarks MR/NMR | | |
| 1. | and fire safety U/R 33 | Requirement | | IVIN/IVIN | | |
| 1. | • Road width | Accessible | 12 mtr | MR | | |
| | W. 25-75 CRES (MESSAGE DE ASSESSE ASSESSES) | NA | NA | NA | | |
| | Gate width Width of internal road | NA | NA | NA | | |
| 2 | • Width of internal road | | | | | |
| 2. | Number, Width, Type & Arrangement o a. Number of staircases | LXIIS | | | | |
| | | | 0 | MP OH C | | |
| | Upper Floors | One | One | MR, Old Case | | |
| | Basements All Middle of their seasons | NA | NA | No Basement | | |
| | b. Width of staircases | | | | | |
| _ | - Unner Floor | 125 cms | 90cm to 94 cms | MR, Old Case | | |
| | Upper FloorBasements | NA | NA | No Basement | | |
| ~ | • basements | | | | | |
| | c. Protection of exits | NA | NA | NA | | |
| | Fire check door | NA | NA | NA | | |
| | Pressurization | INA | INA | INA | | |
| | d. No. of continuous staircases to | | | | | |
| * 4 | terrace | One | One | MR | | |
| | e. Width of Corridor | 1.0 Mtr | 3.0 Mtr | MR | | |
| | | | | | | |
| | f. Door Size | 1.0 Mtr. | 87 cm X 205 cm | MR, Old Case | | |
| | | | | | | |
| 3. | Compartmentation · | | - 4 | | | |
| | Fire check door | NA | NA | NA | | |
| | Sealing of electrical shafts | NA | Sealed | MR | | |
| | Fire Rating of shaft door | 2 2000 | NA | NA | | |
| | Water Curtain | NA | | | | |
| | Fire Dampers | NA | NA | NA | | |
| | | NA | NA | NA | | |
| 4. | Smoke Management System | * | | | | |
| | Basements | 30 ACPH | NA | No Basement | | |
| | | | Natural | MR | | |
| | Upper floors | 12 ACPH | Ventilation | IVIK | | |
| | | 2 2 | Viidiation | | | |
| 5. | Fire Extinguishers | | | | | |
| | Total numbers | 02 at each floor | Provided | MR | | |
| | • Types | Co2, WCO2 | Provided | MR | | |
| | IS marking | ISI marked | ISI marked | MR | | |
| 6 | First-Aid Hose Reels | 131 marked | | | | |
| 6. | | One | Provided | MR | | |
| | Total numbers on each floor Longth of boso roal boso | 30 m | Provided | MR | | |
| | Length of hose reel hose | 5 mm | Provided | MR | | |
| | Nozzle diameter | 1 | Provided | IVIN | | |
| | | | | | | |

| - 2 | 1 10 90 001 | | | X. | |
|-----|--|--------------|----------|--------------|--|
| 7. | Automatic fire detection and alarming sy | vstem | | | |
| • | Type of detectors | NA | NA | NA | |
| | Location of Main Panel | NA | NA | NA | |
| | Location of Repeater Panel | NA | NA | NA | |
| | Alternate source of power | | NA | NA | |
| | | NA | NA | NA | |
| | Hooters' Location | NA | 1111 | 1111 | |
| 3. | MOEFA | Required | Provided | MR | |
|). | Public Address System | Required | Provided | MR | |
| 0. | Automatic Sprinkler System | | | | |
| | Basement | NA | NA | No Basement | |
| | , | NA | NA | NA | |
| | Ground Floor | NA | NA | NA | |
| 4 | Sprinkler above false ceiling | | | | |
| 1. | Internal Hydrants | NA | NA | NA | |
| | Size of riser/down-comer Number of hydrants per floor | NA NA | NA NA | NA NA | |
| | Number of hydrants per floorHose Box | NA | NA | NA NA | |
| 2. | Yard Hydrants | 11/11 | 11/1 | 1111 | |
| 4. | | NA | NA | NA | |
| | Total number of hydrantsHose Box | NA NA | NA NA | NA NA | |
| 3. | Pumping Arrangements | 11/1 | 1117 | 11/1 | |
| | Ground Level | | | | |
| | Discharge of main Pump | NA | NA | NA | |
| | > Head of Main pump | NA | NA | NA | |
| | Number of main pumps | | | 174,000,000 | |
| | Jockey Pump out put | NA | NA | NA | |
| | Jockey pump head | NA | NA | NA | |
| | Standby Pump out put | NA | NA | NA | |
| | Standby Pump Head | NA | NA | NA | |
| | Auto Starting/Manual | NA | NA | NA | |
| | Stopping | NA | NA | NA | |
| | Pump House Access | | | | |
| | Terrace level | 450 LPM | 450 LPM | MR | |
| | Discharge of pump | 30 M | 30 M | MR | |
| | ➤ Head of the pump | | | | |
| | Power SupplyAuto Starting of pump | Required | Provided | MR | |
| | Auto Starting of pump | NA | NA | NA | |
| | | | | | |
| | | | | | |
| 14. | Captive Water Storage for fire fighting | NA | NA | NA | |
| | Underground tank capacity Draw-off connection | 2022 300000 | NA NA | NA NA | |
| | Fire service inlet | NA | | | |
| | > Access to tank | NA | NA | NA | |
| | Overhead Tank capacity | NA | NA | NA | |
| | 2.5edd raint capacity | 2500 Ltr | 2500 Ltr | MR, Old Case | |
| 5. | Exit Signage. | Required | Provided | MR | |
| | | | | | |
| 16. | Provision of Lifts.Pressurization of Lift Shaft | NA | NA | NA | |
| | | 1775 441 485 | | | |
| | Pressurization of Lift lobbyCommunication In lift Car | NA | NA | NA | |
| | The state of the s | NA | NA | NA | |
| | Fireman's Grounding Switch Lift Signage | NA | NA | Old Lift | |
| | Lift Signage | Required | Provided | MR | |

| 17. | Standby power supply | Required | Provided | MR |
|-----|---|----------|----------|----|
| 18. | Refuge Area. | | | |
| | > Total Area | NA | NA | NA |
| | Location | NA | NA | NA |
| 19. | Fire Control Room | 8 | | |
| | Detector System Panel | NA | NA | NA |
| | Flow Switch Panel | NA | NA | NA |
| | PA System Panel Patter backura | NA | NA | NA |
| | Batter backupBuilding Floor Plans | NA | NA | NA |
| | | NA | NA | NA |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | NA | NA | NA |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2013/204 dated 25.04.2013 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting O

Signature of Inspecting Officer

Name:- Rajesh Panwar

Name

Designation: - Dy. C.F.O (NDZ)

Designation

Direton