GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001

E-mail: gargatul@hotmail,com, Tel:- 011-26189168

No. F6/DFS/MS/School/2016/52/790

Dated: 17/5/16

FIRE SAFETY CERTIFICATE

Certified that Lions Vidhya Mandir Secondary School located at Kushak Lane, New Delhi comprised of ground plus two upper floors was granted fire safety certificate by this department vide letter No. F.6/DFS/MS/School/2013/287 dated 10-05-2013. The school building was re-inspected by the officer concerned of this department on 07/05/2016 in presence of Mr. Pradeep Kumar, Vice Principal of the school and found that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with the Directorate of Education circular No. F.6/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 and that the school building is fit for occupancy class "Educational" with effect from the date of issue of this certificate for a period of 03 (three) years, subject to compliance of the under mentioned conditions.

Issued on 17/5/16 at New Delhi by.

(ATÙL ĠARG) Dy. CHIEF FIRE OFFICER

Copy to: -

1. The Principal, Lions Vidhya Mandir Secondary School, Kushak Lane, New Delhi

2. The Director of Education, MCD (North), Kashmere Gate, Nigam Bhawan, Delhi

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

HIGH DOTTON RELIGION

1. Name & address of the building: Lion's Vidya Mandir Secondary School, Kushak Lane, New

Delhi-1

2. Type of Occupancy : Educational

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/School/2013/287 dated 10-05-2013

5. Fire Safety directives letter No : F.16/ESTATE/CC/Fire Safety/2011/3298-3398 dated 01.03.2011

6. Date of inspection : 07.05.2016

7. Name of the Inspecting Officers : M.K. Chattopadhyay, ADO (MRD)

8. Name and designation of officers

from the building side : Shri Pradeep Kumar, Vice Principal

9. Year of Construction : 1960

10. Applicant's letter No. : VM/Fire Safety/2016/6921 dated 25-04-2016

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	06 mts	11 mts	MR
	Gate width	03 mts	Provided	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangement	of Exits		
	a. Number of staircases		<u> </u>	-
	Upper Floors	04	5 stair + 01 ramp	MR
	Basements	N/A	N/A	N/A
	b. Width of staircases	_	_	
	Upper Floors	1.5 mts	1.60(2), 1.20 (2), 1.08(1), Ramp- 1.22 mts	MR
	Basements	N/A	N/A	N/A
	Protection of exitsFire check door	N/A	N/A	N/A
	Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	N/A	N/A	N/A
		02	01 stair + 01 ramp	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	N/A	N/A	N/A
	Compartmentation. Not required			
	Fire check door	N/A	N/A	N/A
	 Sealing of electrical shafts 	N/A	N/A	N/A
	• Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	• Fire Dampers	N/A	N/A	N/A
1	Smoke Management System.	Low-rise bldg,	Not required	



	Basements	30 a/c per hour	N/A	N/A			
	 Upper floors 	12 a/c per hour	N/A	N/A			
			11/12				
5	Fire Extinguishers	12	Provided	MR			
	Total numbers	ABC, CO ₂	Provided	MR			
	• Types	ISI marked	Provided	MR			
6	IS marking Is marked First-Aid Hose Reels						
0	Total numbers on each floor	01	Provided	MR			
	¥	30 m	Provided	MR			
	• Length of hose reel hose	5 mm	Provided	MR			
_	Nozzle diameter Translatestian and slarming						
7	Automatic fire detection and alarming	N/A	required N/A	N/A			
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel			500 800 800			
ē	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System						
	Basement	N/A	N/A	N/A			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	100 mm	Provided	MR			
	Number of hydrants per floor	01	Provided	MR			
	Hose Box	01	Provided	MR			
12	Yard Hydrants.						
12	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements	er floor 01 Provided 01 Provided 01 Provided 01 N/A N/A	NT/A				
	Ground Level			N/A			
	Discharge of main Pump	N/A	N/A	N/A			
	➤ Head of Main pump	N/A	N/A	N/A			
	> Number of main pumps	N/A	N/A	N/A			
	> Jockey Pump out put	N/A	N/A	N/A			
	> Jockey pump head	N/A	N/A	N/A			

	>	Standby Pump out put	N/A	N/A	N/A
	>	Standby Pump Head	N/A	N/A	N/A
	>	Auto Starting/ Manual	N/A	N/A	N/A
	,	stopping	N/A	N/A	N/A
	>	Pump House Access	N/A	N/A	N/A
	• Te	rrace level	450 LPM (2)	Provided	MR
	>	Discharge of pump	40 meters	Provided	MR
	>	1	N/A	N/A	N/A
	>	11.	-	Provided at GF	MR
1.4	Contino	Auto Starting of pump Water Storage for fire fighting			
14			N/A	N/A	N/A
		nderground tank capacity raw-off connection	N/A	N/A	N/A
		re service inlet	N/A	N/A	N/A
		ccess to tank	N/A	N/A	N/A
		verhead Tank capacity	10,000 liters	Provided	MR
15	Exit Sign	age.	Required	Provided	MR
16		of Lifts.	Not Applicable	e	
		ressurization of Lift Shaft	N/A	N/A	N/A
		ressurization of Lift lobby	N/A	N/A	N/A
		ommunication In lift Car	N/A	N/A	N/A
	• F	ireman's Grounding Switch	N/A	N/A	N/A
		ift Signage	N/A	N/A	N/A
			N/A	N/A	N/A
17		power supply			
18	Refuge A	otal Area	N/A	N/A	N/A
		ocation	N/A	N/A	N/A
19		ntrol Room	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
1)	111000	Detector System Panel	N/A	N/A	N/A
		Flow Switch Panel	N/A	N/A	N/A
		PA System Panel	N/A	N/A	N/A
		Batter backup	N/A	N/A	N/A
		Building Floor Plans	N/A	N/A	N/A
		Dulluling 1 1001 1 1alis		01 ABC type fire	MR
20	Special	Fire Protection Systems for	Required	of fibe type in	
20		Fire Protection Systems for on of special Risks, if any:	Required	extinguisher	

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/School/2013/287 dated 10-05-2013, renewal under the Directorate of Education circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 is recommended.

DFA is put up for approval & signature please

10/5/2016

Signature of the Inspecting Officer (M.K. CHATTOPADHYAY)

Assistant Divisional Officer (MRD)

DCFO (D. P. Bhardwaj)

DCFO (SZ)

13/5/15

DIRECTOR FORS Whi