GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ H02/783

Dated: 17/57/6

FIRE SAFETY CERTIFICATE

Certified that the Rachna Tourist Lodge Guest House located at 8510, Arakashan Road, Pahar Gani, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + 04 guest rooms + 01 office), 1st floor to 3rd floor (10 guest rooms at each floor) and 4th floor (05 guest rooms + 01 store+ kitchen for staff + 02 Staff rooms), total 39 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/4166 dated 07/11/12. The premises was re-inspected by the officer concerned of this department on 06/05/16 in the presence of Sh. Ravinder (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 39 guest rooms only with effect under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 17 --- at New Delhi by.

(Rajesh Panwar) Dy. Chief Fire Officer Delhi Fire Service Ph-011-23412025

Copy to:-

Olem 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager, Rachna Tourist Lodge Guest House at 8510, Arakashan Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

			JE.			
	INSI	PECTION REPO	ORT			
1.	Name & address of the building					
2.	Type of occupancy:-	Residential, Sub Division-A-1 Gr. + 04 Upper floors (total 39 Guest rooms)				
3.	Type of case:-	Renewal				
	Details of previous FSC:-	No. F6/DFS/MS/GH/2012/4166 dated 07/11/12.				
5.	Fire safety directives No	N/A				
	Date of inspection:-	06/05/16				
	Name of the inspecting officer	:- Sh. Manoj	Kumar Sharma (Al	OO/CC)		
	Name & designation of officer			,		
	he building side:-		ler (Manager)			
9.	Year of construction:-	1989				
10.	Applicant's letter No:-	No. Nil dat	ed 18/04/2016.			
				Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site PSS	Remarks MR/NMR		
1.	Access to Building	н				
	1) Road width	NA	06 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.22 to 1.35 Mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	and the formation of the formation of the					

2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements 30 ACPH N/A N/A 2) Upper floors 12 a/c per Natural MR hour

N/A

N/A

01 mtr.

N/A

N/A

01 mtr.

N/A

MR

N/A

staircase to terrace E. Width of corridor

Compartmentation

1) Fire check door

F. Door size

3.

5.	Fire Extinguishers			100	
	1) Total numbers	12 Nos.	12 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection &	Alarming Syst	em		
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	1	21011404	1711	
	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling		1111	IV/A	
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	N/A	
	floor			1771	
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement				
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump				
	b) Head of main pump	N/A	N/A	N/A	
			to the same of the		
	c) Number of main pun	np N/A	N/A	N/A	
•	c) Number of main pund) Jockey pump out put	_	N/A N/A	N/A N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	d) Jockey pump out pute) Jockey pump head	N/A N/A	N/A N/A	N/A N/A	
	d) Jockey pump out pute) Jockey pump headf) Stand by pump output	N/A N/A	N/A	N/A N/A N/A	
	d) Jockey pump out pute) Jockey pump headf) Stand by pump output	N/A N/A nt N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	
	 d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual 	N/A N/A nt N/A N/A	N/A N/A N/A	N/A N/A N/A	
	d) Jockey pump out pute) Jockey pump headf) Stand by pump outputg) Stand by pump head	N/A N/A nt N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	
	d) Jockey pump out put e) Jockey pump head f) Stand by pump outpu g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level	N/A N/A nt N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	
	d) Jockey pump out put e) Jockey pump head f) Stand by pump outpu g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump	N/A N/A N/A N/A N/A N/A 1 N/A 450 LPM	N/A N/A N/A N/A N/A 450 LPM	N/A N/A N/A N/A N/A	
	d) Jockey pump out put e) Jockey pump head f) Stand by pump outpu g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A N/A N/A N/A N/A N/A N/A 1 N/A 450 LPM 30 mtr.	N/A N/A N/A N/A N/A N/A N/A 30 mtr.	N/A N/A N/A N/A N/A N/A MR	
	d) Jockey pump out put e) Jockey pump head f) Stand by pump outpu g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A N/A N/A N/A N/A N/A N/A 1 N/A 450 LPM 30 mtr. Required	N/A N/A N/A N/A N/A N/A N/A 450 LPM 30 mtr. Provided	N/A N/A N/A N/A N/A N/A MR MR MR	
14.	d) Jockey pump out put e) Jockey pump head f) Stand by pump outpu g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A N/A N/A N/A N/A N/A N/A A Solution N/A N/A N/A A Solution N/A N/A Required Required Required	N/A N/A N/A N/A N/A N/A N/A 30 mtr.	N/A N/A N/A N/A N/A N/A MR	

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst Risk, if any: One ABC fire extin	ction of special ovided near elect, panel	MR .	

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/4166 dated 07/11/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy CAGO (NDZ)