GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

E-mail: gargatul@hotmail,com, Tel:- 011-26189168

NO.F6/DFS/MS/2016/ \$2/796

Dated: 17/5/16

FIRE SAFETY CERTIFICATE

Certified that Plot No. F-2, Block- B-1 Mohan Co-operative Industrial Estate, Mathura Road, New Delhi-44 comprised of basement, ground plus two upper floors was granted N.O.C. by this department vide letter No. F.6/DFS/MS/2011/2409 dated 04.10.2011 and was reinspected by the officer concerned of this department on 09-05-2016 in the presence of Mr. Ashok Arora (manager), and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class Industrial with effect from 17/5/16 for a period of 3 (three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 17/5/16 at New Delhi by.

(ATUL GARG)

Dy. Chief Fire Officer

Copy to: -

- 1. The Manager, Plot No. F-2, Block- B-1 Mohan Co-operative Industrial Estate, Mathura Road, New Delhi-44.
- 2. The Executive Engineer-II (Bldg.) HQ, SDMC, 8th floor, Civic Centre, Minto Road, New Delhi-110002.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Plot No. F-2, Block- B-1 Mohan Co-operative Industrial

Estate, Mathura Road, New Delhi-44

2. Type of Occupancy : Industrial3. Type of Case : Renewal

1

4. Details of previous NOC : F.6/DFS/MS/2011/2409 dated 04.10.2011

5. Fire Safety directives letter No : F.6/DFS/MS/BP/2007/3853 dated 31.12.2007.

6. Date of inspection : 09.05.2016

7. Name of the Inspecting Officers: M.K. Chattopadhyay, ADO (M. Road)

8. Name and designation of officers

from the building side : Mr. Ashok Arora (manager)

9. Year of Construction : 2011

10. Applicant's letter No. : nil dated 07.04.2016

The building is comprised of basement, ground plus two upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	09 mts	Provided	MR
	Gate width	4.5 mts	Provided	MR
	Width of internal road	Required	Provided	MR
2	Number, Width, Type & Arrangement	of Exits		
	a. Number of staircases	-	-	-
	Upper Floors	02	02	MR
	Basements	02 + 01 ramp	02 + 01 ramp	MR
	b. Width of staircases	-	-	-
	Upper Floors	1.25 mts each	1.25 mts each	MR
	Basements	1.25 mts each	1.25 mts each	MR
	c. Protection of exits	-	-	-
	Fire check door	Required	Provided	MR
	Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	02	02	MR
	g. Width of Corridor	1.50 mts	Provided	MR
	h. Door Size	1.50 mts	Provided	MR
3	Compartmentation.			
	Fire check door	Required	Provided	MR
	Sealing of electrical shafts	Required	Provided	MR
	Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	Fire Dampers			
		N/A	N/A	N/A

	Upper floors	12 a/c per hour	Naturally ventilated	MR		
5	Fire Extinguishers					
	Total numbers	24	Provided	MR		
	• Types	ABC, CO ₂ type	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	02	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming	system.				
	Type of detectors	Required	Provided (smoke, heat)	MR		
	Location of Main Panel	Required	Provided at GF	MR		
	Location of Repeater Panel	Required	Provided at GF	MR		
	Alternate source of power	Required	Provided	MR		
	Hooters' Location	Required	Provided at each floor near stairs	MR		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
	Upper Floor	Required	Provided	MR		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	100 mm	Provided	MR		
	Number of hydrants per floor	Required	Provided (2 nos.)	MR		
	Hose Box	Required	Provided (2 nos.)	MR		
12	Yard Hydrants.					
12	Total number of hydrants	Required	Provided (6 nos.)	MR		
	Hose Box	Required	Provided (6 nos.)	MR		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	2280 LPM	Provided	MR		
	➤ Head of Main pump					
	Number of main pumps	70 mts	Provided	MR		
	Jockey Pump out put	01	Provided	MR		
	> Jockey pump head	180 LPM	Provided	MR		
	> Standby Pump out put	70 mts	Provided	MR		
	Standby I amp out put	2280 I PM	Provided	MR		

Head of the pump Power Supply Auto Starting of pump Underground tank capacity Tire service inlet Overhead Tank capacity Provided Tire Startisginage. Provided Model That Access to tank Provided Model Tequired Provided Model Model Model Tequired Provided Model Mo	
• Terrace level • Discharge of pump > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump • Underground tank capacity > Draw-off connection > Fire service inlet • Overhead Tank capacity 15 Exit Signage. Pressurization of Lift Shaft • Pressurization of Lift Shaft • Pressurization of Lift Shaft • Fireman's Grounding Switch • Lift Signage • Terrace level	1R
Discharge of pump Head of the pump Head of the pump Power Supply Auto Starting of pump Underground tank capacity Fire service inlet Overhead Tank capacity Standby power supply Communication In lift Car Fireman's Grounding Switch Lift Signage Power Supply Auto Starting of pump Required Provided MRequired MRequired Provided MRequired Provided MRequired Provided MRequired Provided MRequired MRequired Provided MRequired MRequi	
Head of the pump Power Supply Auto Starting of pump Underground tank capacity Pire service inlet Overhead Tank capacity Standby power supply Captive Water Storage Provided Mequired Mequired Provided Mequired	
Power Supply Auto Starting of pump Required Required Provided M Required Provided M Required Provided M 14 Captive Water Storage for fire fighting. • Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Required Provided M Provided M Required Provided M Provided M Required Provided M Provided M Provided M Provided M Provided M Provided M N/A N/A N/A N/A N/A Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided M Required Provided M N/A N/A N/A N/A N/A N/A N/A N	1R
Auto Starting of pump Required Provided M 14 Captive Water Storage for fire fighting. • Underground tank capacity > Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity 1,00,000 lts Required Provided M N/A N/A Required Provided M • Overhead Tank capacity 15 Exit Signage. Required Provided M Required Provided M 15 Provided M 16 Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car • Fireman's Grounding Switch • Lift Signage Required Provided M	
Captive Water Storage for fire fighting. 1,00,000 lts Provided M	ſR
 Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provided Provided M Provided M Provided M Provided M Provided M Exit Signage. Required Provided M Provided M Provided M M Provided M N/A N/A N/A N/A N/A Provided M Fireman's Grounding Switch Lift Signage Required Provided M Lift Signage Required Provided (125 KVA) M 	1R
Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provided M N/A N/A N/A N/A Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided M Provided M N/A N/A N/A N/A N/A N/A N/A Provided M Required Provided M Provided M Required Provided M Required Provided M	
Fire service inlet N/A N/A N/A N/A N/A N/A N/A N/	1R
Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Required Provided M 20,000 lts Provided M Provided M Provided M Provided M Provided M Provided M N/A N/A N/A N/A N/A Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided M Required Provided Provided M Required Provided Provided M Provided	1R
Overhead Tank capacity 20, 000 lts Provided M Exit Signage. Required Provided M Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Required Provided M Lift Signage Required Provided M Standby power supply Required Provided M	I/A
Required Provided M	1R
16 Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided Provided M Provided M Required Provided M	IR
 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided Provided M Provided M Provided M Required Provided M Provided M Provided M Provided M 	I R
 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided M Provided M Required Provided M Required Provided M Provided M Provided M Provided M Provided M 	
 Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Provided M Provided M Required Provided M Required Provided M M Provided M M Required Provided (125 KVA) M 	[/A
• Fireman's Grounding Switch Required Provided M • Lift Signage Required Provided M 17 Standby power supply Required Provided (125 KVA) M	I/A
• Lift Signage Required Provided M 17 Standby power supply Required Provided (125 KVA) M	ſR
17 Standby power supply Required Provided (125 KVA) M	1R
Standby power supply	IR
	IR
18 Refuge Area.	
	Ī/A
	T/A
19 Fire Control Room	
Detector System Panel Required Provided M	ÍR.
• Flow Switch Panel Required Provided M	IR
PA System Panel Required Provided M	IR
Batter backup Required Provided M M M M M M M M M M M M M	IR
Building Floor Plans N/A N/A N/A	/A
20 Special Fire Protection Systems for Protection of special Risks, if any Required Provided 02 ABC type fire extinguishers near elect. Panel	IR

The fire protection systems provided in the building were checked and found functional at the time of inspection.

All the shortcomings pointed out by this department vide letter no. F.6/DFS/MS/2015/2504 dated 04.12.2015 have been rectified by the building management.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/2011/2409 dated 04.10.2011, renewal under the Delhi Fire Service Act-2007 & Delhi Fire Service Rules- 2010 is recommended.

OCEO (D. P. Phondylai)

DCFO (D.P. Bhardwaj)

DCFO (SZ)

OIRACTORIOAS PONS

M.K.CHATTOPADHYAY Asstt. Div. Officer (M. Road)