## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/GH/2016/ MD2 / 839

Dated: 20/05/16

## FIRE SAFETY CERTIFICATE

Certified that M/s Satyam Guest House located at 5134-35, Main Bazar, Pahar Ganj, New Delhi comprises of Ground + 03 Upper floor, Ground floor reception + 08 guest rooms, 1st floor 10 guest rooms + office + store, 2nd floor + 11 guest rooms + store, 3nd floor + 10 guest rooms total 39 guest rooms was granted FSC by this department vide letter No.F6/MS/DFS/GH/2013/581 dated 12/02/2013. The premises was re-inspected by the officer concerned of this department on 18/05/2016 in the presence of Mr. Bhagwan Singh (G. M.) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 39 guest rooms only with effect from

2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on ... 2016 for a Period Office Rules, 2010. mentioned below.

(Rajesh Panwar)
Dy. Chief Fire Officer
Delhi Fire Service
Ph: - 011-23412025

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

 The Licensee, M/s Satyam Guest House
 5134-35, Main Bazar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to it expiry.

				INSI	PECTION	N REPORT
T	0 11	0.1	- 1		200 000	

1.Name & address of the building:- M/s Satyam Guest House 5134-35, Main

Bazar, Pahar Ganj, New Delhi. Residential Group A-1 Ground

+ 3 Floor.(39 guest rooms)

3. Type of case:- Renewal

4. Details of previous FSC:- No.F6/DFS/MS/GH/2013/581

dated 12/02/13

5. Fire safety directives No.-

2. Type of occupancy:-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

N/A 18/05/16

D.O. Gurmukh Singh

Mr. Bhagwan Singh (G.M.)

1987

1015/Joint C.P./Lic. (H) dated 04/05/16

S.No.	Minimum Standards on fire	Requirement	Provided at site	Old Case Remarks			
	Prevention and fire safety U/R 33	(PSS Area)	PSS PSS	MR/NMR			
1.	Access to Building	4					
	1) Road width	N/A	06 Mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrar		14/11	IN/A			
	A. Number of staircases	-8					
	1. Upper floors	01 No.	02 No.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase			11111			
	1. Upper floors	80 cms.	94 cms &126 cms.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase to terrace	N/A	N/A	N/A			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1 mtr.	1 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			
5.	Fire Extinguishers						
	1) Total numbers	10 Nos.	10 Nos.	MR			

	2) Types					
	3) ISI marking	ABC & CO2	ABC &CO2	MR		
6.	First-Aid Hose Reel	Required	Provided	MR		
0.	1)Total most Reel			1,11		
	1)Total number at each floor	01 no.	01 no.	MR		
				IVIIC		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
7.	3) Nozzle diameter	5 mm.	5 mm.	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
8.	5) Hooter's Location	N/A	N/A	N/A N/A		
	MOEFA	Required	Provided			
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System		Trovided	MR		
	1) Basement	N/A	N/A	DT/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling		IV/A	N/A		
1.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	27/		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	1011	IN/A	N/A		
	3) Hose box	N/A	N/A			
2.	Yard Hydrants	1071	IN/A	N/A		
	1) Total number of hydrants	N/A	NI/A			
	2) Hose box	N/A	N/A	N/A		
3.	Pumping Arrangement	14/21	N/A	N/A		
	1) Ground level	NI/A	*			
	a) Discharge of main	N/A	N/A	N/A		
	pump	N/A	N/A	N/A		
	b) Head of main pump	27/4				
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	) paripoutput	N/A	N/A	N/A		
	. I - P meda	N/A	N/A	N/A		
	, striditual	N/A	N/A	N/A		
	stopping			11/11		
	2) Terrace level					
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	30 Mtr.	30 Mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
	Captive Water Storage for Fire I	Fighting		IVIK		
	1) Under ground tank	N/A	N/A	NT/A		
	capacity		11/11	N/A		

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltrs.	10,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
9	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/MS/DFS/GH/2013/581 dated 12/02/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh Divisional Officer

A. OCOUNDOD