GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ M02/808

Dated : 19/01/16

FIRE SAFETY CERTIFICATE

Certified that the India International Sitare Guest House located at 2024/7, Chuna Mandi, Pahar Ganj, New Delhi comprised of Ground + 4 Upper Floors, Ground floor – reception, 1st floor 06 guest rooms +01 office, 2nd floor 06 guest rooms +01 Manager room, floor 06 guest rooms +01 store & 4th floor room found sealed total 18 guest rooms have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 10/05/16 in the presence of Mr. Saurabh Gupta that the premises is fit for occupancy of class Residential Group -A-1 for total 18 guest rooms only as above with effect from -19-1-55-7-1-4- for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 mentioned below.

Issued on — at New Delhi by.

19/05/16

(Rajesh Panwar) Dy. Chief Fire Officer Delhi Fire Service Ph: - 011-23412025

Copy to:

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. The Licensee, India International Sitare Guest House, 2024/7, Chuna Mandi, Pahar Ganj, New Delhi.

Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry'.

INSPECTION REPORT

1.Name & address of the building:-

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

India International Sitare Guest House,

2024/7, Chuna Mandi, Pahar Ganj, New Delhi.

Residential Group A-1 Ground

+ 4 Upper Floors. (18 guest rooms)

Renewal

No.F6/DFS/MS/GH/2012/719

dated 20/02/13

N/A

10/05/16

D.O. Gurmukh Singh

Mr. Saurabh Gupta

1990

Nil. Dated 29/04/16

	11	Mii. Dated	29/04/16			
S.No.	Minimum Start I G					
	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement (PSS Area)	Provided at site PSS	Remarks MR/NMF		
1.	Access to Building					
	1) Road width	N/A	06 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3) Width of internal road	N/A	NI/A	N/A		
2.	Number, Width Type & Arra	ingement of Exits	1 1/11	IN/A		
	A. Number of staircases					
	1. Upper floors	01 No.	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase			IVA		
	1. Upper floors	80 cms.	1.17 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits			14/11		
	1. Fire check door	N/A	N/A	N/A		
-	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System					
	1) Basements	30 ACPH	Exhaust fan	MR		
	2) Upper floors	12 ACPH	Natural	MR		
	Fire Extinguishers					
	1) Total numbers	08 Nos.	08 Nos.	MR		
	2) Types	ABC & CO2	ABC &CO2	MR		

	0) 101						
-	3) ISI marking	Required	Provided	Mı			
6.	First-Aid Hose Reel						
	1)Total number at each floor	01 no.	01 no.	MR			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	5 mm.	5 mm	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System	IVIIC					
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling	20 9000	11/11	IVA			
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor		14/11	IV/A			
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants N/A N/A						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
3.	Pumping Arrangement		14/11	IN/A			
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A				
	pump	11/11	11/14	N/A			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump	N/A	N/A				
	d) Jockey pump out put	N/A	N/A N/A	N/A			
	e) Jockey pump head	N/A		N/A			
	f) Stand by pump output	N/A	N/A	N/A			
	g) Stand by pump head	N/A N/A	N/A	N/A			
	h) Auto starting/Manual	N/A	N/A	N/A			
	stopping	19/71	N/A	N/A			
	2) Terrace level						
	a) Discharge of pump	225 LPM	225 I D) 6	3.00			
	b) Head of pump	30 Mtr.	225 LPM	MR			
	c) Power supply		30 Mtr.	MR			
		Required	Provided	MR			
1.	8 - 1	Required	Provided	MR			
4.	Captive Water Storage for Fire Fighting						
	1) Under ground tank capacity	N/A	N/A	N/A			
		DT/A					
	a) Draw-off connection	N/A	N/A	N/A			

	b) Fire service inlet	N/A	37/1	
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltrs.	N/A 2,500 ltrs.	N/A MR
15. 16.	Exit Signage. Provision of Lifts.	Required	Provided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
17.	e) Lift signage	N/A	N/A	N/A
18.	Stand by Power Supply	Required	Provided	MR
10.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
0.	Special Fire Protection System for Protection of special Risk, if any:			

The shortcomings communicated by this department vide letter dated 13/04/16 found rectified

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/MS/DFS/GH/2013/719 dated 20/02/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh
Divisional Officer