## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001 Fax: 23412593, Email:gargatul@hotmail.com, Tel:- 011-26189168

NO.F6/DFS/MS/2016/ 52 875

Dated: 26/5/16

## FIRE SAFETY CERTIFICATE

Certified that Delhi Tamil Sangam located at Tamil Sangam Marg, Sec-5, Ramakrishnapuram, New Delhi-110022. Comprised of two blocks - Old Block: - Basement, Ground & two upper floors and New Block: -Basement, ground floor, mezzanine floor, first floor & second floor(The basement and ground floor is common for old & new block) owned/occupied by Delhi Tamil Sangam was issued NOC vide letter no. F.6/ MS/ DFS/2001/1103 dated:11/06/2001. The premises was re- inspected by the officer concerned of this department on 10/05/16 in the presence of Mr. Murthy and found that the said premises have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Mixed (Business, Assembly & Mercantile) with effect sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Te my sagare

Copy to:-

Mr. N Kannan (General Secretary), Delhi Tamil Sangam, Tamil Sangam Marg, Sec-5, Ramakrishnapuram, New Delhi-110022

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of NBC

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

NIIS

## **INSPECTION REPORT**

- 1.Name & address of the building:- Delhi Tamil Sangam, Tamil Sangam Marg, Sec-5, Ramakrishnapuram, New Delhi-110022
- 2. Type of occupancy: Mixed Occupancy (Business, Assembly & Mercantile)
- 3. Type of case:- Renewal
- 4. Details of previous NOC:- F.6/ MS/ DFS/2001/1103 dated:11/06/2001
- 5. Fire safety directives No.- F.6/DFS/MS/83/Auditorium/213 dated 03/07/1983

F6/DFS/MS/84/786

dated 09/08/1984

- 6. Date of inspection: 10/05/2016
- 7. Name of the inspecting officer:- D.B.Mukherjee, A.D.O.(BCP)
- 8. Name & designation of officer From the building side:- Mr. Murthy
- 9. Year of construction:- 1990 & 1997
- 10. Applicant's letter no:- Nil Dated: 21/12/2015 received at HQ on 23/03/2016
- 11. Composition of building: Building is in two blocks Old Block: basement, Ground floor, first floor & second floor and New Block: basement, ground floor, mezzanine floor, first floor & second floor. The basement is common for old & new block.

Old Case S.No. Minimum Standards on fire Requirement Provided at site Remarks Prevention and fire safety U/R 33 **NBC** MR/NMR 1. Access to Building 1) Road width 09 m Provided MR 2) Gate width 5 m Provided MR 3) Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 02 Old Block is served by a single staircase WHICH IS common with new block upto first floor. New Block 03nos including common staircase. 2. Basements 02 03nos MR B. Width of staircase 1. Upper floors 1.25 m Old Block- Ground floor MR to First floor -1.37m First Floor to Second Floor- 1.25m New Block-1.40m, 1.37m 1.37m 2. Basements 1.25 m 1.40m,1.26m & 1.07m MR C. Protection of exits 1. Fire check door Required Provided MR 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace 02 02 MR E. Width of corridor N/A N/A N/A F. Door size 1.5m 1.53,1.52m,1.40m,1.40m MR Auditorium & Balcony-1.37m, 1.37m (Old Case) 1 m for others Old Case

W116

3.	Compartmentation	10110	- 1783 C	The state of
3.	1) Fire check door	Required	Provided	Mĸ
	2) Sealing of electrical shafts	Required	Provided	MR
	3) Fire rating of shaft door	Required	Provided	MR
	4) Water curtain	N/A	N/A	N/A
		N/A	N/A	N/A
4	5) Fire Dampers	IWA	14/14	12.112
4.	Smoke Management System  1) Basements	30 a/c per hour	Provided Exhaust Fans	MR
		12 a/c per hour	Auditorium has Exhaus	
s _ *	2) Upper floors	12 are per nour	and rest of the building Natural Ventilation	
5.	Fire Extinguishers			1200
	1) Total numbers		42Nos.	MR
	2) Types	ISI Marked	ABC, Co2	MR
	3) ISI marking		Yes	MR
6.	First-Aid Hose Reel			
	1) Total number of each floor	02nos	Provided	MR
	2) Length of hose reel hose	30 m	Provided	MR
	3) Nozzle diameter	5 mm	Provided	MR
7.	Automatic Fire Detection & Alarming Sys	tem		A SHIP COLUMN
	1) Type of detectors	Smoke	Provided	MR
	2) Location of main panel	Ground Floor	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Every Floor	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
10.	1) Basement	Required	Provided	MR
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	100 mm	Provided	MR
	2) Number of hydrants per floor	01	Provided	MR
	3) Hose box	01	Provided	MR
12	Yard Hydrants	101		
12.	1) Total number of hydrants	04nos	Provided	MR
	2) Hose box	04nos	Provided	MR
12	1	OTHOS	120.2000	2 2
13.	Pumping Arrangement  1) Ground level			
		2280 LPM	Provided	MR
	a) Discharge of main pump	60m	Provided	MR
	b) Head of main pump	01	Provided	MR
	c) Number of main pump	450 LPM	Provided	MR
	d) Jockey pump out put	430 LPM 40m	Provided	MR
	e) Jockey pump head	900 LPM	Provided	MR
	f) Stand by pump output		Provided	MR
	g) Stand by pump head	60 m	Provided	MR
A TOP	h) Auto starting/Manual stopping	Required	rrovided	IVIIC
	2) Terrace level	000 7 73 5	D	MR
	a) Discharge of pump	900 LPM	Provided	
	b) Head of pump	54m	Provided	MR
	c) Power supply	Required	Provided	* MR
1	d) Auto starting of pump	Required	Provided	MR

2111

-	Captive Water Storage for Fire Fightin  1) Under ground tank capacity	1,00,000 Ltrs.	1,00,000 Ltrs.	MR	
	a) Draw-off connection	Required	Provided	MR	
	b) Fire service inlet	Required	Provided	MR	
	c) Access to tank	Required	Provided	MR	
	d) Over head tank capacity	30,000 Ltrs.	30,000 Ltrs.	MR	
	Exit Signage.	Required	Provided	MR	
<b>5. 6.</b>	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
Fe L	e) Lift signage	N/A	N/A	N/A	
	Stand by Power Supply	Required	Provided	MR	
	Refuge Area				
	Total area	N/A	N/A	N/A	
	location	N/A	N/A	N/A	
9.	Fire Control Room				
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
	Special Fire Protection System for Pro	tection of special Risk, if	any: Provided	N/A	

The fire protection system provided in the building were checked and found functional at the time of inspection. In view of the compliance of the minimum standards on fire prevention and fire safety measures as required under the rules 35 of the Delhi Fire Service rules 2010, renewal of NOC is recommended.

Accordingly DFA is put up for signature please.

hap 12/5/2016 Signature of the inspecting officer

Name: - D.B. Mukherjee.

Designation: - Asstt. Div. Officer (BCP)

Dy cho (D.P. 13handwai) Dy cho.53/ Time

Time limb has and gone in the ext. Knody explain why 80 much lely by