FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE

NEW DELHI - 110001

No.

F6/DF3/M5/BNO7/2016/W2/936

Dated: 03/06/16

FIRE SAFETY CERTIFICATE

Certified that the Ecstasy Hotels Pvt. Ltd. (Banquet Hall), Located at 2/78, W.H.S. Kirti Nagar, New Delhi -110015. in a building comprised of Ground Floor (Banquet Hall) + First Floor (Restaurant), 3 Office Rooms on terrace owned/ occupied by Ecstasy Hotels Pvt. Ltd. (Banquet Hall) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officer concerned of this department on 22-04-2016 in the presence of Sh. Sandeep Kumar (Director) and found that the said building that the premises is fit for occupancy class "Assembly" Group D with effect from ________ for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on03/06/16... at New Delhi by.

Chief Fire Officer, Ph: 011 - 23846352.

Copy to:

1. Sh. Sh. Sandeep Kumar (Director), (Ecstasy Hotels Pvt. Ltd.), 2/78, W.H.S. Kirti Nagar, New Delhi -110015.

The Dy. Health Officer, North Delhi Municipal Corporation, Nigam Bhawan, D B Gupta Road, Anand Parabt, Karol Bagh, New Delhi – 110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

Name & address of the building: (Ecstasy Hotels Pvt. Ltd.), Located at 2/78, W.H.S. Kirti Nagar, New Delhi -110015.

1. Type of Occupancy : Assembly (Ground Floor = Banquet Hall + First Floor = Restaurant), 3 Office Rooms on terrace

2. Type of Case

: New

Ground & First Floor each –

3. Details of previous NOC

: Nil

(Area=477sq.mtr)·

4. Fire Safety directives Letter No.: Nil

5. Date of inspection

: 22-04-2016

6. Name of the Inspecting Officer: Mukesh Verma ADO (MN)

7. Name and designation of Officer

from the building side

: Sh. Sandeep Kumar (Director)

8. Year of Construction

: 1999

9. Applicant's letter No.

: DHO/KBZ/2016/1694 dated 21-05-2015 &

DHO/KBZ/2016/1271 dated 03-02-2016

S No	Minimum standards on fire prevention and fire safety U/R 33		BBL Requirements	Provided at site	Remarks MR/NMR			
1.	Access of	building						
	Road width		12 m	Provided	MR			
	• Ga	te width	4.5 m	On Main Road	MR			
	• Wi	dth of internal road	NA	NA	NA			
2.	Number, width, Type & Arrangements of exits							
	a. Nu	mber of staircases						
	• Up	Upper floors2		Provided	MR			
		sements	NA	NA	NA			
	b. Wi	dth of staircases		<u>'</u>				
	• Up _l	per floors	1.5m& 1m	152 cm & 105 cm	MR			
	Bas	ements	NA	NA	NA			
	c. Pro	tection of exits						
	• Fire	check door	Required	Required Provided				
	• Pre	ssurization	NA	NA	MR NA			
	d. No of continuous staircase to terrace		Required	Provided	MR			
		th Of Corridor	NA	NA	NA			
		Door Size	1X2m & 1X1m	GF=2X223cm, 2X150 cm, 108				
				cm FF=202 cm,				
				151 cm				

3	3. Compartmentation				
	 Fire check door 	NA	NA	27.4	
	 Sealing of electrical 	NR		NA	
	shafts	111	NR	NR	
	 Fire Rating of shaft 	NR	NR	277	
	door		IVIX	NR	
	• Water Curtain	NA	NA	NA	
4.	• Fire Dampers	NA	NA	NA NA	
4.	- managements system			IVA	
	• Basements	NA	NA	· NA	
5.	Upper floors Fire Fytingsisl	Required	Provided	MR	
J.					
	Total numbersTypes	6 nos.	Provided	MR	
	1) PC3	ABC & CO ₂	Provided	MR	
6.	IS marking First – Aid Hose Reels	ISI marked	Provided	MR	
	floor	2	Provided	MR	
	 Length of hose reel hose 	30 m	Provided	MR	
	 Nozzle diameter 	5 mm	Provided	MR	
7.	Automatic fire detection and ala	arming system	Trovided	IVIK	
	• Type of detectors	NA	Provided	NA	
	 Location of Main Panel 	NA	GF	NA	
	 Location of Repeater 	NA	NA	NA	
	Panel	27.			
	Alternate source of power	NA	Provided	NA	
	Hooters' Location	NA	GF	NA	
8.	MOEFA	Required	Provided		
9.	Public Address System	Required	Provided	MR MR	
10.	Automatic Sprinkler System		TTOVICC	IVIK	
	 Basements 	NA	NA	NA	
	• Upper Floor	NR	NR	NR	
	 Sprinkler above false 	NR	NR	NR	
11.	ceiling Internal Hydrod				
1.	Internal Hydrants Size of riser/dayyr	100			
	• Size of riser/down-comer	100 mm	Provided	MR	
	 Number of hydrants 	2	P		
	per floor	4	Provided	MR	
		2	Duo: 1 1	1.00	
2.	Yard Hydrants		Provided	MR	
		NR	NR	NID	
	hydrants	= 0.4.3.	INIX	NR	
	Hose Box	NR	NR	NR	
3.	Pumping Arrangements		4111	INIC	
	Ground Level				
	• Discharge of main	VA	NA	NA	
			INA		
	pump	NA	IVA	INA	

		Head of main pump)	NA					
Number of main pur			mn	nne NA		NA		NA	
Jockey pump out pu			it it			NA		NA	
Jockey pump head		- 12.2			NA		NA		
	Standby Pump out pu Standby Pump Head		nt	NA		NA NA		NA	
			- 12 2					NA	
	Auto Staring/Manual		1	NA ·		NA		NA	
	stopping		1					1171	
	Pump House Access			NA		NA		NA	
		• Terrace level						11/21	
	Discharge of pump			450 lpm		Provided		· MR	
	Head of the pump			40 m		Provided			
	Power supply			Required		Provided		MR	
	Auto starting of pump					Provided		MR	
	14. Captive water Storage for fire) ~			TTOVICEC		MR	
		Under grown de d	e fig						
		 Under ground tank capacity 	NA		NA		NA		
		> Draw of connection							
		Fire service inlet		NA		NA	-	NA	
		Access to tank		NA		NA		NA NA	
				NA		NA			
		• Overhead Tank		15, 000 litres		Provided		VA	
1	capacity Exit Signage					Trovided		MR	
16		Exit Signage		Required		Provided		MD	
1	,	Provision of Lifts				Trovided		MR	
	 Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch 		NA NA		N	NA NA		NA NA	
					N				
					1				
			1	NA		NA		NA	
			N	NA		NA		NA	
			1						
17		Lift Signage	N	ĪΑ	N.	A			
17.	-	tandby power supply	-	equired			NA		
18.	R	lefuge Area		equited	Pr	ovided	M	R	
		> Total area	N	A) T			G.	
1.0		Location	N.		NA		NA	1	
19.	Fi	Fire control room		A NA		A NA			
		Detector system panel	N	٨					
		Flow Switch Panel	N		NA		NA		-
		PA System Panel	NA NA		NA N		NA	NA	
		Battery backup					NA		-
		Building Floor Plans	NA		NA				-
0.). Special Fire Protect:		NA			NA N			
			NA			NA N			
	spe	ecial Risks, if any;							
-		The fire protection							

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Mukesh Vecma ADoven)