FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

FEIDFILMS/Hosportel 2016/ww/ 937

Dated: 03/06/16

FIRE SAFETY CERTIFICATE

Certified that the MGS Super Speciality Hospital, located at 35/37, Rohtak Road, West Punjabi Bagh, New Delhi - 110026 comprised of Basement + Ground + 2 Upper Floors was issued FSC vide Letter no. F6/DFS/MS/2011/1993 dated 16-08-2011. The premises was re inspected by the officers concerned of this department on 20-05-2016 in the presence of Mr Naresh Babbar (Medical Director) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Institutional" Group C Sub Division C - 1 with effect from03/06/16 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Vipin Kental) Chief Fire Officer, Ph: 011 - 23846352.

Copy to:-

No:

1. The Medical Director, MGS Super Speciality Hospital, 35/37, Rohtak Road, West Punjabi Bagh, New Delhi – 110026.

Following fire safety directives must be adhered to:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and

responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning

5. The certificate may not be treated in any case for the regularization of the unauthorized

construction, if any.

6. The basement shall be used as per building bye laws.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

NSPECTION REPORT

1. Name & address of the building: MGS Super Speciality Hospital, 35/37, Rohtak Road, West Punjabi Bagh, New Delhi – 110026.

2. Type of Occupancy

: Institutional (Hospital)

3. Type of Case

: Renewal (Basement + Ground + 2 Upper

Floors)

4. Details of previous NOC

: Letter no. F6/DFS/MS/2011/1993 dated 16-

08-2011

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/93/Hospital/2006 dated 09-

12-1993

6. Date of inspection

: 20-05-2016

7. Name of the Inspecting Officer: DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Dr. Naresh Babbar (Medical Director)

9. Year of Construction

: 1991

10. Applicant's letter No.

: Nil dated 04-04-2016

S		NBC	Provided at site	Remarks				
No	prevention and fire safety U/R33 J	Requirements		MR/NMR				
1.	Access of building			4 8				
	Road width	12 m	Provided	MR				
	• Gate width	5 m	Provided	MR				
	• Width of internal road	5 m	Provided except at one corner	MR(being old case)				
2.	Number, width, Type & Arranger	nents of exits	Control of the contro					
	a. Number of staircases			2 , 2				
	Upper floors	3	4Provided	MR				
	• Basements	3	Provided	MR				
	b. Width of staircases							
	• Upper floors	2 m	Provided2x2mtr. 2x1.5mtr.each	MR(being old case)				
	Basements	2 m	Provided	MR				
	c. Protection of exits							
	• Fire check door	Required	Found Provided	MR				
	 Pressurization 	Required	Found Provided	MR				
	d. No of continuous staircase		Provided	MR				
,	to terrace e. Width Of Corridor	Old Case	1.5 mtr	MR(being old case)				
	f. Door Size	Old Case	1.25 mtr	MR(being old case)				
3.	Compartmentation	-						
	Fire check door	Required	Found Provided	MR				
	 Sealing of electrical shafts 		Provided	MR				

	F: D : C 1 C 1		D	. 1	T	• 1 1	1	· (D	
	• Fire Rating of shaft do	or	Requ			rovided		MR	
	Water Curtain		Requ			rovided		MR	
	Fire Dampers		Requ	iired	P	rovided	1	MR	
4.	Smoke managements System				2				
	 Basements 		Requ			ound Provide		MR	
	Upper floors		Requ	iired	P	rovided	1	MR	
5.	Fire Extinguishers								
	Total numbers		15 no		-	rovided		MR	
	• Types		ABC			rovided	1	MR	
	IS marking		1	O_2 , CO_2					
			ISI n	narked	P	rovided	1	MR	
6.	First – Aid Hose Reels		0.0						
	• Total numbers on each	1	n each	P	rovided	[MR		
	floor		floor		1.00				
	• Length of hose reel ho	se	30 m		_	rovided		MR	
	Nozzle diameter		5 mn		P	rovided	1	MR	
7.	Automatic fire detection and a	alarm	ing syst	em					
1	T. C.I.			e & He		D :11	- ×	1 (1)	
	• Type of detectors				at	Provided		MR	
	Location of Main Pane	31	Requi		м	Provided		MR	
	• Location of Repeater		Requi	rea		Provided		MR	
	Panel		Dogui	mo d		Provided		MD	
	• Alternate source of po	wer	Requi				2 3	MR	
	Hooters' Location		Requi			Provided		MR	
8.	MOEFA		Requi		Provided			MR	
9.	Public Address System		Required Provided					MR	
10.	Automatic Sprinkler System							-	
	• Basements		equired			vided	MF		
	Upper Floor		Required		Provided			MR	
	• Sprinkler above false ceiling	Re	equired		Pro	vided	MF		
11.	Internal Hydrants:	1	- N - N						
11.	C' C · /1	mer		100 m	ım	Provided		MR	
11.	Size of riser/down- con		×			Provided			
11.			or	02		Provided		MR	
11.	27 1 01 1		or	02		Provided Provided		MR MR	
	Number of hydrants per		or						
	Number of hydrants peHose Box	er flo	or 04		Pro		MR	MR	
	Number of hydrants peHose BoxYard Hydrants	er flo				Provided	MR MR	MR	
12.	 Number of hydrants per Hose Box Yard Hydrants Total number of hydrants 	er flo	04			Provided vided		MR	
12.	 Number of hydrants per Hose Box Yard Hydrants Total number of hydrants Hose Box 	er flo	04			Provided vided		MR	
12.	 Number of hydrants per Hose Box Yard Hydrants Total number of hydra Hose Box Pumping Arrangements: Ground Level 	er flo	04	02	Pro	Provided vided	MR	MR	
12.	 Number of hydrants per least section of hydrants Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements: Ground Level 	er floo	04 04	02	Pro	Provided vided vided	MR	MR	
12.	 Number of hydrants per Hose Box Yard Hydrants Total number of hydra Hose Box Pumping Arrangements: Ground Level Discharge of main pump Head of main pump Number of main pump 	er floornts	04 04	02 PM	Pro	Provided vided vided vided & func	MR	MR R MR	
12.	 Number of hydrants per least section in the least section in th	er floorings and series are series and series are series and series and series and series are series and series and series and series are series are series and series are series and series are series are series are serie	04 04 1620 LP	02 M	Prov Prov Prov	vided vided vided & functions	MR	MR R MR MR	
12.	 Number of hydrants per least section in the least section in th	er floornts on 1 4 os (04 04 1620 LP 45mtrs	02 M	Prov Prov Prov Prov	vided vided & function vided vided vided vided	MR	MR MR MR MR	
12.	 Number of hydrants per Hose Box Yard Hydrants Total number of hydra Hose Box Pumping Arrangements: Ground Level Discharge of main pump Head of main pump Number of main pump Jockey pump out put Jockey pump head Standby Pump out put 	er flooring in the second seco	04 04 1620 LP 45mtrs 01 180 LPN	02 M	Prov Prov Prov Prov	vided vided & function vided wided vided vided vided vided	MR	MR MR MR MR MR MR	
12.	 Number of hydrants per least section in the least section in th	unts	04 04 1620 LP 45mtrs 01 180 LPN 45mtr	02 M	Provent Proven	vided vided wided vided vided vided vided vided vided	MR	MR MR MR MR MR MR MR	
12.	 Number of hydrants per Hose Box Yard Hydrants Total number of hydra Hose Box Pumping Arrangements: Ground Level Discharge of main pump Head of main pump Number of main pump Jockey pump out put Jockey pump head Standby Pump out put 	onts 1 4 1 4 1 4 1 4	04 04 1620 LP 45mtrs 01 180 LPN 45mtr 1620lpm	02 PM	Prov Prov Prov Prov Prov Prov	vided & function vided wided vided v	MR	MR MR MR MR MR MR MR MR MR	

w.	• Terrace level	NIA	NIA	NA
1	Discharge of pump	NA	NA	NA NA
	> Head of the pump	NA	NA	
	Power supply	NA	NA	NA
	Auto starting of pump	NA	NA	NA
14.	Captive water Storage for fire fi	ghting:) (D)
	 Under ground tank capacity 	1,00,000 litre	Provided	MR
	Draw off connection	Required	Provided	MR
	> Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
	 Overhead Tank 	10,000 litres	Provided	MR
	capacity			
15	Exit Signage	Required	Provided	MR
16.	Provision of Lifts			
	Pressurization of Lift	Required	Provided	MR
	Shaft			
	Pressurization of lift	Required	Provided	MR
	lobby			
	Communication in lift	Required	Provided	MR
	-C <mark>ar</mark>			
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
	Dit Signage	*	20 M2 DC 21 MAN 30 DC	
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area			
	> Total area	NA	NA	NA
	> Location	NA	NA	NA
19.	Fire control room			
	Detector system panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
	PA System Panel	NA	NA	NA
47	Battery backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
20.	Special Fire Protection	NA	NA	NA
	Systems for Protection of			
	special Risks, if any;			
-	A STATE OF THE STA			- tt alread and

The fire protection systems provided in the building were test checked and

found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. Letter no. F6/DFS/MS/2011/1993 dated 16-08-2011 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name MUKESN VERMA

Name

Designation ADO MM

Designation

vo West) de 21/5

1 1 steet