GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001

E-mail: gargatul@hotmail.com, Tel:- 011-26189168

NO. F6/DFS/MS/Indl./2016/SZ/ 972

DATED: 08/06/16

FIRE SAFETY CERTIFICATE

Issued on & less Delhi by

(Atul Garg) Chief Fire Officer

Сору То:-

 The Authorized Signatory, M/s SMS Exports at Plot No. D-28,Okhla Phase-I, New Delhi-110020.

Conditions for the validity of fire safety certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- 3. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye laws.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

1							
	Annual Control of the	INSP	ECTION REPORT	A THE RESERVE OF RESE	mun takeri in a		
1	Name & address		I/S SMS Export at Plot No relhi	. D-28, Okhla Industrial Area,	Phase-I, New		
	Building Compris	sed of B	+G+M+1 upper floor				
2	Type of Occupar	ncy	Industrial "G"				
3	Type of case		Renewal				
	Details of previo	us NOC	F6/DFS/MS/Indl./2013/342 Dated 21.05.2013				
4	Fire safety direc		Nil				
5		ives lotter ive	2.06.2016				
6	Date of inspection		DCFO D.P. Bhardwaj & ADO M.K. Chatopadhyay				
7	Name of the ins		1				
8			Mr. Ajay Sahni(Partner)				
	from the building						
9	Year of construc	otion	2005 Nil dated 23.05.2016				
	Applicant's lette	r No.	VIII dated 20.00.2010	II dated 23.05.2010			
10					Old Case		
				Devided at aita	Remarks		
S. NO.	Minimum Stan		BBL-1983/NBC Requirement	Provided at site	MR / NMR		
	prevention and	d fire safety U/R 33					
1	Access to buil			Dunidad	MR		
	1) Road width		6 Mtr	Provided N/A	N/A		
	2) Gate width		N/A	N/A	N/A		
	3) Width of inte		N/A	IN//X			
2		Type & arrangement of	exits				
	a. Number of		Two	Provided	MR		
in in	1. Upper floors		Two	Provided	MR		
	2. basements	-ive and					
	b. Width of st		1.25 mtrs	1.7 & 1.00 Mtrs Provided	MR		
	1. Upper floors		1.25 mtrs	1.90 & 1.3 Mtrs Provided	MR		
	2. basements c. Protection	of avite					
	1. Fire check		Required	Provided	MR		
	2 Pressurizati	on	N/A	N/A	N/A MR		
	d. No. of c	continuous staircase to	Required	One Provided	IVIH		
	e. Width of co	rridor	N/A	N/A	N/A		
	f. Door size		N/A	N/A	N/A		
3	Compartmen	tation.			NI/A		
	1. Fire check		N/A	N/A	N/A MR		
		electrical shafts	Required	Provided	N/A		
	3. Fire Rating	of shaft door	N/A	N/A N/A	N/A		
	4. Water curt	a <mark>in</mark>	N/A	N/A	N/A		
	5. Fire dampe		N/A	[1V//*\			
4		agement system.	30 a/c per hour	Exhust Fan Provided	MR		
	basement	7.00	12 a/c per hour	Exhust Fan Provided	MR		
	upper floors			EXTIUST FAIT FTOVIDED	IVII C		
5	Fire Extingu			20 Nos	MR		
	total number	S		Co2, Water Co2, ABC	MR		
	Types			Vec	MB		

		T						
6	First-Aid Hose Reels.							
	total numbers on each floor	One	One Provided	MR				
	Length of Hose reel hose	30 m	30 Mtr Provided	MR				
	Nozzle Diameter	5 mm	Provided	MR				
7	Automatic fire detection and alarming system							
	Type of Detectors	Required	Provided (Smoke/Heat)	MR				
	location of Main Panel	Required	Provided (Ground)	MR				
	location of Repeater panel	N/A	N/A	N/A				
	Alternate source of power	Required	Battary Backup	MR				
	hooter's location	Required	Stairs Provided	MR				
. 8	MOEFA	Required	Provided	MR				
9	Public Address System.	N/A	Provided	MR				
10	Automatic Sprinkler System.							
	basement	Required	Provided	MR				
	upper floors	Required	Provided	MR				
	sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants							
	Size of riser/down-corner	150 mm	Provided	MR				
	Number of Hydrants per floor	One	One Provided	MR				
	hose Box	One	One Porvided	MR				
12	Yard Hydrants.							
	total number of hydrants	Required	Provided	MR				
	hose box	Required	Provided	MR				
13	Pumping arrangements							
	1. Ground level							
	a. Discharge of main Pump	2280 LPM	2280 LPM Provided	MR				
	b.Head of main pump	60 Mtr	60 Mtr Provided	MR				
	c.Number of main pumps	One		MR				
	d.jockey pump out put	180 LPM	180 LPM Provided	MR				
	e.jockey pump head	60 Mtr	60 Mtr Provided	MR				
	f. Standby Pump output	2280 LPM	2280 LPM Provided	MR				
	g.Stanby Pump head	60 Mtr	60 Mtr Provided	MR				
	h.Auto Starting/Manual stopping	Required	Provided (Both)	MR				
14	pump house access	Required	Provided	MR				
	2.Terrace level	. 10 4						
	a. Discharge of pump	900 LPM	900 LPM Provided	MR				
	b. head of the pump	35 mtr	35 Mtr Provided	MR				
	c. Power supply	Required	Provided	MR				
	d. Auto starting of pump	Required	Provided	MR				
	Captive water storage for fire fighting							
14	Underground tank capacity	50,000 ltr	50,000 ltr Provided	MR				
	a. Draw-off connection	Required	Provided	MR				
	b. fire service inlet	Required	Provided	MR				
	c.Access to tank	Required	Provided	MR				
		15,000 ltr	15,000 ltr Provided	MR				
15	Over head tank Capacity	Required	Provided Provided	MR				
15	Exit Signage.	nequired	Ji Tovided	IVIII				
16	Provision of lifts.	NI/A	N/A	N/A				
	a. Pressurization of lift shaft	N/A		N/A				
	b. pressurization of lift lobby	N/A	N/A	N/A N/A				
	c. communication in lift car	N/A	N/A					
	d. Fireman's grounding switch	N/A	N/A	N/A				
	e. Lift signage	N/A	N/A	N/A				

Y Y	Standby power supply	Required	Provided	MR	
3	Refuge Area.	Not Required			
	total area				
	location				
19	Fire control room				
	a. Detector system Panel	N/A	N/A	N/A	
×	b. Flow switch Panel	N/A	N/A	N/A	
	c. PA system Panel	N/A	N/A	N/A	
	d. Batter backup	N/A	N/A	N/A	
	e. Building floor plans	N/A	N/A	N/A	
20	Special Fire Protection systems for protection of special risks, if any:	Required	2 Co2 Fire Extinguishers Provided	MR	

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules of NOC issued vide letter no.F6/DFS/MS/Indl./2013/342 Dated 21.05.2013 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

Signature of the Inspecting Officer

Name D.P. Bhardwaj **Designation: DCFO**

Signature of the Inspecting Officer

Name Designation M.K. Chatopadhyay

ADO (BCP)

CFO (Aful Gazy) At 11 L