GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ MD2/1037

Dated: 15/06/16

FIRE SAFETY CERTIFICATE

Certified that M/s Delhi 55 Guest House located at 8703-8706,Desh Bandhu Gupta Road,Pahar Ganj,New Delhi-110055 comprised of Basement,Ground ,Mezzanine+ 3 Upper Floors, basement – storage,Ground floor – reception +office + lounge,Mezzanine – 05 guest rooms & 1st to 3rd floor 06 guest rooms at each floor total 23 guest rooms was granted FSC by this department vide letter No. F6/DFS/MS/GH/2013/319 dated 16/05/13. the premises was re-inspected by the officer concerned of this department on 06/06/2016 in the presence of Mr. Arun Kumar Vij (Proprietor) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Residential Group–A-1 for total 23 guest rooms only as above with effect from 1.5/16.6.... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service Ph- 011-23412225

Copy to:

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

The Licensee,
 M/s Delhi 55 Guest House,
 8703-8706,Desh Bandhu Gur

8703-8706, Desh Bandhu Gupta Road, Pahar Ganj, New Delhi-110055.

Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT	

1. Name & address of the building:- M/s Delhi 55 Guest House, 8703-8706, D.B.G.

Road, Pahar Ganj, New Delhi-110055.

2. Type of occupancy:- Residential Group A-1 Basement, Ground Mezz.+ 3 Upper Floors. (23 guest rooms)

Renewal

3. Type of case:- Renewa

4. Details of previous FSC:- No. F6/DFS/MS/GH/2013/319 dated

16/05/2013.

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

N/A 06/06/16

D.O. Gurmukh Singh

Mr. Arun Kumar Vij (Proprietor)

2011

1182/Jont.C.P./Lic. Dated 24/05/16

S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks	
J.110.	Prevention and fire safety	(Existing) F.S.	PSS	MR/NMR	
	U/R 33	arrangements.			
1.	Access to Building	0			
	1) Road width	N/A	18 mtr.	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arran	gement of Exits			
	A. Number of staircases				
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	02 Nos.	02 Nos.	MR	
	B. Width of staircase				
	1. Upper floors	1.50 mtr.	1.53 mtr.	MR	
	2. Basements	1.50 mtr.	1.53 mtr. &	MR	
			1.13 mtr.		
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace				
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation			^	
	1) Fire check door	N/A	N/A	N/A·	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	Exhaust fan	MR	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	15 Nos.	15 Nos.	MR	

	0.5			
	2) Types	ABC & CO2	ABC &CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			2
	1)Total number at each	01 no.	01 no.	MR
	floor			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	5 mm.	5 mm.	MR
7.	Automatic Fire Detection & A	larming System		
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System /	Required	Provided	MR
	Intercom		Tiovided	IVIIC
10.	Automatic Sprinkler System	9		
	1) Basement	Required	Provided	MR
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	2017 2 2	14/14	IN/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	
	floor	14/21	IN/A	N/A .
	3) Hose box	N/A	N/A	NI/A
12.	Yard Hydrants	IV/A	IN/A	N/A
12.	1) Total number of hydrants	N/A	NT/A	27/4
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	IN/A	N/A	N/A
13.		27/4	27/1	
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	II TILA
	200		IN/A	N/A
	pump	27/4	2	
	b) Head of main pump	N/A	N/A	N/A
	b) Head of main pumpc) Number of main pump	N/A	N/A N/A	
	b) Head of main pumpc) Number of main pumpd) Jockey pump out put	N/A N/A	N/A	N/A
	b) Head of main pumpc) Number of main pumpd) Jockey pump out pute) Jockey pump head	N/A N/A N/A	N/A N/A	N/A N/A
	 b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output 	N/A N/A N/A N/A	N/A N/A N/A	N/A N/A N/A
	 b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head 	N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
	 b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output 	N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A N/A
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A 900 LPM	N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A N/A N/A N/A N/A N/A N/A 40 Mtr.	N/A N/A N/A N/A N/A N/A N/A N/A N/A 40 M/A	N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A MR
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A N/A N/A N/A N/A N/A N/A A N/A P00 LPM 40 Mtr. Required	N/A	N/A
14.	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A N/A N/A N/A N/A N/A N/A P00 LPM 40 Mtr. Required Required	N/A N/A N/A N/A N/A N/A N/A N/A N/A 40 M/A	N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A MR

- N/8

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	15,000 ltrs.	15,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	The same		
	a) Pressurization of lift shaft	N/A .	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	for Protection of s	pecial Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2013/319 dated 16/05/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh Divisional Officer

Dycho(NDZ)