GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/EH/2016/ NO2 1064

Dated: 21 06/16

FIRE SAFETY CERTIFICATE

Certified that M/s Pind Balluchi Restaurant (A Unit of J.S. Hospitality Services Private Limited) located at 13 Regal Building, Connaught Circus, New Delhi comprised of Ground, Mezzanne + 2 Upper Floor, restaurant at ground & mezzanine floor only was granted FSC by this department vide letter No.F6/DFS/MS/EH/2013/291 dated 13/05/13 The premises was re-inspected by the officer concerned of this department on 13/06/16 in the presence of Mr. Shaad and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Assembly Building Group D (Restaurant) with effect from -2-1-6-6-1-6-- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, mentioned below.

Issued -- 21/06/16--at New Delhi by.

(Sunil Chowdhary) Dy. Chief Fire Officer Delhi Fire Service

Copy to:- (1) Medical Officer of Health. New Delhi Municipal Council, Palika Kendra, New Delhi.

(2) M/s Pind Balluchi Restaurant (A Unit of J.S. Hospitality Services Private Limited), 13 Regal Building, Connaught Circus, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-M/22-

INSPECTION REPORT

1. Name & address of the building:- M/s Pind Balluchi Restaurant (A Unit of J.S.

Hospitality Services Pvt. Ltd.), 13, Regal Building, Connaught Circus, New Delhi.

2. Type of occupancy:- Group – D Assembly Building (Restaurant at ground & mezz. floor)

3. Type of case:- Renewal

4. Details of previous NOC:- No. F6/DFS/MS/2013/EH/291 dated

13/05/13.

5. Fire safety directives No.- N/A

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

13/06/16

D.O. Gurmukh Singh

Mr. Shaad

Old.

Nil. dated 01/06/16

	110.	Mil. dated	01/00/10	011.6	
S.No.	Minimum Standards on fire	D :		Old Case	
S.INU.	Prevention and fire safety U/R 33	Requirement/ Existing fire safety	Provided at site	Remarks MR/NMR	
		arrangements			
1.	Access to Building		9		
2	1) Road width	6 mtr.	12 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arı	angement of E	xits	14/11	
	A. Number of staircases	8			
	1. Upper floors	02 no.	02 no.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase			11/21	
	1. Upper floors	80 cms. &	80 cms. &	MR	
	9	116 cms.	116 cms.	IVIIC	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits			11/11	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1.00 mtr. & 1.10 mtr.	1.00 mtr. & 1.10 mtr.	MR	
	Compartmentation				
<u> </u>	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
•	Smoke Management System				
	1) Basements	30 a/c per hour	N/A	N/A	
	2) Upper floors	12 a/c per hour	Venting provided in	MR	

	-N/2)						
			kitchen.				
5.	Fire Extinguishers						
	1) Total numbers	06 Nos.	06 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO	2 MR			
	3) ISI marking	ISI	Yes	MR			
6.	First-Aid Hose Reel						
	1) Total number of eachfloor	01 (ground fl.)	01 (ground	fl.) MR			
	2) Length of hose reel hose	30 m	30 m	MR			
	3) Nozzle diameter	5 mm	5 mm	MR			
7.	System System						
	1) Type of detectors	N/A	N/A	N/A			
Wales -	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	N/A	N/A	N/A			
10.	Automatic Sprinkler System		1112	1471			
10 E	1) Basement	N/A	N/A	N/A			
	2) Upper floors	Required	Provided	MR			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling		11/21	IWA			
11.	Internal Hydrants						
100000000000000000000000000000000000000	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A N/A			
	floor	14/21	IV/A	IN/A			
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants	14/11	IN/A	IN/A			
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A				
13.	Pumping Arrangement	IN/A	IN/A	N/A			
15.	1) Ground level	N/A	NT/A	27/4			
	,		N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	b) Head of main pump	NT/A	>T/A	27/4			
		N/A	N/A	N/A			
	and the second s	N/A	N/A	N/A			
	d) Joskov nyma ovt myt	NI/A	DI/A	37/1			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump	N/A	N/A	N/A			
	output	DT/A	DT/A	27/1			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual stopping	N/A	N/A	N/A			
	2) Terrace level	•	LA LA				
	a) Discharge of pump	900 LPM & 180 LPM	900 LPM & LPM	180 MR			
	b) Head of pump	40 mtr.	40 mtr.	MR			
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump	Required	Provided	MR			
14.	Captive Water Storage for F	ire Fighting					
	Storage for F	ne righting					

	1) Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank	5,000 ltrs.	5,000 ltrs.	MR		
15	capacity	D. I. I				
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
15 25	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
2	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
a =	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A .		
20.	Special Fire Protection Syste Risk, if any:	m for Protecti	on of special	N/A		

Shortcomings issued vide our letter dated 04/05/16 found rectified. The fire protection system provided in the restaurant were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/EH/2013/NDZ/291 dated 13/05/13, renewal under rule35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh Divisional Officer

Dy C60 (382) My