# GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ 1096

Dated : 30/06/16

## FIRE SAFETY CERTIFICATE

Certified that the Kamil Guest House located at 39/44, Dargah Sheikh Kalimullah, Opp. Red Fort, Jama Masjid, Delhi comprised of Ground + 1 Upper Floors, Ground floor – commercial use, 1<sup>st</sup> floor – reception + 07 guest rooms total 07 guest rooms was granted FSC by this department vide letter No. F6/DFS/MS/GH/2013/24 dated 05/03/13. The premises was re-inspected by the officer concerned of this department on 17/06/2016 in the presence of Mr. Kamil and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Residential Group -A-1' for total 07 guest rooms only as above with effect from -3 a fire fire for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on ...... 30106/16...... at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service
Ph-011-23412225

### Copy to:

- 1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi
- 2. The Licensee, Kamil Guest House, 39/44,Dargah Sheikh Kalimullah, Opp. Red Fort,Jama Masjid,Delhi.

### Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

79/6

# 1.Name & address of the building:- Kamil Guest House,39/44,Dargah Sheikh Kalimullah ,Opp. Red Fort,Jama Masjid, Delhi. 2. Type of occupancy:- Residential Group A-1 Ground

+ 1 Upper Floors.(07 guest rooms)
Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2013/24 dated 05/03/2013.

5. Fire safety directives No.6. Date of inspection:17/06/16

7. Name of the inspecting officer:- A.D.O. Mehmood

8. Name & designation of officer
From the building side:9. Year of construction:1999

10. Applicant's letter No:- Nil. Dated 30/05/16

~			, v		Old Case	
S.	No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site PSS	Remarks MR/NMR	
1.		Access to Building		2		
		1) Road width	N/A	12 mtr.	N/A	
		2) Gate width	N/A	N/A	N/A	
		3)Width of internal road	N/A	N/A	N/A	
2.		Number, Width Type & Arrar	ngement of Exits	A		
		A. Number of staircases				
		1. Upper floors	01 No.	01 No.	MR	
		2. Basements	N/A	N/A	N/A	
		B. Width of staircase				
		1. Upper floors	80 cms.	90 cms.	MR	
		2. Basements	N/A	N/A	N/A	
		C. Protection of exits				
		1. Fire check door	N/A	N/A	N/A	
		2. Pressurization	N/A	N/A	N/A	
		D. No. of continuous staircase to terrace	N/A	N/A	N/A	
		E. Width of corridor	N/A	N/A	N/A	
		F. Door size	1 mtr.	1 mtr.	MR	
3.		Compartmentation				
		1) Fire check door	N/A	N/A	N/A	
		2) Sealing of electrical shafts	N/A	N/A	N/A	
		3) Fire rating of shaft door	N/A	N/A	N/A	
		4) Water curtain	N/A	N/A	N/A	
		5) Fire Dampers	N/A	N/A	N/A	
4.		Smoke Management System				
		1) Basements	30 ACPH	N/A	N/A	
		2) Upper floors	12 ACPH	Natural	MR	

-rela -

5.	Fire Extinguishers				- 1×	
	1) Total numbers			03 Nos.	N	1R
	2) Types		& CO2	ABC &CO2		1R
	3) ISI marking	Required		Provided		1R
6.	First-Aid Hose Reel					
	1)Total number at each floor	01 no.		01 no.	N	1R
	2) Length of hose reel hose	30 mtr		30 mtr.	N	1R
"	3) Nozzle diameter	5 mm.		5 mm.		1R
7.	Automatic Fire Detection & A					
	1) Type of detectors	detectors N/A		N/A	N	/.A
	2) Location of main panel	N/A		N/A		/A
	3) Location of repeater panel	N/A	78	N/A		/A
	4) Alternate source of power	N/A		N/A		/A
e	5) Hooter's Location	N/A		N/A		/A
8.	MOEFA	N/A		N/A		/A
9.	Public Address System	N/A	In .	N/A		/A
10.	Automatic Sprinkler System					
	1) Basement	N/A		N/A	N	/A
	2) Upper floors	N/A		N/A		/A
	3) Sprinkler above false ceiling	N/A		N/A		/A
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A		N/A	N	/A
	2) Number of hydrants per floor	N/A	4	N/A	-	/A
	3) Hose box	N/A		N/A		/A
12.	Yard Hydrants					
	1) Total number of hydrants	N/A		N/A	N	/A
	2) Hose box	N/A		N/A		/A
9 1,4		8			111	11
13.	Pumping Arrangement	2 6		4.		
	1) Ground level		V/A	N/A	N/A	
	a) Discharge of main pump		V/A	N/A	N/A	
	b) Head of main pump		V/A	N/A	N/A	
	c) Number of main pump		V/A	N/A	N/A	
	d) Jockey pump out put		V/A	N/A	N/A	
	e) Jockey pump head		V/A	N/A	N/A	

13.	Pumping Arrangement		3:	T	
	1) Ground level	N/A	N/A	N/A	
я	a) Discharge of main pump	N/A	N/A	N/A	10
	b) Head of main pump	N/A	N/A	N/A	14
# 3 X	c) Number of main pump	N/A	N/A	N/A	1 d 1
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	ži ži
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	2
	stopping	8			
100	2) Terrace level				
	a) Discharge of pump	225 LPM	225 LPM	MR	
tre I	b) Head of pump	30 Mtr.	30 Mtr.	MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of pump	Required	Provided	MR	
14.	Captive Water Storage for Fire Figh	ting			
				11	

3/4

	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	3,000 ltrs.	3,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	p p		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Pany:	rotection of s	pecial Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2013/24 dated 05/03/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Assistant Divisional Officer

DYCFO (NDZ) (OS)LEGNE)

C.F.P. MSCELL Light

Tople

1 there only up for Lightine Chair