GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ ND2/1174

Dated: 19-107-116

FIRE SAFETY CERTIFICATE

Certified that the Cabana Guest House located at 2313, Laxmi Narayan Street, Chuna Mandi, Pahar Ganj, New Delhi comprised of Basement + Stilt +Ground + 03 Upper floors, Basement (storage), Stilt (parking), Ground floor (Reception + 03 guest room), 1st floor to 2nd floor (05 guest rooms at each floor) and 3rd floor (04 guest rooms), total 17 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/NDZ/1132 dated 29/10/13. The premises was re-inspected by the officer concerned of this department on 02/07/16 in the presence of Sh. Dharmender (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 17 guest rooms only with effect from --+-9-1-6--- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 19-107-16-at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. The Manager, Cabana Guest House located at 2313, Laxmi Narayan Street, Chauna Mandi, Pahar Ganj, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

			ECTION REPOR				
	1.	Name & address of the building	·	est House located a			
			Laxmi Nara	yan Street, Chauna	Mandi,		
-			Pahar Ganj,	New Delhi			
	2.	Type of occupancy:-	Residential,	Sub Division-A-1			
and and a		Y		+03 Upper floors			
PO COMPUTATION			(total 17 Guest	t rooms)			
1000		Type of case:-	Renewal				
- Carrier	4.	Details of previous FSC:-	No. F6/DFS/MS/GH/2013/NDZ/1132 dated				
and a second	29/10/13.						
	5.	Fire safety directives No	N/A				
-	6. Date of inspection:- 02/07/16						
	7.	7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)					
ı	8.	Name & designation of officer					
F		ne building side:-	Sh. Dharme	ender (Manager)			
I	9. Year of construction:- 2008						
1	10.	Applicant's letter No:-	1351/Joint C.p/Lic.(H) dated 10/06/2016.				
Account of the last					Old Case		
S	.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
-		Prevention and fire safety	Existing fire		MR/NMR		
and the same		U/R 33	safety				
+			arrangements				
1	•	Access to Building	77/		1.00		
		1) Road width	N/A	06 mtr.	MR		
l		2) Gate width	N/A	N/A	N/A		
		3) Width of internal road	N/A	N/A	N/A		
2	•	Number, Width Type & Arr	angement of Ex	its			
I		A. Number of staircases	284				
		1. Upper floors	01 Nos.	01 Nos.	MR		
eg vojavice		2. Basements	01 Nos.	01 Nos.	MR		
		B. Width of staircase					
O-months and		1. Upper floors	0.80 mtr. Old	1.45 to 1.50 mtr.	MR		
l		1. Oppor moors	Case				
		2. Basements	1.00 mtr. Old	1.45 to 1.50 mtr.	N/A		
-		G.P.	Case				
THOUSAND SER		C. Protection of exits	27/4	27/4	27/4		
ALC SHE AND		1. Fire check door	N/A	N/A	N/A		
		2. Pressurization	N/A	N/A	N/A		
PT-SAMONDA.		D. No. of continuous	01	01	MR		
THE PERSON		staircase to terrace					
Story bearing		E. Width of corridor	N/A	N/A	N/A		
-		F. Door size	N/A	206 cms x 80cms	N/A		
3		Compartmentation					
		1) Fire check door	N/A	N/A	N/A		
-		2) Sealing of electrical shafts	N/A	N/A	N/A		
		3) Fire rating of shaft door	N/A	N/A	N/A		
-		4) Water curtain	N/A	N/A	N/A		
		5) Fire Dampers	N/A	N/A	N/A		
4		Smoke Management System	14/17	14/12	17/11		
+	•	1) Basements	30 ACPH	Exhaust fan	MR		
		1) Dascillellis	JUACIT	Lallaust Iall	IVIIV		

14/6

×	2) Upper floors	12 a/c per hour	Natural	MR
5.	Fire Extinguishers			
	1) Total numbers	10 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel	* .		
a .	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Syste	em	
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	required	Tiovided	IVIIC
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	14/21	14/11	14/71
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	14/11	14/71	14/14
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	14/11	14/21	14/11
12.	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	TV/A	INA	INA
13.	1) Ground level	N/A	N/A	N/A
		N/A	N/A	N/A N/A
	a) Discharge of main	IN/A	N/A	IN/A
	b) Head of main pump	N/A	N/A	N/A
			N/A	N/A
	c) Number of main pumpd) Jockey pump out put	N/A N/A	N/A N/A	N/A N/A
		N/A N/A	N/A N/A	N/A N/A
	e) Jockey pump headf) Stand by pump output	N/A N/A	N/A N/A	N/A
		N/A	N/A N/A	N/A
		N/A N/A	N/A N/A	N/A N/A
	h) Auto starting/Manual	IN/A	IN/A	IN/A
	stopping			
	2) Terrace level	450 I D	450 I DM	MD
	a) Discharge of pump	450 LPm	450 LPM	MR
	b) Head of pump	35 mtr.	35 mtr	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR

Wan

14.	Captive Water Storage for Fire Fighting				
	Under ground tank capacity	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
- 1	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	Required	Provided	MR	
	d) Fireman's switch	Required	Provided	MR	
	e) Lift signage	Required	Provided	MR	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection Syster Risk, if any:	em for Protec	tion of special	NA	

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1132 dated 29/10/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

Doles)

hsylpolic