GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/GH/2016/ W2/1142

FIRE SAFETY CERTIFICATE

Certified that Hotel Shubham Vilas located at A-42, Vishal Enclave, Rajouri Garden, New Delhi-110027, running on 2nd & 3rd Floors with 6 guest rooms on each floor (Total 12 Rooms) in a building comprised of Basement, Ground + Three Upper Floors only, was earlier issued FSC by this department vide letter No. F6/DFS/MS/2013/GH/03 Dated 04/03/2013. The premises was re-inspected by the officer from this department on dated 01/07/2016 in the presence of Mr. Amit Chadha (Partner) and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition. The premises have therefore deemed complied with the requirements of Rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class Residential Group A-1(i) with effect from 14 / 7 /2016 in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 14/7/1/6 at New Delhi by.

(DHARAMPAL BHARDWAJ) DY. CHIEF FIRE OFFICER, Phone No. 011-25156707.

Dated: 14/ 7 2016

Copy to :-

- 1. Mr. Amit Chadha (Partner), Hotel Shubham Vilas located at A-42, Vishal Enclave, Rajouri Garden, New Delhi-110027.
- · 2. Add. Commissioner of Police (Licensing), First Floor, Police Station, Defence Colony, New Delhi.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

Name & address of the building: Hotel Shubham Vilas, A-42, Vishal Enclave, Opp. TDI
 Mall, Rajouri Garden, New Delhi-110027.

2. Type of Occupancy : Class-A (Residential)

3. Type of Case : Renewal (2nd & 3rd floor only in B, G + Three story building)

4. Details of previous NOC : F6/DFS/MS/2013/GH/03 Dated 04/03/2013

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 01/07/2016

7. Name of the Inspecting Officer: A.K. Jaiswal (A.D.O. JWP)

8. Name and designation of Officer

from the building side : Mr. Amit Chadha (Partner)

9. Year of Construction : 2008

10. Applicant's letter No. :-Nil

S No	Minimum standards on fire prevention and fire safety U/R 33			Provided at site	Remarks MR/NMR		
1.	Access of building						
	Road width	Required		Provided	MR		
	Gate width	NR	On ma	in road (24 mtr)	NR		
	Width of internal road	NR		NR	NR		
2.	Number, width, Type & Arrang	gements of ex	xits				
	a. Number of staircases						
	Upper floors	2	* 4	2	MR		
	Basements	NA		NA	NA		
	b. Width of staircases			4			
	Upper floors	Old Case	1.23	mtr & 0.94 mtr	MR		
	Basements	NA		NA	NA		
	c. Protection of exits		-				
	Fire check door	NR		NR	NR		
	Pressurization	urization NR continuous 01 ase to terrace		NR	NR		
	d. No of continuous			Provided	MR		
	staircase to terrace			\$. ·			
	e. Width Of Corridor			1.34 mtr	MR		
	f. Door Size	Old Case		0.86 mtr	MR		
3.	Compartmentation						
-	Fire check door	Required		Provided	MR		
	Sealing of electrical shafts	NR	2	NR	NR		
	Fire Rating of shaft door	NR		NR	NR		
	Water Curtain	NR		NR	NR		
	Fire Dampers	NR		NR	NR		
4.	Smoke managements System						
	Basements	NR		NR	NR		
	Upper floors	NR		Open	MR		
5.	Fire Extinguishers						
	Total numbers	6		6	MR		
	• Types	ISI marked ABC/CO ₂	,	Provided	MR		

	6.	First -	- Aid Hose Reels	- 12 1 1		, , ,		
			Total numbers on each floor	1		Provided	MR	
		•	Length of hose ree	l 30Mtr.		Provided	MR	
		•	Nozzle diameter	5mm.		Provided	MR	
	7.	Auton	natic fire detection ar	nd alarming	evetem	- vovi,aca	IVII	
		. • .	Type of detector	NA NA	system	NA	NI A	
		•	Location of Main	NA		NA	NA	
	A many property of the	The second section of the second	Panel	en e	to the first series with the feeting of the time of time of the time of time o	TVA	NA	*11 19 47 7 2 4 4 7
		•	Location of Repeate Panel	er NA		NA	NA	
	-	•	Alternate source of power	NA		NA	NA	.,
		•	Hooters' Location	NA		VA	NA	
	8.	MOEF	Α.	Required				
	9.		Address System	Required	·	Provided Provided	NR	
	10.	Automa	atic Sprinkler System	nequire		rovided	NR .	
			Basements	NR		Provided	NID	
	2	•;	Upper Floor	NR		IR ·	NR	
			Sprinkler above false			IR	NR	
			ceiling			II.	NR .	
	11.	Internal	Hydrants					
			Size of riser/down-	100 mm	1.	00		
			comer	100 11111	10	00 mm	MR	
		• 1	Number of hydrants	1	1		110	
		p	per floor		1		MR	
		• F	Hose Box	1	1		•	
	12.	Yard Hy		<u> </u>	1		MR	
			otal number of	NR .	NI)	1	
			ydrants		NF	1	NR	
			lose Box	NR	NF)	ND	
	13.		Arrangements		,	1	NR	
	. •	Ground						
	•	Dischar	rge of main pump	NR	NR		NR	
	>	Head of	f main pump	NR	. NR		NR ·	_
-	. >	Numbe	r of main pumps	NR	NR		NR	
-	4	Jočkey	pump out put	NR	NR		NR	\dashv
-	4	Jockey-	pump head	NR	NR		NR	
H	<u> </u>	Standby	Pump out put	NR	NR		NR	
-		Standby	Pump Head	NR	NR		NR	
		Auto Sta	aring/Manual	NR	NR		NR	
-	<u> </u>	stopping						
-			ouse Access	NR.	NR		NR	
	•	Terrace.		A				
		Discharg	ge of pump	450 LPM	Prov	vided	MR	
		Head of	the pump	36 MH	Prov	vided	MR	
Power supply					vided	MR		
	>	Auto sta	rting of pump	Required	Prov	vided	NR	
1	14. C	Captive wa	ater Storage for fire f	fighting				_
		• Un	derground tank	NR	NR		NR	
		cap	pacity		1414		Alphabata in a	1
			aw of connection	NR	NR		NR	
			e service inlet	NR	NR		NR	
		> Acc	cess to tank	NR .	NR		NR	

			N/II	
15	Exit Signage	Required	Provided	M/R
16.	Provision of Lifts	1		
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of lift lobby	Required	Provided	MR
	Communication in lift Car	Required	Provided	NR
	Fireman's Grounding Switch	Required	Provided	NR
	Lift Signage	Required	Provided	NR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area	NR	NR	
	> Total area	NR	NR	NR
	Location	NR	NR	NR
19.	Fire control room			
	Detector system panel	NR	NR	NR
	Flow Switch Panel	NR	NR	NR
	PA System Panel	Required	Provided	NR
	Battery backup	Required	Provided	NR
	Building Floor Plans	NR	NR	NR
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NR	NR ·	NR

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2013/GH/03 Dated 04/03/2013 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name : A.K. Jaiswal

Designation: A.D.O. (JWP)

2.0/(0)

Applied .