GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ MD2/1188

Dated: 22/7/16

FIRE SAFETY CERTIFICATE

Certified that Golcha Cinema located at 3630, Netaji Subhash Marg, New Delhi comprised of Ground + 2 Upper Floors was granted FSC by this department vide letter No. F6/DFS/MS/Cinema/2013/432 dated 12/06/13. the premises was re-inspected by the officer concerned of this department on 25/06/2016 in the presence of Mr. N.R. Saini, DGM of the cinema hall and found that the said cinema hall have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises/building is fit for occupancy of class assembly (cinema) with effect from --2-2-1-7-1-6-- for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

Issued on at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service Ph- 011- 23412225

Copy to:

1. The District Magistrate (Central), Darya Ganj, New Delhi-110002.

2. The DGM, Golcha Cinema, 3630 Netaji Subhash Marg, Darya Ganj, New Delhi-110002

Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	N-	-82	
1.Name & address of the building	SPECTION REP	ORT	
2. Type of occupancy:-	Subhash N	nema located at 36 Marg, New Delhi-1 (GF waiting area,	10002
3. Type of case:-4. Details of previous FSC:-	Renewal No. F6/DF	S/MS/CINEMA/2	
5. Fire safety directives No6. Date of inspection:-7. Name of the inspecting office	N/A 25/06/16 er:- A D.O. M.	3.	duted
8. Name & designation of officeFrom the building side:-9. Year of construction:-	Mr. N.R. S.		
10. Applicant's letter No:- No. Minimum Standards on fire	32/16-17 Da	ated 10/06/16	
Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site PSS	Remarks MR/NMR
Access to Building	artangements		
1) Road width2) Gate width	6 mtr.	12 mtr.	MR
		Directly accessible from the road	MR
3) Width of internal road	N/A	N/A	N/A
Number, Width Type & Arran A. Number of staircases	ngement of Exits	9	

S.No	Minimum St. 1 1 32/16-1/ Dated 10/06/16				
8	Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site PSS	Remarks MR/NMR	
1.	Access to Building	and the second s			
	1) Road width	6 mtr.	12		
	2) Gate width	o mu.	12 mtr.	MR	
			Directly accessible from	MR	
	3) Width of internal road	DI/A	the road		
2.	Number Width Type & A	N/A	N/A	N/A	
	Number, Width Type & Arr. A. Number of staircases	angement of Exits	3		
	1. Upper floors	00.37	2	×	
	2. Basements	02 No.	03 No.	MR	
	B. Width of staircase	N/A	N/A	N/A	
	1. Upper floors				
	2. Basements	1.5 mtr.	1.5 mtr. each	MR	
	C. Protection of exits	N/A	N/A	N/A	
	1. Fire check door	271			
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace	01 No.	01 No.	MR	
	E. Width of corridor	1.5 m	1.5 m	MR	
	F. Door size	1.5 mtr.(8	Provided	MR	
1	Compositor	Nos)		IVIIC	
	Compartmentation		3 /		
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	27/4	N/A	
	5) Fire Dampers	N/A	DT/A	N/A N/A	
	Smoke Management System			IN/A	
	1) Basements	30 ACPH	N/A		



- N/83-

1	2) Upper floors	12 ACPH	Provided Exhaust Fan	MR	
5.	Fire Extinguishers		5 ti		
	1) Total numbers	14 Nos.	Provided	MR	
	2) Types	ABC & CO2	Provided	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1)Total number at each floor	01 Nos.	Provided	MR	
	2) Length of hose reel hose	30 mtr.	Provided	MR	
	3) Nozzle diameter	5 mm.	Provided	MR	
7.	Automatic Fire Detection & A	larming System		1	
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	N/A	N/A	N/A	
9	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System			T.	
	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false ceiling	N/A	N/A	N/A	
11.	Internal Hydrants			v	
	1) Size of riser/down-comer	Required	Provided	MR	
	2) Number of hydrants per	01 at ground	Provided	MR	
	floor	floor		e *	
ā	3) Hose box	01	Provided	MR	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	

13.	Pumping Arrangement	7,0		
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
50	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping		в В	
	2) Terrace level			
	a) Discharge of pump	450 LPM	Provided	MR
	b) Head of pump	30 mtr.	Provided	MR

2

	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank capacity	30000 ltrs	Provided	MR		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	Required	Provided	MR		
	d) Over head tank capacity	2,7000 ltrs.	Provided.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A		

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/CINEMA/2013/432 dated 12/06/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Assistant Divisional Officer

Dy CRO (4152)