FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/WZ/ EH/2016/ 1196

Dated: 16/07/2016

FIRE SAFETY CERTIFICATE

Certified that the M/s Raftaar (A Unit of AAA Hospitality) located at Premises No. 15C, NWA, Punjabi Bagh(W), New Delhi-110041 is running on 2nd and 3rd Floor only, in a premises comprising Basement, Stilt Floor, Upper Ground Floor, 1st floor, 2nd Floor & 3rd Floor only owned / occupied by M/s Raftaar (A Unit of AAA Hospitality) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service rules, 2010 and verified by the officers concerned of Fire Service on 19.07.2016 in presence of Mr. Ram Aiyer and that the building / premises is fit for occupancy class Assembly / Restaurant (Eating House) (Group-D) with effect from 2 6 / 67 /2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of conditions under 38 of the Delhi Fire Service rules, 2010.

(ATUL GARG) CHEF FIRE OFFICER, Phone No .011-23414250.

Copy to :-

ou

- 1. Authorized Signatory, M/s Raftaar (A Unit of AAA Hospitality), Premises No. 15C, 2nd and 3rd Floor, NWA, Punjabi Bagh(W), New Delhi-26.
- 2. Dy. Health officer, South Delhi Municipal Corporation, Public health Department, West Zone Vishal Enclave, New Delhi-27 w.r.t. letter No. D-1433/HD/WZ dated 02/05/2016.

Conditions for the validity of Fire Safety Certificate:-

- 1. All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire- fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW dfs Delhigovt pic in

INSPECTION REPORT

Re-Inspection to see the compliance of Shortcoming communicated vide Letter No.F6/DFS/MS/2016/1694 dated 12/07/2016

1. Name &address of the building : M/s Raftaar (A Unit of AAA Hospitality),

Premises No. 15C, 2nd and 3rd Floor, NWA, Punjabi

Bagh(W), New Delhi.

2. Type of Occupancy : Assembly / Restaurant (Eating House)

3. Type of Case : New (Restra at 2nd Floor, 3rd Floor.)

4. Details of previous NOC : Nil

5. Fire Safety directives letter No. : NBC (Part-IV)

6. Date of inspection : 20.06.2016

Basement, Stilt Floor, Upper Ground Floor, 1st floor, 2nd Floor & 3rd Floor.

Area: 464 m2

7. Name of the Inspecting Officers: Mukesh Verma (D.O. West) & A. K. Jaiswal (ADO JWP)

8. Name and designation of officers

From the building side : Sh. Vineet Mittal (Partner)

9. Year of Construction : 2009

10. Applicant's letter No. : Nil.

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC / BBL Requirement	Provided at site	Remarks MR/NMR		
1.	Access to building					
	Road width	09mtr	30 mtr	M.R.		
	• Gate width	On main road	On main road	MR		
	Width of internal road	N/A	N/A	N/A.		
2.	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases		2			
	Upper Floors	02	02	M.R.		
	Basement	N/A	N/A	N/A		
8	b. Width of staircases		a 8			
	Upper Floors	1.5 mtr & 1.00 mtr	2.00Mtr.,1.20Mtr.	M.R.		
	Basement	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	d. No. of continuous staircases to terrace	1	1	M.R.		
	e. Width of Corridor	N/A	N/A	N/A		
	f. Door size	2.00mtr X 1 1.5m X 1	2.00x1, 1.50x1	M.R.		
				A		
				:		

N/A	N/A	N/A				
N/A	N/A	N/A				
N/A	N/A	N/A				
N/A	N/A	N/A				
N/A	N/A	N/A				
Smoke Management System.						
N/A	N/A	N/A				
Required	Provided	M.R.				
· · · · · · · · · · · · · · · · · · ·						
6	8	M.R.				
ABC & CO ₂ type	Provided	M.R.				
ISI marks required	provided	M.R.				
1 "	1	M.R.				
30 mtr.	Provided	M.R.				
5 mm	Provided	M.R.				
, and the second						
arming system.						
Smoke	Smoke	M.R.				
Ground floor	Provided	M.R.				
required	Provided	M.R.				
Required	Provided	M.R.				
Required	Provided	M.R.				
Required	Flovided	IVI.R.				
Required	Provided	M.R.				
N/A	N/A	N/A				
Required	Provided	M.R				
N/A	N/A	N/A				
Required	Provided	M.R				
N/A	N/A	N/A				
ceiling Internal Hydrants						
150 mm	Provided	M.R				
1	1	M.R				
1	1	M.R				
1		1				





	Total number of	N1/0			
	hydrants	N/A		N/A	N/A
	Hose Box	N/A		N/A	N/A
13		7			
	Ground Level				
	Discharge of main pum	p 2280 LPM	Pro	vided at terrace	NAD
	> Head of Main pump	40 MH		vided at terrace	
	Number of main pumps			vided at terrace	
	> Jockey Pump out put	180 LPM		vided at terrace	
	> Jockey pump head	40 MH			
	Standby pump out put	2280 LPM		vided at terrace	37,513,63,6
	Standby pump Head	40 MH		vided at terrace	A AMERICAN A
	> Auto Starting/Manual	Required		vided at terrace	
	stopping	Required	Prov	vided at terrace	MR
	Pump Hose Access Terrace level	Required	Prov	rided at terrace	MR
				4	
	Discharge of pump	450 LPM	450 1	LPM Provided	M.R
	Head of the pump	40 MH	Prov	ided	M.R
	> Power supply	Required	Prov	ided	M.R
	Auto Starting of pump	required	Prov	ided	M.R
4.	Captive Water Storage for fire f	ighting.			
		9			
	Underground tank capacity	50,000 ltr	Prov	ided (on terrace)	MR
	Draw -off connection	N/A	N/A	8 3	N/A
	Fire service inlet	Required	Prov	ided	MR
	Access to tank	Required	Prov	rided	MR
	Overhead Tank Capacity	10,000 ltrs		00 ltrs	M.R
	Exit Signage.	Required	Prov		M.R.
. 1	Provision of Lifts				
	Pressurization of Lift Shaft	N/A	>T/4	7	
			N/A		N/A
	Pressurization of Lift lobbyCommunication In lift Car	N/A	N/A		N/A
	• Fireman's Grounding	N/A	N/A	1	N/A
	Switch	N/A	N/A		N/A
	• Lift Signage	N/A	N/A		N/A
					-

17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area			
	Total Area	N/A	N/A	N/A
0	Location	N/A	N/A	N/A
9.	Fire Control Room	Required	Provided	M.R
*	Detector System Panel	N/A	N/A	N/A
*	Flow Switch Panel PA system Panel	N/A	N/A	N/A
-	system raner	N/A	N/A	N/A
	Battery backup Building Floor plans	N/A	N/A	N/A
	- straing 1 loof plans	N/A	N/A	N/A
S	Special Fire Protection Systems for Protection of pecial Risks, if any:	N.R.	N.R.	N.R.

Note:- All the water storage tanks are provided on terrace. Total capacity of water storage tank 50,000 + 10,000=60,000 ltrs.

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspection Officer

Name: A. K.Jaiswal

Designation; ADO (Jwp.)

Signature of the Inspection Officer

Name: Mukesh Verma

Designation; D.O.(West)

cho wed to 1/6