GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ NO2/12/8

Dated : 01/08/16

FIRE SAFETY CERTIFICATE

Certified that M/s Hotel Raj Kamal located at 1895-97 Chandni Chowk, Delhi - 110006. Comprised of Ground floor (Commercial use), 1st floor (reception + 06 guest rooms + lobby + office) and 2nd floor (06 tin shed rooms for staff and store) Total 06 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/NDZ/624 dated 26/07/2013. The premise was re-inspected by the officer concerned of this department on 20/07/16 in the presence of Sh. Charanjeet Singh, Manager and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 06 guest rooms only as above with effect from Delhi Sire Service Rules above with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on-01-08-11-6--at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service Ph: - 011-23412225

Copy to: -

1 The Joint. C.P.(Lic.), Police Station, Defence colony, 1st floor, New Delhi

M/s Hotel Raj Kamal,
 1895-97 Chandni Chowk, Delhi - 110006.
 Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8 The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to it expiry

INSPECTION REPORT

1. Name & address of the building: - M/s Hotal Raj Kamal, 1895-97 Chandni Chowk, Delhi - 110006.

2. Type of occupancy:-

Residential Group A-1, Ground + 2 upper floors

Total 06 guest rooms

3. Type of case:-

4. Details of previous FSC: -

Renewal No. F6/DFS/MS/GH/2013/NDZ/624 dated

Provided at site

Old case

Remarks

N/A

N/A

26/07/2013.

N/A 5. Fire safety directives No.-6. Date of inspection:-

20/07/16

Minimum Standards on fire Requirement

7. Name of the inspecting officer:-

A. D.O. Mehmood

8. Name & designation of officer From the building side:-

1) Basements

2) Upper floors Fire Extinguishers

1) Total numbers

Sh. Charanjeet Singh Starting year 1982

9. Year of construction:-10. Applicant's letter No:-

Dated 30/06/16 Nil

| 5.110. | Prevention and fire safety U/R 33 | (Existing Fire Safety Measures) | (PSS) | MR/NMR | |
|--------|---|---------------------------------------|-----------------|--------|--|
| 1. | Access to Building | | | | |
| | 1) Road width | Accessible | 12 mtr. (Aprox) | MR | |
| | 2) Gate width | N/A | N/A | N/A | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Arrangement of Exits | | | | |
| y | A. Number of staircases | | | | |
| | 1. Upper floors | 01 No | 01 No. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | | |
| | 1. Upper floors | 80 cms. | 87 - 93 cms. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | | | | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous staircase to terrace | N/A | N/A | N/A | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | 1.0 0 mtr | 1.00 mtr | MR | |
| 3. | Compartmentation | | | | |
| | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 4. | Smoke Management System | | | | |
| | | 7.71 | 3.7/4 | NT/A | |

1) brod Mor- Stops brond- House, beautin Afree.
2) Print 61000 - to Room brond- House, beautin office.
3) toward Mow - store, start Room.
3) toward Mow - store, start Room.

Shorten

N/A

N/A

07 Nos.

N/A

N/A

Provided

| | 2) Types | ABC & CO2 | Provided | MR | | | |
|---------|--|-----------|----------|-------|--|--|--|
| | 3) ISI marking | Required | Provided | MR | | | |
| 6. | First-Aid Hose Reel | | | | | | |
| | 1)Total number of each floor | N/A | N/A | N/A | | | |
| | 2) Length of hose reel hose | N/A | N/A | N/A | | | |
| | 3) Nozzle diameter | N/A | N/A | N/A | | | |
| 7. | Automatic Fire Detection & Alarming System | | | | | | |
| | 1) Type of detectors | N/A | N/A | N/A | | | |
| | 2) Location of main panel | N/A | N/A | N/A | | | |
| | 3) Location of repeater panel | N/A | N/A | N/A | | | |
| | 4) Alternate source of power | N/A | N/A | N/A | | | |
| | 5) Hooter's Location | N/A | N/A | N/A | | | |
| 8. | MOEFA | N/A | N/A | N/A | | | |
| 9. | Public Address System | N/A | N/A | N/A | | | |
| 10. | Automatic Sprinkler System | | | | | | |
| | 1) Basement | N/A | N/A | N/A | | | |
| | 2) Upper floors | N/A | N/A | N/A | | | |
| | 3) Sprinkler above false | N/A | N/A | N/A | | | |
| | ceiling | | | | | | |
| 11. | Internal Hydrants | | | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | | | |
| | 2) Number of hydrants per | N/A | N/A | N/A | | | |
| | floor | | | | | | |
| | 3) Hose box | N/A | N/A | N/A | | | |
| 12. | Yard Hydrants | | | | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A | | | |
| | 2) Hose box | N/A | N/A | N/A | | | |
| 13. | Pumping Arrangement | 18 | | | | | |
| | 1) Ground level | N/A | N/A | N/A | | | |
| | a) Discharge of main pump | N/A | N/A | N/A | | | |
| | b) Head of main pump | N/A | N/A | N/A | | | |
| | c) Number of main pum | | N/A | N/A | | | |
| | d) Jockey pump out put | N/A | N/A | N/A | | | |
| | e) Jockey pump head | N/A | N/A | N/A | | | |
| | f) Stand by pump outpu | | N/A | N/A | | | |
| | g) Stand by pump head | N/A | N/A | N/A | | | |
| | h) Auto starting/Manual stopping | | N/A | N/A | | | |
| + | 2) Terrace level | | | | | | |
| | a) Discharge of pump | N/A | N/A | N/A | | | |
| | b) Head of pump | N/A | N/A | N/A | | | |
| | c) Power supply | N/A | N/A | N/A | | | |
| | d) Auto starting of pump | | N/A | N/A | | | |
| 14. | Captive Water Storage for Fi | | | | | | |
| * | | | NT/A | N/A | | | |
| - 1 × 1 | 1) Under ground tank | N/A | N/A | IN/Fi | | | |

| | b) Fire service inlet | N/A | N/A | N/A |
|-----|-------------------------------------|------------------|--------------------|------------|
| | c) Access to tank | N/A | N/A | N/A |
| 1.5 | d) Over head tank capacity | N/A | N/A | N/A |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | 1 | Trovided | MR |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| 17. | e) Lift signage | N/A | N/A | N/A |
| | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | |
| | d) Battery backup | N/A | N/A | N/A N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 0. | Special Fire Protection System any: | for Protection o | f special Risk, if | N/A |

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2013/NDZ/624 dated 26/07/2013, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Assistant Divisional Officer

2015/16 FTP15