GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ MD2/12/7

Dated: 01/08/16

FIRE SAFETY CERTIFICATE

Certified that M/s Shezan Palace Guest House located at 1331 Chowk Chitli Qabar, Jama Masjid, Delhi comprised of Ground floor (Commercial use), 1st floor (reception + 04 guest rooms), 2nd floor (04 guest rooms), 3rd floor (04 guest rooms), 4th floor (owner's residence) and terrace (Mobile antenna + Water tank) Total 12 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/NDZ/678 dated 07/08/2013. The premise was re-inspected by the officer concerned of this department on 19/07/16 in the presence of Mr. Faiser Zamal, Manager of the guest house and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 12 guest rooms only as above with effect from occupancy class Residential Group A-1 for 12 guest rooms only as above with effect from or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on _____o1 \[\sigma_8 \] 16 ___at New Delhi by.

(Vipin Kental). Chief Fire Officer Delhi Fire Service Ph- 011- 23412225

مار

Copy to: -

1 The Joint. C.P.(Lic.), Police Station, Defence colony, 1st floor, New Delhi

The Manager, Shezan Palace guest house,
 1331 Chowk Chitli Qabar, Jama Masjid, Delhi – 110006.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8 The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to it expiry.

INSPECTION REPORT

1. Name & address of the building:- M/s Shezan Palace guest house, 1331 Chowk Chitli

Qabar, Jama Masjid, Delhi - 110006

2. Type of occupancy:-

Residential Group A-1, Ground + 4 upper floors(GF - commercial, 1st to 3rd floor - 04 guest rooms each & Rec. of at 1st floor, 4th floor - owner's residence,

Terrace - water tank and antena)

Total 12 guest rooms

3. Type of case:-Renewal

No. F6/DFS/MS/GH/2013/NDZ/678 dated 4. Details of previous FSC: -

07/08/2013.

5. Fire safety directives No.-N/A

6. Date of inspection:-19/07/16

7. Name of the inspecting officer:-A. D.O. Mehmood

8. Name & designation of officer

From the building side:-Mr. Faiser Zamal (manager)

9. Year of construction:-2009

Nil Dated 12/07/16 10. Applicant's letter No:-

				Old case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement (Existing) Fire Safety Measures	Provided at site (PSS)	Remarks MR/NMR	
1.	Access to Building	**			
	1) Road width	Accessible	5 mtr. (Aprox)	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arran	gement of Exits			
	A. Number of staircases				
	1. Upper floors	01 No	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	80 cms.	81-87 cms.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	01 No	01 No.	MR	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1.0 0 mtr	1.00 mtr	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	NA	

. /	1 1 6)
NI	14
V	

	2) Upper floors	N/A	N/A	N/A		
5.	Fire Extinguishers					
	1) Total numbers	06 Nos.	06 Nos.	MR \square		
	2) Types	ABC & CO2	Provided	MR		
	3) ISI marking	Required	Provided	MR		
5.	First-Aid Hose Reel	1				
0.	1)Total number of each	01 Nos.	Provided	MR		
	floor					
- 2	2) Length of hose reel hose	30 m.	30 m.	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & Alarming System					
7.	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
0	MOEFA	N/A	N/A	N/A		
8. 9.	Public Address System	Required	Provided	MR		
		Required	TTOVICE	11111		
10.	Automatic Sprinkler System	N/A	N/A	N/A		
	1) Basement	N/A	N/A	N/A		
- "	2) Upper floors	N/A	· N/A	N/A		
	3) Sprinkler above false	IN/A	11//11	11/21		
	ceiling	, , , , , , , , , , , , , , , , , , ,				
11.	Internal Hydrants	NT/A	N/A	N/A		
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	IN/A	IN/A		
	floor	NT/A	N/A	N/A		
	3) Hose box	N/A	IN/A	IN/A		
12.	Yard Hydrants	77/4	NT/A	N/A		
	1) Total number of hydrants	N/A	N/A	N/A N/A		
	2) Hose box	N/A	N/A	IN/A		
13.	Pumping Arrangement		27/1	DT/A		
	1) Ground level	N/A	N/A	N/A		
× .	a) Discharge of main	N/A	N/A	N/A		
	pump			27/4		
	b) Head of main pump	N/A	N/A	N/A		
*	c) Number of main pum		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output		N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping	,				
	2) Terrace level					
	a) Discharge of pump	225 LPM	Provided	MR		
	b) Head of pump	40 mtr.	Provided	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump		Provided	MR		

AS)

N/13

14.	Captive Water Storage for Fir	e Fighting		
	1) Under ground tank	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltrs	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			,
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and tire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2013/NDZ/678 dated 07/08/2013,renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

D.O. (Central)

Assistant Divisional Officer