## FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE. NEW DELHI-110001

No. F6/DFS/MS/WZ/ EH/2016/1231

Dated: 4 / 8 /2016

## FIRE SAFETY CERTIFICATE

Certified that the M/s Nando's (A Unit of Janpath Restarants Pvt. Ltd.) Property No. 25, UGF, NWA Club Road, Punjabi Bagh West, New Delhi-110026 located on upper ground floor only, in a premises comprising Basement, Stilt Floor, Upper Ground Floor, 1<sup>st</sup> floor, 2<sup>nd</sup> Floor & 3<sup>rd</sup> Floor only owned / occupied by M/s Nando's (A Unit of Janpath Restarants Pvt. Ltd.) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service rules, 2010 and verified by the officers concerned of Fire Service on 28.07.2016 in presence of Sh. Devender (General Manager / Brand) and that the building / premises is fit for occupancy class Assembly / Restaurant (Eating House) (Group-D) with effect from // 2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of conditions under 38 of the Delhi Fire Service rules, 2010.

(ATUL GARG) CHEF FIRE OFFICER, Phone No .011-23414250.

Copy to :-

- 1. Dy. Health officer, South Delhi Municipal Corporation, Public health Department, West Zone Vishal Enclave, New Delhi-27 w.r.t. letter No. D-2244/HD/WZ dated 05/07/2016.
- 2. Sh. Devender (G. M. / Brand), M/s Nando's (A Unit of Janpath Restarants Pvt. Ltd.) Property No. 25, UGF, NWA Club Road, Punjabi Bagh West, New Delhi-110026.

## Conditions for the validity of Fire Safety Certificate:-

- 1. All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire- fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in
- 8. Basement shall be used strictly as per Building By Laws-1983.

lond

## **INSPECTION REPORT**

1. Name & address of the building

M/s Nando's(A Unit of Janpath Restarants Pvt.

Ltd.), Property No. 25, UGF, NWA Club Road.

Punjabi Bagh West, New Delhi-110026.

2. Type of Occupancy

: Assembly / Restaurant (Eating House)

3. Type of Case

: New (Restra at Upper Ground floor)

4. Details of previous NOC

: Nil

5. Fire Safety directives letter No.

: NBC (Part-IV)

6. Date of inspection

: 28.07.2016

7. Name of the Inspecting Officers

: A. K. Jaiswal (ADO JWP)

8. Name and designation of officers

From the building side

: Sh. Devender (General Manager / Brand)

9. Year of Construction

: 2015-16

10. Applicant's letter No.

: D-2244/HD/WZ Dated 05/07/2016.

Prevention and fire safety U/R 33	NBC / BBL Requirement	Provided at site	Remarks MR/NMR				
Access to building							
Road width	09mtr	30 mtr	M.R.				
Gate width	On main road	On main road	MR				
Width of internal road	N/A	N/A	N/A.				
Number, Width, Type & Arrangement of Exits							
a. Number of staircases							
<ul> <li>Upper Ground Floor</li> </ul>	2	2	M.R.				
<ul> <li>Basement</li> </ul>	N/A	N/A	N/A				
b. Width of staircases							
• Upper Floors	2.00m x 1, 1.00m x 1	2.00m x1 & 1.50m x 1	M.R.				
• Basement	N/A	N/A	N/A				
<ul> <li>Fire check door</li> </ul>		N/A	N/A				
<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A				
	1	1	M.R.				
e. Width of Corridor	N/A	N/A	N/A				
f. Door size	2.00m x 1 1.00m x 1	2.00m x1& 1.00 x 1	M.R.				
		ų.					
	<ul> <li>Gate width</li> <li>Width of internal road</li> <li>Number, Width, Type &amp; Arrange</li> <li>a. Number of staircases</li> <li>Upper Ground Floor</li> <li>Basement</li> <li>b. Width of staircases</li> <li>Upper Floors</li> <li>Basement</li> <li>c. Protection of exits</li> <li>Fire check door</li> <li>Pressurization</li> <li>d. No. of continuous staircases to terrace</li> <li>e. Width of Corridor</li> </ul>	<ul> <li>Gate width</li> <li>Width of internal road</li> <li>Number, Width, Type &amp; Arrangement of Exits</li> <li>a. Number of staircases <ul> <li>Upper Ground Floor</li> <li>Basement</li> <li>Width of staircases</li> <li>Upper Floors</li> <li>2 N/A</li> </ul> </li> <li>b. Width of staircases <ul> <li>Upper Floors</li> <li>2.00m x 1</li> <li>1.00m x 1</li> </ul> </li> <li>Basement</li> <li>N/A</li> </ul> <li>c. Protection of exits <ul> <li>Fire check door</li> <li>Pressurization</li> <li>No. of continuous staircases to terrace</li> <li>Width of Corridor</li> <li>Door size</li> </ul> </li> <li>7 N/A</li> <li>2.00m x 1</li> <li>N/A</li> <li>N/A</li> <li>2.00m x 1</li>	<ul> <li>Gate width</li> <li>Width of internal road</li> <li>Width of internal road</li> <li>Number, Width, Type &amp; Arrangement of Exits</li> <li>a. Number of staircases <ul> <li>Upper Ground Floor</li> <li>Basement</li> <li>Width of staircases</li> <li>Upper Floors</li> <li>Upper Floors</li> <li>Basement</li> <li>Protection of exits</li> <li>Fire check door</li> <li>Pressurization</li> <li>No. of continuous staircases to terrace</li> <li>Width of Corridor</li> <li>N/A</li> <li>N/A&lt;</li></ul></li></ul>				

).	Compartmentation.				Standard of the second of the	A STATE OF THE PARTY CO. LANSING STREET	and the same and t	
	Fire check door		N/A					
	Sealing of electrical shafts		N/A			N/A		
	• Fire Rating of shaft door		N/A	tion relation recovery that we have	N/A	N/A		
The state of the s	<ul> <li>Water Curtain</li> </ul>		N/A		N/A		N/A	
	• Fire Dampers		N/A	Parameter and the second second	N/A		N/A	
4.	Smoke Management System.				N/A		N/A	
	Basements	n.	7			THE RESERVE THE PARTY NAMED IN	The second secon	
	• Upper floors		N/A		N/A		N/A	
<i>p</i> =			Required	*	Provided		M.R.	
5.	Fire Extinguishers					-1		
	<ul> <li>Total numbers</li> </ul>							
	• Types	2		4		2	M.R.	
		A	ABC & CO <sub>2</sub> type	P	rovided		M.R.	
	<ul> <li>IS marking</li> </ul>	15	SI marks required	pi	rovided		M.R.	
	First-Aid Hose Reel.							
	<ul> <li>Total numbers on each floor</li> </ul>	1		1	1		M.R.	
	<ul> <li>Length of hose reel hose</li> </ul>	30 mtr.		Provided				
	<ul> <li>Nozzle diameter</li> </ul>		nım				M.R.	
	Automotic C.			riovided		M.R.		
	Automatic fire detection and a  Type of detectors	alarmi	ng system.					
		NR		Sm	Smoke		VR	
	<ul> <li>Location of Main Panel</li> </ul>	NR		Pro	vided	1	VR	
	<ul> <li>Location of Repeater</li> </ul>		NR				NR	
	Panel	NR		Pro	Provided		VR	
	<ul> <li>Alternate source of power</li> </ul>	NID					100.00	
-	<ul> <li>Hooter's Location</li> </ul>	NR		Provided		N	NR	
	OEFA	Requ	iired	Prov	/ided	M	.R.	
Pu	blic Address System.	N/A		N/A				
Aı	tomatic Sprinkler system			IN/A		N/	'A	
	sprinkler system							
	• Basement	N/A		N/A N				
	<ul> <li>Upper Floor</li> </ul>	NR			ded on	N/		
					upper Ground			
Int	• Sprinkler above false ceiling	N/A		N/A		N/A	1	
	rnal Hydrants		5	C was could write her being bee				
	• Size of riser/down-comer 100		ımm 10		100mm N			
	the of fly diality ber	1		1	The state of the s	MR		
	floor	1		1			Section 2	



12.	Vand III. day	N/3					
12.	yard Hydrants.	Yard Hydrants.					
	Total number of	N/A	N/A	N/A			
	hydrants	N/A	N/A	N/A			
2	Hose Box			IV/A			
13.	Pumping Arrangements.			3:			
	Ground Level						
	Discharge of main pump	NR	NR	NR			
	► Head of Main pump	NR	NR	NR			
	Number of main pumps	NR	NR	NR			
	Jockey Pump out put	NR	NR	NR			
	> Jockey pump head	NR					
	> Standby pump out put		NR	NR			
	Standby pump Head	NR	NR	NR			
	<ul> <li>Auto Starting/Manual</li> </ul>	NR	NR	NR			
	stopping	NR	NR	NR			
	Pump Hose Access	NR	NR	NR			
	Terrace level						
	Discharge of pump	450 LPM	450 LPM	M.R			
	Head of the pump	40 MH	40 MH	M.R			
	Power supply	Required	Provided	M.R			
	Auto Starting of pump	required	Provided	M.R			
4.	Captive Water Storage for fire fi	ghting.					
		ss <sup>,</sup>					
	Underground tank capacity	NR	NR	NR			
	Draw -off connection	NR	NR	NR			
	Fire service inlet	NR	Provided	NR			
	Access to tank	NR	Provided	NR			
	Overhead Tank Capacity	10,000 ltrs	10,000 ltrs	M.R			
	Exit Signage.	Required	Provided	M.R.			
. 1	Provision of Lifts		,				
	The second secon	· ·					
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	.N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
	• Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
				010			

17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area	<u> </u>		
		*		
	> Total Area	N/A	N/A	N/A
	Location			
	Location	N/A	N/A	N/A
10	Eine Control D	D		
19.	Fire Control Room	Required	Provided	M.R
-	Detector System Panel	N/A	N/A:	N/A
	· · · · · · · · · · · · · · · · · · ·	. 17.2.2	IV/A	TV/A
	Flow Switch Panel	N/A	N/A	N/A
	PA system Panel			
	PA system Panel	N/A	N/A	N/A
	Battery backup			
	. Battery backup	N/A	N/A	N/A
	Building Floor plans	NI/A		37/1
		N/A	N/A	N/A
20.	Special Fire Protection	N.R.	N.R.	N.R.
	Systems for Protection of		1 1111	14.14.
	special Risks, if any:			
	vpecial relates, if any.			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspection Officer

Name: A. K.Jaiswal Designation; ADO (Jwp.)

Dy. 180 (W2)

cho. work hat 16