FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F-6/0/3/ M5/ W2/2018/ 1320

Dated: 36/08/2016

FIRE SAFETY CERTIFICATE

Certified that the Capital Business Systems Pvt. Ltd., Plot No. G-13, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41 comprised of Basement, Ground Floor, Mezzanine Floor, 1st floor only owned / occupied by Capital Business Systems Pvt. Ltd. have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service rules, 2010 and verified by the officer concerned of Fire Service on 23.08.2016 in presence of Mr. Sehgal (G.M. Admin.) and that the building / premises is fit for occupancy class "Industrial" Group – G with effect from 3° / 0° / 2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of conditions under 38 of the Delhi Fire Service rules, 2010

Issued on. 30/08/2016 at New Delhi by.

(DHARAMPAL BHARDWAJ) DY. CHIEF FIRE OFFICER, PHONE:011-25156707.

Copy to:

1. Authorized Signatory, Capital Business Systems Pvt. Ltd., Plot No. G-13, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-110041.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- . 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
 - 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
 - 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in
 - 8. Basement shall be used strictly as per BBL.

INSPECTION REPORT

1. Name & address of the building: Capital Business Systems Pvt. Ltd., Plot No. G-13,

Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41.

2. Type of Occupancy : Industrial

3. Type of Case : New (B., GF, Mezz. Floor & 1st Floor)

4. Details of previous NOC : Nil

5. Fire Safety directives Letter No.: F6/BP/79/DFS/676 dated 14.02.1979

6. Date of inspection : 23/08/2016 | Plot Area -1616 Yard² | Covered Area of Basem. – 725 Yard²

7. Name of the Inspecting Officer: A. K.-Jaiswal Covered Area of G. Floor-725 Yard²

Covered Area of Mezz.—103 Yard²

Name and designation of Officer

Covered Area of 1st Floor -725 Yard²

Covered Area of 1st Floor -725 Yard²

8. Name and designation of Officer

from the building side : Mr. Sehgal (G. M. Admin.)

9. Year of Construction : 1980

10. Applicant's letter No. :-Nil dated 19/07/2016

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements		Provided at site	Remarks MR/NMR			
1.	Access of building							
	Road width	06 mtr		15 mtr.	MR			
	Gate width	5 mtr		5 mtr	MR			
	Width of internal road	NA	3	NA	NA			
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases							
	Upper floors	2 2			MR			
	Basements	2 3			MR			
	b. Width of staircases							
	Upper floors	1.20 Mtr		1.20Mtr x 2	MR			
	Basements	1.20 Mtr		1.20Mtr x 3	MR			
	c. Protection of exits		r.s.					
	Fire check door	Required		Provided	MR			
	Pressurization	N/A		N/A	N/A			
	d. No of continuous	As per sanctioned		1	MR			
	staircase to terrace	plan N/A						
	e. Width Of Corridor			N/A	N/A			
	f. Door Size	1.20 mtr.		1.20 mtr	MR			
3.	Compartmentation				1			
	Fire check door	Required		Provided	MR			
	Sealing of electrical	Required		Provided	MR			
	shafts	3		*				
	Fire Rating of shaft door	N/A		N/A	N/A			
	Water Curtain	N/A		N/A	N/A			
	Fire Dampers	N/A		N/A	N/A			
4.	Smoke managements System	Required						
	Basements			Provided	MR			
	Upper floors	N/A		N/A	N/A			
5.	5. Fire Extinguishers							
5.	Total numbers	15		25	MR			
-								

	 Total numbers on 	NA	2		NA		
	each floor						
	 Length of hose reel 	NA	NA 30 mtr		NA		
	hose	to the same of the		ilitti	INA		
	Nozzle diameter	NA	5m	m .	NA		
			ts _				
7.	Automatic fire detection and						
	• Type of detector	N/A	Smo	ke	N/A		
	Location of MainPanel	ocation of Main N/A GF			N/A		
	Location of RepeaterPanel	N/A	N/A	. 4	N/A		
	Alternate source of power supply	N/A	Prov	ided	N/A		
	Hooters' Location	Hooters' Location N/A GF			N/A		
8.	MOEFA	Required	Prov	ided	MR		
9.	Public Address System	N/A	N/A		N/A		
10.	Automatic Sprinkler System						
	• Basements	NA (as per recommendated 14/02/79)	mendation	Provided	NA		
	Upper Floor	N/A	N/A	T-100	N/A		
	Sprinkler above false	N/A	N/A		N/A		
11.	ceiling						
11.	Internal Hydrants • Size of riser/down-	N/A (as par racom	mondation	Provided	N/A		
	comer	N/A (as per recommendation dated 14/02/79)		riovided	N/A		
	 Number of hydrants per floor 	N/A	Provi	ded	N/A		
	Hose Box	N/A Provided		ded	N/A		
12.	Yard Hydrants						
	• Total number of	N/A	N/A		N/A		
	hydrants • Hose Box	N/A	NI/A		D1 / 0		
13.	Pumping Arrangements	N/A	N/A		N/A		
	Ground Level						
	Discharge of main pump	N/A	N/A		N/A		
	Head of main pump	N/A	N/A		N/A		
	Number of main pumps	N/A	N/A		N/A		
	Jockey pump out put	N/A	N/A		N/A		
	Jockey pump head	N/A	N/A		N/A		
	Standby Pump out put Standby Pump Head	N/A	N/A		N/A		
	Standby Pump HeadAuto Staring/Manual	N/A N/A	N/A N/A		N/A		
	stopping	IN/A	IN/A	*	N/A		
)	Pump House Access	N/A	N/A		N/A		
	Terrace level						
	Discharge of pump	Not required as per recommendation dt.14/2/79	900 LF	PM	NA		
	Head of the pump	NA	40 MH	i	NA		
	Power supply	NA	Provid	ed	NA		
>	The starting of pamp	NA	Provid	ed	NA		
14.	Captive water Storage for fire f						
	 Underground tank capacity 	50,000 ltr	Provided (on 50,000 ltrs	terrace)	MR		
	Draw of connection	NI/A	20,000 1113		21/2		

Evit Cianaga						
Exit Signage	Required Provided		M/R			
Provision of Lifts						
Pressurization of LiftShaft	N/A	N/A	N/A			
Pressurization of lift lobby	N/A	N/A	N/A			
Communication in lift Car	N/A	N/A	N/A			
Fireman's Grounding Switch	N/A	N/A	N/A			
➤ Lift Signage	N/A	N/A	N/A			
Standby power supply	required	Provided	MR			
Refuge Area	N/A	N/A				
> Total area	N/A	N/A	N/A			
> Location	N/A	N/A	N/A			
Fire control room						
Detector system panel	N/A	N/A	N/A			
> Flow Switch Panel	N/A	N/A	N/A			
PA System Panel	N/A	N/A	N/A			
Battery backup	N/A	N/A	N/A			
Building Floor Plans	N/A	N/A	N/A			
Special Fire Protection	N/A	N/A	N/A			
Systems for Protection of						
special Risks, if any;	\\		1			
	Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans Special Fire Protection Systems for Protection of	 ➢ Pressurization of Lift Shaft ➢ Pressurization of lift lobby ➢ Communication in lift Car ➢ Fireman's Grounding Switch ➢ Lift Signage ➢ Lift Signage ➢ Total area ➢ Location ➢ Location ➢ Detector system panel ➢ Flow Switch Panel ➢ PA System Panel ➢ Battery backup ➢ Building Floor Plans Ø Systems for Protection of 	➤ Pressurization of Lift Shaft N/A N/A ➤ Pressurization of lift lobby N/A N/A ➤ Communication in lift Car N/A N/A ➤ Fireman's Grounding Switch N/A N/A ➤ Lift Signage N/A N/A Refuge Area N/A N/A ➤ Total area N/A N/A ➤ Location N/A N/A Pire control room N/A N/A ➤ Flow Switch Panel N/A N/A ➤ PA System Panel N/A N/A ➤ Building Floor Plans N/A N/A Special Fire Protection N/A N/A Systems for Protection of N/A N/A			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)

D. \$ (w)

Apple 14/2/16

23