GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

NEW DELHI- 110 001 No. 66/08/ans/school/2016/32/1390
FIRE SAFETY CERTIFICATE

Dated: 08/09/16

Certified that M/s Heera Public School, Samalka, Gurgaon Road, New Delhi-110037, comprised of ground plus two upper floors, owned/occupied by Heera Public School, was issued No Objection Certificate for ground plus one upper floor only vide this office letter No.F6/MS/DFS/2007/685, dated 08.03.2007. Now the school building comprised of ground plus two upper floors have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on dated 31.08.16 in the presence of Mr. Pawan Vatts (Principal) of the school and found that the school building is fit for occupancy class B 'Educational Building' with effect from S./. 5.7.... 2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules, 2010.

Issued on 68/...2016 at New Delhi by

(Vipin Kental) Chief Fire Officer T.No.011-23412225

- 1. The Principal, Heera Public School, Samalka, Gurgaon Road, New Delhi-110037. To,
 - 2. The Director of Education, Old Secretariat, Civil Lines, Delhi-52.

Conditions for the validity of fire safety certificate are as under :-

- All the means of escape shall be kept free of all type of obstruction all the time. 1.
- The employees shall be acquainted with the use and maintenance of all fire equipments 2. and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All fire fighting equipments shall be maintained in perfect working condition all time and 3. any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This Fire Safety Certificate may not be treated in any case for regularizations of 5. unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first 6. available on Delhi Fire Service Rule 2010. The form schedule www.dfs.delhigovt.nic.in.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six 7. month prior to its expiry.

| | INS | PECTION REPOR | T | | | | | | |
|-----------------------------------|--|--|---------------------|-----------------------------|----------------|--------------|--|--|--|
| 1. N | | | | Gurgaon Road, New | Delhi | -110037. | | | |
| | uilding is comprised of : G+2. | | | | | | | | |
| | | pe of Occupancy : Education | | | | | | | |
| 4. T | | | | chool was running or | | | | | |
| | | | ors). | Building was alread | ly grou | and plus two | | | |
| 5 D | | floors. | 040 | 02 2007 | | | | | |
| | AND | : F6/MS/DFS/2007/685, Dated 8.03.2007. | | | | | | | |
| | Fire Safety direction letter No : Nil. Date of Inspection : 31.08.2016. | | | | | | | | |
| 8. N. | ame of the Inspecting Officers: : Vedpa | | | | | | | | |
| | ame and designation of Officer | | | | | | | | |
| | | wan Vats (Owner/Pr | incip | oal) | | | | | |
| | ear of Construction :1997. | | | | | | | | |
| Particular transport and the same | - ^ -,* | dated 06.08.16. | | | 1 - | | | | |
| S.N | Minimum Standards on fire | | as | Provided at Site | | narks | | | |
| 0 | prevention and fire safety as per | per NBC/BBL | per NBC/BBL | | MR/NMR | | | | |
| | Rule. | | | | | | | | |
| 1 | Access to building | - | | | | | | | |
| | Road width | 9m | 9m | | MR | | | | |
| | Gate width | 5m | | 5m | MR | | | | |
| | Width of internal road | N.A. | | N.A. | N.A | | | | |
| 2 | Number, Width, Type and Arrangem | ent of Exits. | | 1 | 1 | | | | |
| | a. Number of Staircases | | | | | | | | |
| | Upper Floor | 4nos. | 04 | nos. | MR | | | | |
| | Basement | N.A. | N. | | | N.A. | | | |
| | B. Width of Staircases | | | | | 11.7 (. | | | |
| | Upper Floor | 1.5m/75cm | 1 5m/75cm 1 22 1 22 | | 1.22 &1.15m MR | | | | |
| | Basement | | N.A. N.A. | | N.A. | | | | |
| | c. Protection of exits | N.A. N.A. | | | | | | | |
| | Fire check door | | - | | | N.A. | | | |
| | Pressurization | | N.A. N.A. | | N.A. | | | | |
| | e. No. of continuous staircases to | N.A. | N. | | N.A. | | | | |
| | terrace | ⁰ 1no. | 1n | Ο. | MR | | | | |
| | g. Width of Corridor | | | _ | | | | | |
| | h. Door Size | 1.5 m | | | .5 m MR | | | | |
| | 1 m 1 m | | | | MR | | | | |
| 3 | Compartmentation | | | | | | | | |
| | Fire check door | N.A. | N.A. | | N.A. | | | | |
| | Sealing of electrical shafts | N.A. | | N.A. | N.A | | | | |
| | Fire rating of shaft door | N.A. | | N.A. | N.A | | | | |
| | `Water curtain | N.A. | | N.A. | N.A | | | | |
| | Fire Dampers | | | | | | | | |
| 1 | Smoke Managament Court | N.A. | | N.A. | N.A. | | | | |
| 4 | Smoke Management System. | 00 / | | N. A. | T | | | | |
| | Basement | 30a/c per hour | | N.A. | N.A. | | | | |
| | Upper floor | 12 a/c per hour | | N.A. | N.A. | | | | |
| 5. Fire Extinguisher | | | | | | | | | |
| | Total numbers | 12nos. | | | | MR - | | | |
| | types | CO ₂ & ABC | | CO ₂ , ABC & WCC |)2 | MR | | | |
| | IS marking | ISI marked | | ISI marked | | MR | | | |
| 6 | First-aid-Hose Reels. | | | | | | | | |
| | Total numbers of each floor | 02nos. | | 02nos. MR. | | | | | |
| | Length of hose reel hose | 30m | | Provided MR. | | | | | |
| | Nozzle diameter | 5cm | | | | | | | |
| 7 | | | | Tovided | | MR. | | | |
| 1 | | etection and alarming system. | | | | | | | |
| | Type of detectors | | N.A. N.A. | | | N.A. | | | |
| | Location of main panel | N.A. | | N.A. N.A. | | | | | |
| | Location of repeater panel | N.A. | 7/17 | N.A. | N.A. | | | | |
| | Alternate source of power | N.I. A | | | | | | | |

| 8 | MOEFA | N.A. | N.A. | N. | A | | | |
|----------|--|-----------------------|--------------|----------|---------|--|--|--|
| 9 | Public address System. | N.A. | N.A. | | N.A. | | | |
| 10 | Automatic Sprinkler System. | | | | | | | |
| | Basement | N.A. | N.A. | N. | A | | | |
| | upper floor | N.A. | N.A. | N. | | | | |
| | stage of auditorium | N.A. | N.A. | N. | | | | |
| 11 | Internal Hydrants | | IN.A. | IV. | Α. | | | |
| | size of down-comer | N.A. | N.A. | NI | Λ | | | |
| | Number of hydrants per floor | N.A. | N.A. | N. | | | | |
| | Hose Box | N.A. | N.A. | | | | | |
| 12 | Yard Hydrants. | N.A. N.A. | | | | | | |
| | Total number of hydrants | N.A. | N.A. | N.I. | ^ | | | |
| | Hose Box | N.A. | N.A. | N./ | | | | |
| 13 | Pumping Arrangements. | IV.A. | N.A. | N:A | ٧. | | | |
| | Ground Level | N.A. | N.A. | | | | | |
| | Discharge of main Pump | N.A. | N.A. | | N.A. | | | |
| | Head of Main Pump | N.A. | | 100 | N.A. | | | |
| | Number of main pumps | har of main numes | | | N.A. | | | |
| | Jockey pump out put | N.A. | N.A. | | N.A. | | | |
| | Jockey pump head | N.A. | N.A. | | N.A. | | | |
| | Standby pump out put | N.A. | N.A. | | N.A. | | | |
| | Standby pump Head | N.A. | N.A. | | N.A. | | | |
| | Auto Starting /Manual | N.A. | N.A. | | N.A. | | | |
| | stopping | IND C | IN.A. | | N.A. | | | |
| | Pump House Access | N.A. | N.A. | | N.A. | | | |
| | For Terrace Level | 01no. | 01no. | | MR. | | | |
| | Discharge of pump | 450LPM | 450LPM | | MR. | | | |
| | Head of the Pump | 40m | 40m | | MR. | | | |
| | Power supplyAuto Starting of pump | Required | Provided | | MR. | | | |
| | Auto Starting of pump | Required | Provided | 2 | MR. | | | |
| 14 | Captive Water Storage for Fire Fight | | | | 1711 (. | | | |
| | Underground tank capacity | N.A. | NI A | | | | | |
| | Draw-off connection | N.A. | N.A. | | N.A. | | | |
| | Fire service inlet | N.A. | N.A. | | N.A. | | | |
| | Access to tank | | N.A. | | N.A. | | | |
| | Overhead Tank capacity | nk capacity N.A. N.A. | | | N.A. | | | |
| 15 | Exit Signage. | 10000 liters | 10000 liters | | MR. | | | |
| 16 | Provision of Lifts. | Required | Provided MR. | | | | | |
| 10 | Pressurization of Lift Shaft | N.A. | NΙΛ | . | | | | |
| | Pressurization of Lift lobby | N.A. | N.A. | N.A | | | | |
| | Communication in lift car | | | N.A | | | | |
| | Firemen's grounding switch | N.A. | N.A. | N.A. | | | | |
| | Lift Signage | N.A. | N.A. | N.A. | | | | |
| 17 | | N.A. | N.A. | N.A. | | | | |
| 18 | Standby power supply | N.A. | N.A. | N.A. | | | | |
| 10 | Refuge Area. Total area | NI A | | | | | | |
| | Location | N.A. | N.A. | N.A. | | | | |
| 10 | | N.A. | N.A. | N.A. | .A. | | | |
| 19 | Fire Control Room | | | | | | | |
| | Detector system panel | N.A. | N.A. | N.A. | | | | |
| | Flow switch panel | N.A. | N.A. | N.A. | N.A. | | | |
| | PA system panel Batter backup | N.A. | N.A. N., | | Α. | | | |
| | Building Floor Plans | N.A. | N.A. | N.A. | | | | |
| | Danding Floor Flams | N.A. | N.A. | N.A. | | | | |
| July Jak | | | 1 | | | | | |

09

Heera Public School, Samalka, Gurgaon Road, New Delhi-110037.

20 Special Fire Protection systems for N.A. N.A. N.A. N.A. N.A.

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Accordingly DFA is put up for kind consideration please.

Signature of the Inspecting Officer

Name: Vedpal

Designation: ADO

SEALICE STATES

Dy CFO(52)

CPO (STI

dans 215