GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F.6/DFS/MS/2016/ school/w2/ 1396

Dated: 09/09 /2016

FIRE SAFETY CERTIFICATE

One block, Ground + Three upper floors owned/occupied by that Govt. Co-ed Sarvodaya Vidyalaya was issued fire safety certificate vide letter no. F.6/DFS/MS/2013/School/63 dated 14/03/2013. The premises was re-inspected by the officer from this department on dated 26/08/2016 in the presence of Dr. Suresh Kumar (Vice Principal) and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition. The premises have therefore deem complied with the requirements of NBC Part IV and the building / premise is fit for occupancy under Education Class with effect from Og / Dg / 2016 for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

Issued on _______ at New Delhi by

Chief Fire Officer Ph: 011-26189168

Copy to:

- 1. The Principal, Govt. Co-ed Sarvodaya Vidyalaya, Sector, B-4, Narela, Delhi-40
- 2. The Director of Education, Old Secretariat, Delhi.

INSPECTION REPORT

One block

Ground + Three upper floor

1. Name & address of the building: Govt. Co-ed Sarvodaya Vidyalaya, Sector, B-4, Narela,

Delhi-110040

2. Type of Occupancy

: Educational

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F.6/DFS/MS/2013/School/63 dated 14/03/2013

5. Fire Safety directives letter No : F.6/DFS/MS/BP/2002/407 dated 11/03/2002

6. Date of inspection

: 26/08/2016

7. Name of the Inspecting Officers: ADO (BW)

8. Name and designation of officers

from the building side

: Dr. Suresh Kumar (Vice Principal)

9. Year of Construction

: 2006

10. Applicant's letter No.

: 1183

dated 09/08/2016

Plot Area: 16042 m2

Covered Area:4671 m2

No. of Students:840

NO. of Class

		Rooms: $32 + 07$ room for other purpose and 4 la					
S. No.	1	Minimum Standards on fire evention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR		
	Acces	s to building					
	•	Road width	12.0 mtr	Provided	MR		
	•	Gate width	5.0 mtr	Provided	MR		
	•	Width of internal road	6.0 mtr	Provided	MR		
)	Number, Width, Type & Arrangement of Exits						
	a. Nur	nber of staircases	03	03	MR		
	•	Upper Floors	03	03	MR		
	•	Basements	N/A	N/A	N/A		
	b. Wie	dth of staircases	N/A	N/A	N/A		
			1.50 mtr each	1.50 mtr each	MR		
	٠,	Upper Floors	N/A	N/A	N/A		
	•	Basements	N/A	N/A	N/A		
	c. Pro	tection of exits	N/A	N/A	N/A		
	•	Fire check door	N/A	N/A	N/A		
	•	Pressurization					
	e. No.	of continuous staircases to terrace	02	02	MR		
	g. Wie	dth of Corridor	Required	2.34 mtr	MR		
	h. Do	or Size	1.00 mtr	1.10 mtr Double Door	MR		

H-12

Govt. Co-ed Sarvodaya Vidyalaya, Sector, B-4, Narela, Delh.

3	Compartmentation.	_				
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	• Upper floors	12 a/c per hour	N/A	N/A		
5	Fire Extinguishers					
	Total numbers	21 ABC	21	MR		
	• Types		ABC	MR		
	• IS marking	ISI marked	Yes	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	Two	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	N/A	N/A	N/A		
9	Public Address System.	N/A	N/A	N/A		
10	Automatic Sprinkler System.					
	Basement	N/A	N/A	N/A		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	100 mm	Provided	MR		
	 Number of hydrants per floor 	02	Provided	MR		
	Hose Box	Required	Provided	MR		

Lum

		Yard Hydrants.	N/A	N/A	N/A
	• "	Total number of hydrants	N/A	N/A	N/A
	•	Hose Box	N/A		
P	umpii	ng Arrangements.	· · · · · · · · · · · · · · · · · · ·	N/A	N/A
+		Ground Level	N/A	N/A	N/A
		Discharge of main Pump	N/A		
	Service Control	> Head of Main pump	N/A	N/A	N/A
	and the same of th	Service numps	N/A	N/A	N/A
			N/A	N/A	N/A
	oog en all on a series	> Jockey Pump out put	N/A	N/A	N/A
	a constant	> Jockey pump head	N/A	N/A	N/A
		Standby Pump out put		N/A	N/A
		> Standby Pump Head	N/A		N/A
		> Auto Starting/ Manual	N/A	N/A	Win Grant Committee Commit
		stopping	N/A	N/A	N/A
		> Pump House Access	N/A	N/A	N/A
	•	Terrace level	2 X 1620 LPM	Provided	MR
		Discharge of pump	40 m	Provided	MR
1		> Head of the pump	N/A	N/A	N/A
		> Power Supply	Required	Provided	MR
		> Auto Starting of pump			
4	Capt	ive Water Storage for fire fighting) (D	
		Underground tank capacity	50,000 ltr	Provided	MR
	•		N/A	N/A	N/A
	>		N/A	N/A	N/A
	2			N/A	N/A
	7	Access to tank	N/A	N A	MR
		Overhead Tank capacity	10,000 ltr	Provided	**
			Required	Provided	MR
15	2	Signage.	,		i.e.
16	Pro	vision of Lifts.	>1/A	N/A	N/A
	•	Pressurization of Lift Shaft	N/A	N/A	N/A
		Pressurization of Lift lobby	N/A		N/A
		Communication In lift Car	N/A	N/A	
	•		N/A	N/A	N/A
	•	Fireman's Grounding Switch	N/A	N/A	N/A
	•	Lift Signage		N/A	N/A
17	Sta	andby power supply	N/A	1 1/1 %	

Ah Shus

Govt. Co-ed Sarvodaya Vidyalaya, Sector, B-4, Narela, Delhi-40

18	Refuge Area.			,
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19				
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2013/School/63 dated 14/03/2013. Renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name

Designation

Designation

4DO(BW)

Dyce (W2)

180/k